


FEATURES

- Direct Modulation Laser for WDM systems
- Optimized for Long Distance Transmission (Dispersion 1800ps/nm)
- Peak wavelength 1527.99 to 1563.05nm (C-band: 191.8 to 196.2THz, 100GHz spacing)
- Output Power: 10mW
- 14-pin Butterfly type package
- Built-in Optical Isolator, Power Monitor PIN-PD, Thermistor, and Cooler
- Single Mode Fiber



APPLICATIONS

This laser is intended for the application of 2.5 Gb/s long haul Dense Wavelength Division Multiplexing (DWDM). Transmission spans of 100 km (1800ps/nm) are possible.

DESCRIPTION

The laser is a high power laser capable of 2.5 Gb/s transmission. It is packaged in a “butterfly” type module. The module employs a high efficiency optical coupling system, coupling the laser output through a built-in optical isolator into a single mode fiber pigtail. The module also includes a monitor photodiode, a thermoelectric cooler (TEC), and thermistor. This device is designed for use in DWDM direct modulation transmission systems. Selected wavelengths specified to the ITU-T grid are available.

ABSOLUTE MAXIMUM RATINGS (T_C=25°C, unless otherwise specified)

| Parameter | Symbol | Condition | Ratings | | Unit |
|----------------------------------|-------------------|---------------|---------|------|------|
| | | | Min. | Max. | |
| Storage Temperature | T _{stg} | - | -40 | +85 | °C |
| Operating Case Temperature | T _{op} | - | -20 | +70 | °C |
| Optical Output Power | P _f | CW | - | 12 | mW |
| LD Forward Current | I _F | CW | - | 150 | mA |
| LD Reverse Voltage | V _R | - | - | 2 | V |
| PD Reverse Voltage | V _{DR} | - | - | 20 | V |
| PD Forward Current | I _{PF} | - | - | 10 | mA |
| Cooler Voltage | V _c | Cooling | - | 2.5 | V |
| | | Heating | -2.5 | - | |
| Cooler Current | I _c | Cooling | - | 1.4 | A |
| | | Heating | -0.9 | - | |
| Thermistor Temperature | T _{th} | ATC Operation | -20 | +70 | °C |
| Lead Soldering Time | T _{sold} | 260°C | - | 10 | sec |
| Environmental Operating Humidity | X _{op} | Top<30°C | - | 95 | % |
| Environmental Storage Humidity | X _{st} | Tstg<30°C | - | 95 | % |

OPTICAL AND ELECTRICAL CHARACTERISTICS (T_L=T_{set}, T_C=25°C, BOL, unless otherwise specified)

| Parameter | Symbol | Test Conditions | Limits | | | Unit |
|--|---------------------------------|--|----------|------|-------|-------|
| | | | Min. | Typ. | Max. | |
| Laser Set Temperature | T _{set} | - | 20 | - | 35 | °C |
| Threshold Current | I _{th} | CW | 4 | - | 40 | mA |
| Forward Voltage | V _{FDC} | CW, I _F =30 mA, pin 12, 13 | - | 1.6 | 1.75 | V |
| Series Resistance | R _S | CW, pin 12, 13 | 22 | 25 | 28 | Ω |
| Optical Output Power | P _f | CW | 10.0 | - | - | mW |
| Slope Efficiency | η | CW, P _f =10mW | 0.14 | - | - | mW/mA |
| Threshold Power | P _{th} | I _F =I _{th} , CW | - | - | 150 | μW |
| Tracking Error (Note 1) | TE | P _f =10mW, T _C =-20 to 70°C, I _m -APC | -0.5 | - | +0.5 | dB |
| Monitor Current | I _m | CW, P _f =10mW, V _{DR} =5V | 0.25 | - | 2.5 | mA |
| Photodiode Dark Current | I _D | V _{DR} =5V | - | 2 | 100 | nA |
| Photodiode Capacitance | C _t | V _{DR} =5V, f=1 MHz | - | - | 10 | pF |
| Photodiode Cutoff Frequency | f _{cm} | V _{DR} =5V, 50Ω load | 100 | - | - | MHz |
| Peak Wavelength | λ _p | Note (2) | Note (4) | | | nm |
| Wavelength Drift (after 20 yrs) | Δλ | Note (2) | -100 | - | +100 | pm |
| Wavelength Stability with Case Temperature | dλ/dT _C | T _C =-20 to 70°C | -1.0 | - | +1.0 | pm/°C |
| Side Mode Suppression | S _r | Note (2) | 35 | 40 | - | dB |
| Spectral Width (-20dB) | δλ | Note (2) | - | - | 0.5 | nm |
| Rise/Fall Time | T _r , T _f | 20% to 80% | - | - | 0.125 | nsec |
| Cutoff Frequency | f _c | P _f =10mW, -3 dB | 3.5 | - | - | GHz |
| RF Return Loss | S ₁₁ | f=50 MHz ~ 2 GHz | 8 | - | - | dB |
| | | f=2 GHz ~ 3 GHz | 6 | - | - | dB |
| | | f=3 GHz ~ 5 GHz | 3 | - | - | dB |
| Optical Isolation | I _S | T _C =-20 to 70°C | 25 | 35 | - | dB |
| Relative Intensity Noise | RIN | f=2.5 GHz P _f =10 mW, ORL=24 dB | - | - | -140 | dB/Hz |
| Kink | K _{ns} | up to 12mW | No Kink | | | - |
| Dispersion Penalty | dP | Note (3) | - | - | 2.0 | dB |

Note 1. TE=10*log(pf(Tcase)/Pf(Tc=25°C))(dB)

Note 2. 2.5 Gb/s NRZ, P_{peak}=10.0mW, R_{ext}=8.2dB, PRBS=2²³-1,

Note 3. Bit rate=2.48832 Gb/s, PRBS=2²³-1, Dispersion=1,800 ps/nm, P_{peak}=10mW, R_{ext}=8.2dB

Decision point: Center of Back-to-Back at 10⁻⁹, No Floor,

Receiver: Eudyna Standard Receiver

Note 4. The selected wavelengths available are listed in Fig. 8

TEC AND THERMISTOR CHARACTERISTICS ($T_L=T_{set}$, $T_C=25^\circ\text{C}$, BOL, unless otherwise specified)

| Parameter | Symbol | Test Conditions | Limit | | | Unit |
|-----------------------|--------|---|-------|-------|-------|------------------|
| | | | Min. | Typ. | Max. | |
| Cooler Current | I_C | $T_L=T_{set}$, $P_f=10\text{mW}$, $T_C=70^\circ\text{C}$ | - | - | 1.0 | A |
| Cooler Voltage | V_C | | - | - | 2.4 | V |
| Cooler Power | P_C | | - | - | 2.4 | W |
| Thermistor Resistance | Rtr | $T_L=25^\circ\text{C}$ | 9.5 | 10.0 | 10.5 | $\text{k}\Omega$ |
| Thermistor B Constant | B | | 3,270 | 3,450 | 3,630 | K |

Fig. 1 Forward Current vs Output Power




Fig. 2 Frequency Response




Fig. 3 RF Return Loss




Fig. 4 Cooler Voltage -Current




Fig. 5 Spectrum




Fig. 6 Temperature Dependence of Wavelength (ACC Operation)




Fig. 7 Transmission Characteristics





Fig. 8 Wavelength Table

| Part Number | Wavelength (nm) (TL=Tset) (in vacuum) | Tolerance (nm) |
|-----------------|---|----------------|
| FLD5F15CX-J9620 | 1527.99 | ±0.1 |
| -J9610 | 1528.77 | ±0.1 |
| -J9600 | 1529.55 | ±0.1 |
| -J9590 | 1530.33 | ±0.1 |
| -J9580 | 1531.12 | ±0.1 |
| -J9570 | 1531.90 | ±0.1 |
| -J9560 | 1532.68 | ±0.1 |
| -J9550 | 1533.47 | ±0.1 |
| -J9540 | 1534.25 | ±0.1 |
| -J9530 | 1535.04 | ±0.1 |
| -J9520 | 1535.82 | ±0.1 |
| -J9510 | 1536.61 | ±0.1 |
| -J9500 | 1537.40 | ±0.1 |
| -J9490 | 1538.19 | ±0.1 |
| -J9480 | 1538.98 | ±0.1 |
| -J9470 | 1539.77 | ±0.1 |
| -J9460 | 1540.56 | ±0.1 |
| -J9450 | 1541.35 | ±0.1 |
| -J9440 | 1542.14 | ±0.1 |
| -J9430 | 1542.94 | ±0.1 |
| -J9420 | 1543.73 | ±0.1 |

| | | |
|--------|---------|------|
| -J9410 | 1544.53 | ±0.1 |
| -J9400 | 1545.32 | ±0.1 |
| -J9390 | 1546.12 | ±0.1 |
| -J9380 | 1546.92 | ±0.1 |
| -J9370 | 1547.72 | ±0.1 |
| -J9360 | 1548.51 | ±0.1 |
| -J9350 | 1549.32 | ±0.1 |
| -J9340 | 1550.12 | ±0.1 |
| -J9330 | 1550.92 | ±0.1 |
| -J9320 | 1551.72 | ±0.1 |
| -J9310 | 1552.52 | ±0.1 |
| -J9300 | 1553.33 | ±0.1 |
| -J9290 | 1554.13 | ±0.1 |
| -J9280 | 1554.94 | ±0.1 |
| -J9270 | 1555.75 | ±0.1 |
| -J9260 | 1556.55 | ±0.1 |
| -J9250 | 1557.36 | ±0.1 |
| -9240 | 1558.17 | ±0.1 |
| -J9230 | 1558.98 | ±0.1 |
| -J9220 | 1559.79 | ±0.1 |
| -J9210 | 1560.61 | ±0.1 |
| -J9200 | 1561.42 | ±0.1 |
| -J9190 | 1562.23 | ±0.1 |
| -J9180 | 1563.05 | ±0.1 |



For further information please contact:

Eudyna Devices USA Inc.

2355 Zanker Rd.
 San Jose, CA 95131-1138, U.S.A.
 TEL: (408) 232-9500
 FAX: (408) 428-9111
www.us.eudyna.com

Eudyna Devices Europe Ltd.

Network House
 Norreys Drive
 Maidenhead, Berkshire SL6 4FJ
 United Kingdom
 TEL: +44 (0) 1628 504800
 FAX: +44 (0) 1628 504888

Eudyna Devices Asia Pte Ltd.

Hong Kong Branch
 Rm. 1101, Ocean Centre, 5 Canton Rd.
 Tsim Sha Tsui, Kowloon, Hong Kong
 TEL: +852-2377-0227
 FAX: +852-2377-3921

Eudyna Devices Inc.

Sales Division
 1, Kanai-cho, Sakae-ku
 Yokohama, 244-0845, Japan
 TEL: +81-45-853-8156
 FAX: +81-45-853-8170

CAUTION

Eudyna Devices Inc. products contain **gallium arsenide (GaAs)** which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- Do not put this product into the mouth.
- Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.
- Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.

Eudyna Devices Inc. reserves the right to change products and specifications without notice. The information does not convey any license under rights of Eudyna Devices Inc. or others.

© 2004 Eudyna Devices USA Inc.
 Printed in U.S.A.