

## GaAs N-channel Dual-Gate MES FET

### Description:

The 3SK148 is a GaAs N-channel Dual-Gate MES FET for low noise UHF amplifiers and mixers. Low noise and high gain characteristics are accomplished by optimum mask pattern designing. Easier high frequency circuits adjustments are made possible by the miniaturized plastic molded package which contributes to reduce parasitic elements of the device.

### Features:



Low NF: NF = 1.2 dB (typ.) at 800MHz  
 High PG: PG = 20 dB (typ.) at 800MHz  
 High Stability

### Applications:

- UHF Amplifier, mixer, oscillator

### Absolute Maximum Ratings: (Ta = 25°C)

- Drain to Source Voltage: Vdsx 8 V
- Gate 1 to Source Voltage: Vg1s -6 V
- Gate 2 to Source Voltage: Vg2s -6 V
- Drain Current: Id 80 mA
- Power Dissipation: Pch 150 mW
- Channel Temperature: Tch +150 °C
- Storage Temperature: Tstg -55 ~ +150 °C




### Electrical Characteristics: (Ta = 25°C)


| Parameter                | Symbol | Condition  | Min. | Typ. | Max. | Unit |
|--------------------------|--------|--|------|------|------|------|
| Drain to Source Voltage  | Vdsx   | Id = 100µA<br>Vg1s = 8<br>Vg2s = -5V               | 8    |      |      | V    |
| Gate 1 Cutoff Current    | Ig1ss  | Vg1s = -4V<br>Vg2s = 0V<br>Vds = 0V                | -10  |      |      | µA   |
| Gate 2 Cutoff Current    | Ig2ss  | Vg2s = -4V<br>Vg1s = 0V<br>Vds = 0V                | -10  |      |      | µA   |
| Drain Saturation Current | Idss   | Vds = 5V<br>Vg1s = 0V<br>Vg2s = 0V                 | 30   |      | 80   | mA   |
| Gate 1 Pinchoff Voltage  | Vp1    | Vds = 5V<br>Id = 100µA<br>Vg2s = 0V                | -4   |      | -1   | V    |
| Gate 2 Pinchoff Voltage  | Vp2    | Vds = 5V<br>Id = 100µA<br>Vg1s = 0V                | -4   |      | -1   | V    |
| Transconductance         | gm     | Vds = 5V<br>Id = 10mA<br>Vg2s = 1.5V<br>f = 1KHz   | 15   | 22   |      | mS   |
| Input Capacitance        | Ciss   | Vds = 5V<br>Id = 10mA<br>Vg2s = 1.5V<br>f = 1MHz   |      | 0.5  | 1.0  | PF   |
| Feedback Capacitance     | Crss   |  |      | 7.5  | 25   | fF   |
| Power Gain               | PG     | Vds = 5V<br>Id = 10mA<br>Vg2s = 1.5V<br>f = 800MHz | 16   | 20   |      | dB   |
| Noise Figure             | NF     |  |      | 1.2  | 2.0  | dB   |

The specifications are subject to change without notice.


Output Characteristics: ( $T_a = 25^\circ\text{C}$ ,  $V_{g2s} = 1.5\text{V}$ ,  $V_{g1s} = -0.5\text{V/step}$ )





NF, Ga Frequency Dependence: ( $V_{ds} = 5.0\text{V}$ ,  $V_{g2s} = 1.5\text{V}$ ,  $I_{ds} = 10\text{mA}$ )



NF- $I_d$  Characteristics: ( $V_{ds} = 5.0\text{V}$ ,  $V_{g2s} = 1.5\text{V}$ , Frequency at 450MHz)




**S-Parameters vs. Frequency Characteristics:** ( $V_{ds} = 5.0V$ ,  $V_{g2s} = 1.5V$ ,  $I_{ds} = 10mA$ )




**S-Parameter Data of FET 3SK148 (50.0 Ohm reference)**

| Frequency<br>MHz | S11  |        | S21   |        | S12    |        | S22  |        |
|------------------|------|--------|-------|--------|--------|--------|------|--------|
|                  | MAG  | ANG    | MAG   | ANG    | MAG    | ANG    | MAG  | ANG    |
| 100              | .999 | -1.60  | 2.065 | 177.40 | 0.0011 | 88.48  | .961 | -.77   |
| 200              | .998 | -2.97  | 2.044 | 172.69 | 0.0021 | 93.67  | .961 | -1.85  |
| 300              | .999 | -4.28  | 2.180 | 169.86 | 0.0023 | 105.04 | .971 | -2.98  |
| 400              | .993 | -5.70  | 2.077 | 170.12 | 0.0049 | 89.67  | .958 | -3.51  |
| 500              | .989 | -6.98  | 1.981 | 167.14 | 0.0054 | 83.41  | .958 | -4.17  |
| 600              | .979 | -8.16  | 1.999 | 161.04 | 0.0068 | 83.94  | .960 | -5.09  |
| 700              | .969 | -9.57  | 2.004 | 160.63 | 0.0082 | 83.47  | .955 | -5.68  |
| 800              | .958 | -10.84 | 1.957 | 159.23 | 0.0084 | 82.97  | .955 | -6.83  |
| 900              | .948 | -12.16 | 1.856 | 153.88 | 0.0091 | 79.56  | .948 | -7.22  |
| 1000             | .938 | -13.23 | 1.938 | 150.58 | 0.0106 | 78.17  | .949 | -8.58  |
| 1200             | .912 | -15.27 | 1.789 | 147.43 | 0.0131 | 79.92  | .941 | -10.37 |
| 1400             | .877 | -17.11 | 1.823 | 139.04 | 0.0151 | 74.26  | .936 | -12.06 |
| 1600             | .841 | -19.12 | 1.700 | 137.04 | 0.0156 | 78.12  | .935 | -13.26 |
| 1800             | .805 | -21.04 | 1.704 | 132.09 | 0.0171 | 77.47  | .928 | -13.91 |
| 2000             | .756 | -22.32 | 1.448 | 126.14 | 0.0176 | 76.07  | .922 | -14.46 |

**Noise Figure Characteristics: (Vds = 5.0V, Vg2s = 1.5V, Ids = 10mA)**  
 at 450MHz at 880MHz




Vds = 5.0V  
 Vg2s = 1.5V  
 Ids = 10mA  
 Frequency 450 MHz  
 NF min 0.50 dB  
 Ga 23.83 dB  
 Gamma (S); Mag 0.799 Ang 7.78°  
 Gamma (L); Mag 0.887 Ang 7.31°



Vds = 5.0V  
 Vg2s = 1.5V  
 Ids = 10mA  
 Frequency 880 MHz  
 NF min 0.86 dB  
 Ga 23.70 dB  
 Gamma (S); Mag 0.771, Ang 25.07°  
 Gamma (L); Mag 0.830, Ang 21.84°

at 2000MHz



| Frequency (MHz) | Ga (dB) | NF (dB) | Gamma- S |        | Gamma- L |        |
|-----------------|---------|---------|----------|--------|----------|--------|
|                 |         |         | (Mag.)   | (Ang.) | (Mag.)   | (Ang.) |
| 400             | 23.54   | 0.59    | 0.824    | 3.16°  | 0.910    | 8.75°  |
| 450             | 23.83   | 0.50    | 0.799    | 7.78°  | 0.887    | 7.31°  |
| 500             | 22.79   | 0.47    | 0.792    | 12.03° | 0.848    | 14.56° |
| 880             | 23.70   | 0.86    | 0.771    | 25.07° | 0.830    | 21.84° |
| 2000            | 12.92   | 1.60    | 0.643    | 78.48° | 0.559    | 46.00° |

Vds = 5.0V  
 Vg2s = 1.5V  
 Ids = 10mA  
 Frequency 2000 MHz  
 NF min 1.60 dB  
 Ga 12.91 dB  
 Gamma (S); Mag 0.643, Ang 78.48°  
 Gamma (L); Mag 0.559, Ang 46.00°



Sony Component Products Division  
 West Coast Main Office: 23430 Hawthorne Blvd., Suite No. 330, Torrance, California 90505 213-373-9425  
 Northwest Office: 1359 Old Oakland Road, San Jose, California 95112 408-280-0111  
 East Coast Office: 15 Essex Road, Paramus, New Jersey 07653 201-368-5020

This datasheet has been downloaded from:

[www.DatasheetCatalog.com](http://www.DatasheetCatalog.com)

Datasheets for electronic components.