



SPEC. NO	
ISSUED DATE	

CUSTOMER	:	
M O D E L	:	OGM-128GS24Y-1-C4021
DESCRIPTION	:	LCD MODULE

THIS SPECIFICATION IS APPLIED FOR LCD MODULE DELIVERED TO YOUR COMPANY BY ORION DISPLAY TECHNOLOGY CO., LTD


◆ CUSTOMER APPROVAL

	CHECKED	CHECKED	APPROVAL
APPROVAL			
REMARK			

◆ SUPPLIER APPROVAL

PREPARED	CHECKED		APPROVAL

ADDRESS : ORION DISPLAY TECHNOLOGY CO., LTD
257 3, GONGDAN DONG, GUMI, KYUNG BUK, KOREA
(TEL) 82 546 467 5420~9 (FAX) 82 546 462 2496


	LCD MODULE SPECIFICATION	ISSUED DATE	
	FOR APPROVAL	REV. NO.	0
	OGM-128GS24Y-1-C4021	PAGE	3 OF 12

CONTENTS

1. FEATURES -----	4
2. MECHANICAL SPECIFICATION -----	4
3. ABSOLUTE MAXIMUM RATINGS -----	5
4. ELECTRICAL CHARACTERISTICS -----	5
5. ELECTRO OPTICAL CHARACTERISTICS	6
6. QUALITY SPECIFICATION	7
7. RELIABILITY -----	10
8. PIN CONNECTIONS -----	10
9. PRECAUTION FOR USING -----	11
10. EXTERNAL DIMENSION-----	12

NOTE: When using this specification, the reader should keep the followings in mind.

1. This specification may, wholly or partially, be subjected to change without notice.
2. Information contained herein is proprietary information of ORION DISPLAY TECHNOLOGY CO.,LTD. The dissemination use or duplication for any purpose other than for which the information is provided is prohibited by ORION DISPLAY TECHNOLOGY CO., LTD except by express permission.

	LCD MODULE SPECIFICATION FOR APPROVAL	ISSUED DATE	
	OGM-128GS24Y-1-C4021	REV. NO.	0
		PAGE	4 OF 12

1. FEATURES

1) Number of dot	240 x 128 dots
2) Display mode	STN GREY
3) Display type	Transflective, Positive
4) Viewing direction	6 o'clock
5) Operating temperature	Indoor
6) Driving voltage	Double power
7) Driving method	1/128 duty
8) Type	QFP (Quad Flat Package)
9) Number of data line	8 bit parallel
10) Applicated IC	T6963C or equivalent
11) Backlighting	CCFL. (Emitting color : White)

2. MECHANICAL DATA

ITEM		WIDTH	HEIGHT	THICKNESS	UNIT
Module size		170.0	105.0	14.0	mm
Viewing area		126.0	70.0		mm
Dot	Size	0.47	0.47		mm
	Pitch				