

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:


The **ASI BLW33** is Designed for Television, Transmitters, and transposers Applications up to 860 MHz.

FEATURES:

- Common Emitter
- $P_G = 10$ dB at 1.0 W/ 860 MHz
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	1.25 A
V_{CES}	50 V
V_{CEO}	30 V
V_{EBO}	4.0 V
P_{DISS}	19.4 W @ $T_C = 25^\circ C$
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	9.0 °C/W

PACKAGE STYLE .280 4L STUD


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	1.010 / 25.65	1.055 / 26.80
B	.220 / 5.59	.230 / 5.84
C	.270 / 6.86	.285 / 7.24
D	.003 / 0.08	.007 / 0.18
E	.117 / 2.97	.137 / 3.48
F	.572 / 14.53	
G	.130 / 3.30	
H	.245 / 6.22	.255 / 6.48
I	.640 / 16.26	
J	.175 / 4.45	.217 / 5.51
K	.275 / 6.99	.285 / 7.24

ORDER CODE: ASI10500
CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CES}	$I_C = 4.0$ mA	50			V
BV_{CEO}	$I_C = 30$ mA	30			V
BV_{EBO}	$I_E = 2.0$ mA	4.0			V
I_{CES}	$V_{CE} = 30$ V			2.5	mA
h_{FE}	$V_{CE} = 25$ V $I_C = 300$ mA	20	40	120	---
P_G	$V_{CE} = 25$ V $I_C = 300$ mA $f = 860$ MHz	10			dB
IMD_1	$P_{OUT} = 1.0$ W	-60			dBc