



STL100NH3LL

N-channel 30V - 0.0032Ω - 25A - PowerFLAT™ (6x5)
STripFET™ III Power MOSFET

General features

| Type | V _{DSS} | R _{DS(on)} | I _D |
|-------------|------------------|---------------------|--------------------|
| STL100NH3LL | 30V | <0.0035Ω | 25A ⁽¹⁾ |

1. The value is rated according R_{thj-pcb}


- Improved die-to-footprint ratio
- Very low profile package (1mm max)
- Very low thermal resistance
- Conduction losses reduced
- Switching losses reduced

Description

This series utilizes the last advanced design rules of ST's proprietary STripFET™ technology. This process complete to unique metallization technique realised the most advanced low voltage Power MOSFET in PowerFLAT™(6x5). The Chip-scaled PowerFLAT™ package allows a significant board space saving, still boosting the performance.

Applications

- Switching application




Description

This series utilizes the last advanced design rules of ST's proprietary STripFET™ technology. This process complete to unique metallization technique realised the most advanced low voltage Power MOSFET in PowerFLAT™(6x5). The Chip-scaled PowerFLAT™ package allows a significant board space saving, still boosting the performance.

Applications

- Switching application

Internal schematic diagram



Order codes

| Part number | Marking | Package | Packaging |
|-------------|-----------|------------------|-------------|
| STL100NH3LL | L100NH3LL | PowerFLAT™ (6x5) | Tape & reel |

Contents

| | | |
|----------|---|-----------|
| 1 | Electrical ratings | 3 |
| 2 | Electrical characteristics | 4 |
| | 2.1 Electrical characteristics (curves) | 6 |
| 3 | Test circuit | 8 |
| 4 | Package mechanical data | 9 |
| 5 | Revision history | 11 |

1 Electrical ratings

Table 1. Absolute maximum ratings

| Symbol | Parameter | Value | Unit |
|--------------------|---|------------|------|
| V_{DS} | Drain-source voltage ($V_{GS} = 0$) | 30 | V |
| $V_{GS}^{(1)}$ | Gate-source voltage | ± 16 | V |
| $V_{GS}^{(2)}$ | Gate-source voltage | ± 18 | V |
| $I_D^{(3)}$ | Drain current (continuous) at $T_C = 25^\circ\text{C}$ | 100 | A |
| $I_D^{(3)}$ | Drain current (continuous) at $T_C = 100^\circ\text{C}$ | 71 | A |
| $I_D^{(5)}$ | Drain current (continuous) at $T_C = 100^\circ\text{C}$ | 15.6 | A |
| $I_{DM}^{(4)}$ | Drain current (pulsed) | 100 | A |
| $I_D^{(5)}$ | Drain current (continuous) at $T_C = 25^\circ\text{C}$ | 25 | A |
| $P_{TOT}^{(3)}$ | Total dissipation at $T_C = 25^\circ\text{C}$ | 80 | W |
| $P_{TOT}^{(5)}$ | Total dissipation at $T_C = 25^\circ\text{C}$ | 4 | W |
| | Derating factor | 0.03 | W/°C |
| T_J T_{stg} | Operating junction temperature Storage temperature | -55 to 150 | °C |

1. Continuous mode
2. Guaranteed for test time $\leq 15\text{ms}$
3. The value is rated according R_{thj-c}
4. Pulse width limited by safe operating area
5. The value is rated according $R_{thj-pcb}$

Table 2. Thermal resistance

| Symbol | Parameter | Value | Unit |
|---------------------|---|-------|------|
| $R_{thj-case}$ | Thermal resistance junction-case (Drain) (steady state) | 1.56 | °C/W |
| $R_{thj-pcb}^{(1)}$ | Thermal resistance junction-ambient | 31.3 | °C/W |

1. When mounted on FR-4 board of 1inch^2 , 2oz Cu, $t < 10\text{sec}$

Table 3. Avalanche data

| Symbol | Parameter | Value | Unit |
|----------|--|-------|------|
| I_{AV} | Not-repetitive avalanche current, (pulse width limited by $T_J \text{ Max}$) | 12.5 | A |
| E_{AS} | Single pulse avalanche energy (starting $T_J = 25^\circ\text{C}$, $I_d = I_{AV}$, $V_{DD} = 24\text{V}$) | 1.3 | J |

2 Electrical characteristics

($T_{CASE}=25^{\circ}C$ unless otherwise specified)

Table 4. On/off states

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---------------|--|--|------|-----------------|-----------------|----------------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage | $I_D = 250\mu A, V_{GS} = 0$ | 30 | | | V |
| I_{DSS} | Zero gate voltage drain current ($V_{GS} = 0$) | $V_{DS} = \text{Max rating},$ $V_{DS} = \text{Max rating} @ 125^{\circ}C$ | | | 1 10 | μA μA |
| I_{GSS} | Gate body leakage current ($V_{DS} = 0$) | $V_{GS} = \pm 16V$ | | | ± 100 | nA |
| $V_{GS(th)}$ | Gate threshold voltage | $V_{DS} = V_{GS}, I_D = 250\mu A$ | 1 | | | V |
| $R_{DS(on)}$ | Static drain-source on resistance | $V_{GS} = 10V, I_D = 12.5A$ $V_{GS} = 4.5V, I_D = 12.5A$ | | 0.0032 0.004 | 0.0035 0.005 | Ω Ω |

Table 5. Dynamic

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|------------------------------|--|------|------|------|----------|
| $g_{fs}^{(1)}$ | Forward transconductance | $V_{DS} = 10V, I_D = 12.5A$ | | 30 | | S |
| C_{iss} | Input capacitance | $V_{DS} = 25V, f = 1 \text{ MHz}, V_{GS} = 0$ | | 4450 | | pF |
| C_{oss} | Output capacitance | | | 655 | | pF |
| C_{rss} | Reverse transfer capacitance | | | 50 | | pF |
| Q_g | Total gate charge | $V_{DD} = 15V, I_D = 25A$ | | 30 | 40 | nC |
| Q_{gs} | Gate-source charge | $V_{GS} = 4.5V$ | | 12.5 | | nC |
| Q_{gd} | Gate-drain charge | (see Figure 7) | | 10 | | nC |
| R_G | Gate input resistance | $f = 1 \text{ MHz}$ Gate DC Bias = 0 Test signal level = 20mV open drain | 1 | 2 | 3 | Ω |

1. Pulsed: pulse duration=300 μs , duty cycle 1.5%

Table 6. Switching times

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|--------------|---------------------|---|------|------|------|------|
| $t_{d(on)}$ | Turn-on delay time | $V_{DD}=15V, I_D=12.5A,$ $R_G=4.7\Omega, V_{GS}=10V$ <i>(see Figure 13)</i> | | 18 | | ns |
| t_r | Rise time | | | 50 | | ns |
| $t_{d(off)}$ | Turn-off delay time | | | 75 | | ns |
| t_f | Fall time | | | 8 | | ns |

Table 7. Source drain diode

| Symbol | Parameter | Test conditions | Min | Typ. | Max | Unit |
|-----------------|-------------------------------|---|-----|------|-----|------|
| I_{SD} | Source-drain current | | | | 25 | A |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) | | | | 100 | A |
| $V_{SD}^{(2)}$ | Forward on voltage | $I_{SD}=25A, V_{GS}=0$ | | | 1.3 | V |
| t_{rr} | Reverse recovery time | $I_{SD}=25A,$ $di/dt = 100A/\mu s,$ $V_{DD}=25V, T_j=150^\circ C$ | | 32 | | ns |
| Q_{rr} | Reverse recovery charge | | | 34 | | nC |
| I_{RRM} | Reverse recovery current | | | 2.1 | | A |

1. Pulse width limited by safe operating area
2. Pulsed: pulse duration=300 μs , duty cycle 1.5%

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Thermal impedance




Figure 3. Output characteristics




Figure 4. Transfer characteristics




Figure 5. Transconductance




Figure 6. Static drain-source on resistance




Figure 7. Gate charge vs gate-source voltage Figure 8. Capacitance variations




Figure 9. Normalized gate threshold voltage vs temperature Figure 10. Normalized on resistance vs temperature





Figure 11. Source-drain diode forward characteristics Figure 12. Normalized $B_{V_{DS}}$ vs temperature



3 Test circuit

Figure 13. Switching times test circuit for resistive load




Figure 14. Gate charge test circuit




Figure 15. Test circuit for inductive load switching and diode recovery times




Figure 16. Unclamped inductive load test circuit




Figure 17. Unclamped inductive waveform





Figure 18. Switching time waveform




4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect . The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com

PowerFLAT™ (6x5) MECHANICAL DATA

| DIM. | mm. | | | inch | | |
|------|------|------|------|-------|--------|--------|
| | MIN. | TYP | MAX. | MIN. | TYP. | MAX. |
| A | 0.80 | 0.83 | 0.93 | 0.031 | 0.032 | 0.036 |
| A1 | | 0.02 | 0.05 | | 0.0007 | 0.0019 |
| A3 | | 0.20 | | | 0.007 | |
| b | 0.35 | 0.40 | 0.47 | 0.013 | 0.015 | 0.018 |
| D | | 5.00 | | | 0.196 | |
| D1 | | 4.75 | | | 0.187 | |
| D2 | 4.15 | 4.20 | 4.25 | 0.163 | 0.165 | 0.167 |
| E | | 6.00 | | | 0.236 | |
| E1 | | 5.75 | | | 0.226 | |
| E2 | 3.43 | 3.48 | 3.53 | 0.135 | 0.137 | 0.139 |
| E4 | 2.58 | 2.63 | 2.68 | | 0.103 | 0.105 |
| e | | 1.27 | | | 0.050 | |
| L | 0.70 | 0.80 | 0.90 | 0.027 | 0.031 | 0.035 |



5 Revision history

Table 8. Revision history

| Date | Revision | Changes |
|-------------|----------|--|
| 18-Apr-2005 | 1 | First Release |
| 20-Jun-2005 | 2 | Updated mechanical data |
| 22-Jun-2005 | 3 | New Rg value on Table 6 |
| 10-Oct-2005 | 4 | Inserted ecopack indication |
| 09-Jan-2006 | 5 | New footprint |
| 08-Mar-2006 | 6 | New template |
| 29-Jun-2006 | 7 | Modified curves, see Figure 1 and Figure 2 |
| 04-Sep-2006 | 8 | The document has been reformatted, no content change |
| 04-Jan-2007 | 9 | New updated on Table 1 |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com