


PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24														
COM	COM	6E	6D	6C	DP6	5E	5D	5C	DP5	4E	4D	4C	DP4	3E	3D	3C	DP3	2E	2D	2C	DP2	1E	1D	1C	1B	1A	1F	1G	2B	2A	2F	2G	COM	3B	3A	3F	3G	COM
PIN	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48														
COM	DP3	2E	2D	2C	DP2	1E	1D	1C	1B	1A	1F	1G	2B	2A	2F	2G	COM	3B	3A	3F	3G	COM	4B	4A	4F	4G	COL2	5B	5A	5F	5G	6B	6A	6F	6G	COM		



NOTES:

1. TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.20
2. VIEWING ANGLE: 12:00 O'CLOCK
3. DISPLAY MODE: POSITIVE, REFLECTIVE, TN TYPE
4. DUTY CYCLE: STATIC
5. DRIVING VOLTAGE: 5.0V
6. OPERATING TEMPERATURE: -30°C TO 85°C
7. STORAGE TEMPERATURE: -40°C TO 90°C

Revision Record		Date	AZ Displays, Inc.		
1	Viewing Angle: 6 o'clock to 12 o'clock	4/18/02	DRAWN BY: W.L.L	TITLE:	SCALE:
2			CHECKED BY: H.L.P		UNIT: mm
3			APP BY:	GD-269P	SIZE: A4
4			DATE: 96.3.22	SHEET 1 OF 1	