


PHOTO COUPLER

PS2043

HIGH SPEED 8PIN PHOTO COUPLER

PACKAGE DIMENSIONS

(Unit: mm)




FEATURES

- High Speed Response  $0.3 \mu s$  TYP.
- High Isolation Voltage  $2500 V_{r.m.s.}$
- Compact, Dual In-Line Package

APPLICATIONS

1. Interface circuit for various instrumentations, control equipments.
2. Computer and peripheral manufactures.
3. TV sets.

PIN CONNECTION



PIN	Function
1.	NC
2.	Anode
3.	Cathode
4.	NC
5.	Emitter
6.	$V_O$
7.	Base
8.	$V_{CC}$

ABSOLUTE MAXIMUM RATINGS ( $T_a = 25^\circ C$ )

Diode

Forward Current	$I_F$	25	mA
Reverse Voltage	$V_R$	5	V
Power Dissipation	$P_D$	45	mW

Detector

Supply Voltage	$V_{CC}$	-0.5 to 15	V
Output Voltage	$V_O$	-0.5 to 15	V
Output Current	$I_O$	8	mA
Power Dissipation	$P_C$	100	mW
Isolation Voltage*	BV	2500	$V_{r.m.s.}$
Storage Temperature	$T_{stg}$	-55 to +125	$^\circ C$
Operating Temperature	$T_{opt}$	-55 to +100	$^\circ C$
Lead Temperature (10 s)		260	$^\circ C$

\* Condition

AC Voltage for 1 minute at  $T_a = 25^\circ C$ , RH = 60 %  
between input (pin No. 1, 2, 3, 4 Common) and output (pin No. 5, 6, 7, 8 Common)



PS2043

ELECTRICAL CHARACTERISTICS (T<sub>a</sub> = 25 °C)







CHARACTERISTIC		SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Diode	Forward Voltage	V <sub>F</sub>		1.7	2.2	V	I <sub>F</sub> = 16 mA
	Reverse Current	I <sub>R</sub>		0.01	10	μA	V <sub>R</sub> = 5 V
	Forward Voltage Temperature Coefficient	$\frac{\Delta V_F}{\Delta T}$		-1.6		mV/°C	I <sub>F</sub> = 16 mA
	Capacitance	C <sub>t</sub>		60		pF	V = 0, f = 1 MHz
Detector	High Level Output Current	I <sub>OH</sub> (1)		3	500	nA	I <sub>F</sub> = 0 mA, V <sub>CC</sub> = V <sub>O</sub> = 5.5 V
	High Level Output Current	I <sub>OH</sub> (2)			100	μA	I <sub>F</sub> = 0 mA, V <sub>CC</sub> = V <sub>O</sub> = 15 V
Coupled	Current Transfer Ratio	CTR *	15	22		%	I <sub>F</sub> = 16 mA, V <sub>CC</sub> = 4.5 V, V <sub>O</sub> = 0.4 V
	Low Level Output Voltage	V <sub>OL</sub>		0.1	0.4	V	I <sub>F</sub> = 16 mA, V <sub>CC</sub> = 4.5 V, I <sub>O</sub> = 2.4 mA
	Low Level Supply Current	I <sub>CCL</sub>		50		μA	I <sub>F</sub> = 16 mA, V <sub>O</sub> = Open, V <sub>CC</sub> = 15 V
	High Level Supply Current	I <sub>CCH</sub>		0.01	1	μA	I <sub>F</sub> = 0 mA, V <sub>O</sub> = Open, V <sub>CC</sub> = 15 V
	Isolation Resistance	R <sub>1-2</sub>	10 <sup>11</sup>			Ω	V <sub>in-out</sub> = 1 kVDC
	Isolation Capacitance	C <sub>1-2</sub>		0.7		pF	V = 0, f = 1 MHz
	Propagation Delay Time to Low Output Level	t <sub>PHL</sub> **		0.3	0.8	μs	I <sub>F</sub> = 16 mA, V <sub>CC</sub> = 5 V, R <sub>L</sub> = 1.9 kΩ
	Propagation Delay Time to High Output Level	t <sub>PLH</sub> **		(K/L/R) 0.3/1.0/0.8	(K/L/R) 0.8/1.5/1.25	μs	I <sub>F</sub> = 16 mA, V <sub>CC</sub> = 5 V, R <sub>L</sub> = 1.9 kΩ

- \* CTR rank  
K: 15 % ~  
L: 25 % ~  
R: 20 % ~

- \*\* Measuring circuit  
input PW = 100 μs  
Duty = 10 %



TYPICAL CHARACTERISTICS ( $T_a = 25^\circ\text{C}$ )



PS2043

T-41-83

