



- 3-Terminal Regulators
- Output Current up to 100 mA
- No External Components
- Internal Thermal-Overload Protection
- Internal Short-Circuit Current Limiting
- Provided Pb-Free packages from the end of 2004

description

This series of fixed-voltage integrated-circuit voltage regulators is designed for a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation. In addition, they can be used with power-pass elements to make high-current voltage regulators. One of these regulators can deliver up to 100 mA of output current. The internal limiting and thermal-shutdown features of these regulators make them essentially immune to overload. When used as a replacement for a zener diode-resistor combination, an effective improvement in output impedance can be obtained, together with lower bias current.



SOT-89
78L10CPK

electrical characteristics at specified virtual junction temperature, $V_I = 17V$, $I_O = 40mA$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T ‡	78L010			UNIT
			MIN	TYP	MAX	
Output voltage		25°C	9.6	10	10.4	V
	$I_O = 1mA$ to 40mA, $V_I = 13V$ to 25V	Full range	9.5	10	10.5	
	$I_O = 1$ mA to 70 mA	Full range	9.5	10	10.5	
Input voltage regulation	$V_I = 13V$ to 25V	25°C		51	175	mV
	$V_I = 14V$ to 25V			42	125	
Ripple rejection	$V_I = 15V$ to 25V $f = 120$ Hz	25°C	37	44		dB
Output voltage regulation	$I_O = 1$ mA to 100 mA	25°C		20	90	mV
	$I_O = 1$ mA to 40 mA			11	40	
Output noise voltage	$f = 10$ Hz to 100 kHz	25°C		62		µV
Dropout voltage		25°C		1.7		V
Bias current		25°C		4.2	6	mA
		125°C			5.5	
Bias current change	$V_I = 14V$ to 25V	Full range			1.5	mA
	$I_O = 1$ mA to 40 mA				0.1	

‡ Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-µF capacitor across the input and a 0.1-µF capacitor across the output. Full range for the 78L05 is $T_J = 0°C$ to 70°C

WS 78L10


absolute maximum ratings over operating temperature range (unless otherwise noted)

78L10		PARAMETER	UNIT
Input voltage, V_I		30	V
Virtual junction temperature range, T_J		150	°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds		260	°C
Storage temperature range, T_{stg}		-65 to 150	°C

recommended operating conditions

78L10		MIN	MAX	UNIT
Input voltage, V_I		12.5	25	V
Output current, I_O			100	mA
Operating virtual junction temperature, T_J		0	70	°C

Pad Location 78L10



Chip size 1.0 x 1.2 mm

Pad N	Pad Name	X (µm)	Y (µm)
1	Ground	95	100
2	Input	820	1010
3	Output	535	1015