

LOW NOISE AND HIGH GAIN AMPLIFIER FOR IMPEDANCE CONVERTER OF MICROPHONE

DESCRIPTION

The μPD5747T6J is a silicon MOS monolithic integrated circuit designed as high gain impedance converter for electret condenser microphone. This device exhibits low noise and high voltage gain characteristics.

The package is 3-pin thin-type lead-less minimold, suitable for surface mount.

FEATURES

- Low Noise : $N_v = -101$ dBV TYP. @ $V_{DD} = 1.5$ V, $C_{in} = 3$ pF, $R_L = 2.2$ kΩ
: $N_v = -102$ dBV TYP. @ $V_{DD} = 1.5$ V, $C_{in} = 5$ pF, $R_L = 2.2$ kΩ
- High Gain : $G_v = +5.7$ dB TYP. @ $V_{DD} = 1.5$ V, $C_{in} = 3$ pF, $R_L = 2.2$ kΩ
: $G_v = +7.7$ dB TYP. @ $V_{DD} = 1.5$ V, $C_{in} = 5$ pF, $R_L = 2.2$ kΩ
- Low Consumption Current : $I_{DD} = 190$ μA TYP. @ $V_{DD} = 1.5$ V, $R_L = 2.2$ kΩ
- Built-in the capacitor for RF noise immunity
- High ESD voltage
- 3-pin thin-type lead-less minimold (1.2 × 1.0 × 0.33 mm)

APPLICATIONS

- Microphone, Sensor, etc.

ORDERING INFORMATION

Part Number	Order Number	Package	Marking	Supplying Form
μPD5747T6J-E4	μPD5747T6J-E4-A	3-pin thin-type lead-less minimold (Pb-Free)	6X	<ul style="list-style-type: none"> • Embossed tape 8 mm wide • Pin 3 (GND) face the perforation side of the tape • Qty 10 kpcs/reel

Remark To order evaluation samples, please contact your nearby sales office.

Part number for sample order: μPD5747T6J

Caution Observe precautions when handling because these devices are sensitive to electrostatic discharge.

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.

ABSOLUTE MAXIMUM RATINGS (T_A = +25°C)

Parameter	Symbol	Ratings	Unit
Input Voltage (IN-GND)	V _{in}	-0.5 to +0.5	V
Input Current (IN-GND)	I _{in}	0.5	mA
Output Voltage (OUT-GND)	V _{out}	0 to +5	V
Output Current (OUT-GND)	I _{out}	0.5	mA
Channel Temperature	T _{ch}	130	°C
Operating Ambient Temperature	T _A	-40 to +85	°C
Storage Temperature	T _{stg}	-65 to +150	°C

RECOMMENDED OPERATING CONDITIONS (T_A = +25°C)


Parameter	Symbol	MIN.	TYP.	MAX.	Unit
Supply Voltage ^{Note}	V _{DD}	1.0	1.5	5.0	V

Note R_L = 2.2 kΩ

ELECTRICAL CHARACTERISTICS (T_A = +25°C, unless otherwise specified)


Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
Circuit Current	I _{DD}	V _{DD} = 1.5 V, V _{in} = 0 V, R _L = 2.2 kΩ	140	190	250	μA
Input Capacitance	C _{input}	V _{DD} = 1.5 V, R _L = 2.2 kΩ, f = 1 MHz	-	1.5	-	pF
Voltage Gain	G _v	V _{DD} = 1.5 V, V _{in} = 10 mV, R _L = 2.2 kΩ, C _{in} = 3 pF, f = 1 kHz, see Test Circuit	4.5	5.7	7.0	dB
Reduced Voltage Gain Characteristics	ΔG _{vV}	V _{DD} = 1.5 → 1.0 V, V _{in} = 10 mV, R _L = 2.2 kΩ, C _{in} = 3 pF, f = 1 kHz, see Test Circuit	-	0.7	-	dB
Frequency Characteristics	ΔG _v f	V _{DD} = 1.5 V, V _{in} = 10 mV, R _L = 2.2 kΩ, C _{in} = 3 pF, f = 1 kHz → 110 Hz, see Test Circuit	-	0	-	dB
Output Noise Voltage	N _v	V _{DD} = 1.5 V, V _{in} = 0 V, R _L = 2.2 kΩ, C _{in} = 3 pF, A-Curve, see Test Circuit	-	-101	-	dBV
Total Harmonic Distortion	THD	V _{DD} = 1.5 V, V _{out} = 50 mV, R _L = 2.2 kΩ, C _{in} = 3 pF, f = 1 kHz, see Test Circuit	-	0.7	-	%

TEST CIRCUIT (Voltage Gain, Frequency Characteristics, Output Noise Voltage, Total Harmonic Distortion)




TYPICAL CHARACTERISTICS (TA = +25°C, unless otherwise specified)


CIRCUIT CURRENT vs. SUPPLY VOLTAGE




VOLTAGE GAIN vs. SUPPLY VOLTAGE




VOLTAGE GAIN vs. FREQUENCY




TOTAL HARMONIC DISTORTION vs. OUTPUT VOLTAGE



VOLTAGE GAIN vs. INPUT CAPACITANCE




OUTPUT NOISE VOLTAGE vs. INPUT CAPACITANCE



Remark The graphs indicate nominal characteristics.

PACKAGE DIMENSIONS

3-PIN THIN-TYPE LEAD-LESS MINIMOLD (UNIT: mm)



PIN CONNECTIONS

- 1. OUT
- 2. IN
- 3. GND

Remark () : Reference value

RECOMMENDED SOLDERING CONDITIONS

This product should be soldered and mounted under the following recommended conditions. For soldering methods and conditions other than those recommended below, contact your nearby sales office.

Soldering Method	Soldering Conditions	Condition Symbol
Infrared Reflow	Peak temperature (package surface temperature) : 260°C or below Time at peak temperature : 10 seconds or less Time at temperature of 220°C or higher : 60 seconds or less Preheating time at 120 to 180°C : 120±30 seconds Maximum number of reflow processes : 3 times Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	IR260
Wave Soldering	Peak temperature (molten solder temperature) : 260°C or below Time at peak temperature : 10 seconds or less Preheating temperature (package surface temperature) : 120°C or below Maximum number of flow processes : 1 time Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	WS260
Partial Heating	Peak temperature (terminal temperature) : 350°C or below Soldering time (per side of device) : 3 seconds or less Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	HS350

Caution Do not use different soldering methods together (except for partial heating).

- **The information in this document is current as of July, 2009. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of a customer's equipment shall be done under the full responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. In addition, NEC Electronics products are not taken measures to prevent radioactive rays in the product design. When customers use NEC Electronics products with their products, customers shall, on their own responsibility, incorporate sufficient safety measures such as redundancy, fire-containment and anti-failure features to their products in order to avoid risks of the damages to property (including public or social property) or injury (including death) to persons, as the result of defects of NEC Electronics products.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".

The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.

"Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.

"Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).

"Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

(Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).