


FAST RECOVERY RECTIFIER
Voltage rang 50 TO 1000 Volts
Current 1.5 Ampere

FEATURES

- * Fast switching for high efficiency
- * Glass Passivated Chip junction
- * Low leakage
- * High temperature soldering guaranteed
 260 /10 seconds, 0.375"(9.5 mm) lead length
 at 5 lbs(2.3kg) tension

MECHANICAL DATA

- * Case : Transfer Molded Plastic
- * Epoxy: UL94V-O rate flame retardant
- * Terminals : Plated axial lead, Solderable Per MIL-STD-202
 Method 208
- * Polarity : Color band denotes cathode end
- * Mounting position: Any
- * Weight : 0.014 ounce. 0.39 gram (approx)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- * Rating at 25 ambient temperature unless otherwise specified
- * Single phase, half wave. 60Hz, resistive or inductive load.
- * For capacitive load derate current by 20 %

Characteristic	Symbol	FR151	FR152	FR153	FR154	FR155	FR156	FR157	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	280	420	560	700	V
Average Rectifier Forward Current Per Leg $T_C=55$	$I_{F(AV)}$	1.5							A
Non-Repetitive Peak Surge Current (Surge applied at rate load conditions halfware, single phase, 60Hz)	I_{FSM}	60							A
Maximum Instantaneous Forward Voltage ($I_F=1.5$ Amp $T_C=25$)	V_F	1.3							V
Maximum Instantaneous Reverse Current (Rated DC Voltage, $T_C=25$) (Rated DC Voltage, $T_C=125$)	I_R	5.0 200							uA
Reverse Recovery Time (Note 3)	T_{rr}	150			250		500		ns
Typical Junction Capacitance (Note 1)	C_j	20							pF
Typical Thermal Resistance (Note 2)	$R_{\theta jA}$	50							/W
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to +175							

NOTES:

1. Measured at 1.0MHz and applied reverse voltage of 4.0 volts
2. Thermal Resistance from Junction to ambient at .375"(9.5mm)lead length, P.C. board mounted
3. Test conditions: $I_F=0.5$ A, $I_R=1.0$, $I_{RR}=0.25$ A

FR151 Thru FR157

FIG-1 TYPICAL FORWARD CHARACTERISTICS




FIG-3 FORWARD CURRENT DERATING CURVE




FIG-2 TYPICAL REVERSE CHARACTERISTICS




FIG-4 TYPICAL JUNCTION CAPACITANCE







FIG-5 PEAK FORWARD SURGE CURRENT



- Notes:
 1. Rise Time = 7 ns max. Input Impedance = 1 M Ω , 22 pF
 2. Rise Time = 10 ns max. Input Impedance = 50 Ω



Set time base for 50/100 ns/cm

FIG-6 Reverse Recovery Time Characteristic and Test Circuit Diagram

