

TVR1GPP

GLASS PASSIVATED FAST RECOVERY RECTIFIER

VOLTAGE: 400V

CURRENT: 1.0A




FEATURE

Molded case feature for auto insertion
High current capability
Low leakage current
Fast switching capability
High temperature soldering guaranteed
250°C /10sec/0.375" lead length at 5 lbs tension
Glass Passivated chip

MECHANICAL DATA

Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any

DO - 41\DO- 204AL



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	TVR1GPP	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	400	V
Maximum RMS Voltage	V _{rms}	280	V
Maximum DC blocking Voltage	V _{dc}	400	V
Maximum Average Forward Rectified Current 3/8" lead length at Ta =55°C	I _{f(av)}	1.0	A
Peak Forward Surge Current 8.3ms single Half sine-wave superimposed on rated load	I _{fsm}	30.0	A
Maximum Instantaneous Forward Voltage at Rated forward current	V _f	1.3	V
Maximum DC Reverse Current Ta =25°C	I _r	5.0	μA
At rated DC blocking voltage Ta =100°C		50.0	μA
Typical Junction Capacitance (Note 1)	C _j	15.0	pF
Maximum Reverse Recovery Time (Note 2)	T _{rr}	150	nS
Storage and Operating Junction Temperature	T _{stg} , T _j	-55 to +150	°C

Note:

1. Measured at 1.0 MHz and applied voltage of 4.0Vdc
2. Test Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A

RATINGS AND CHARACTERISTIC CURVES TVR1GPP

1

