



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date: Feb, 2, 2007

Product Name: SAW Filter 700 MHz SMD 3.0X3.0 mm

TST Parts No.: TA0617A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Bob Chau

Approval by: _____ Francis Chen

Date: _____ 2, 2, 2007



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 700MHz

MODEL NO.:TA0617A

REV. NO.:3

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: 0°C to +50°C
4. Storage Temperature: -30°C to +85°C


RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Type.	Max.	Note
Center Frequency Fc	MHz	-	700	-	-
Insertion Loss at Center Frequency ILc	dB	-	1.7	2.2	-
VSWR at Center Frequency		-	1.3	2	-
Attenuation (Reference level from ILc)					
608 ~ 614 MHz	dB	20	60	-	-
786 ~ 792 MHz	dB	20	70	-	-
1308 ~ 1314 MHz	dB	45	60	-	-
1486 ~ 1492 MHz	dB	45	56	-	-
2008 ~ 2014 MHz	dB	35	40	-	-
2186 ~ 2192 MHz	dB	33	39	-	-

C. MEASUREMENT CIRCUIT:

HP Network analyzer



D.OUTLINE DRAWING:



△ : Year Code (2006->6, ..., 2009->9)

□ : Date Code (Follow the table from planner each year)

Note :

The base material is ceramic with Au over Ni plating.


The plating thicknesses are:

Electro Ni : 1.27~8.89 μ m.



Electro Au : 0.3~1.0 μ m (solder pads only).

0.3 μ m Min. (Others)

E. PCB Footprint:





F. Frequency Characteristics :





Reflection Functions :

S11




S22




G. PACKING:

1. REEL DIMENSION

(Reel Count : 7"=1000 ; 13"=3000)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

