

KRH-4686BAAN

Description

The **KRH-4686BAAN** consist of a high power special light in TO-46 package.

This device has a high output power, low operating current and provides high optical performance. It emits parallel infrared lights.

Features

- 1mW High power
- 860nm Wavelength Range
- High Reliability
- Low Current and Voltage
- Other Configurations Available on Request

Applications

- Free Space Optics
- Sensor
- Hight limit of resolution encoder

Absolute Maximum Ratings

[Ta = 25°C]

Parameter	Symbol	Ratings	Unit
Continuous Forward Current	I _F	40	mA
Continuous Reverse Voltage	V _R	3	V
Operating Temperature	T _{opr}	-30 ~ +100	°C
Storage Temperature	T _{stg.}	-40 ~ +125	°C
Soldering Temperature *1	T _{sol.}	260	°C

*1 : Soldering Time ≤ 10 seconds (At a distance of 1 mm from the package).


Electro-Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Optical Output Power	P _o	1.0	1.3		mW	I _F =30mA
Peak Wavelength	λ _p	850	860	880	nm	I _F =30mA
Spectral Bandwidth	Δλ		30		nm	I _F =30mA
Breakdown Voltage	V _b	-3			V	I _R =10uA
Forward Voltage	V _f		1.5	1.7	V	I _F =30mA
Beam Divergence	Θ		2		deg	I _F =30mA, FWHM
Beam Size	Bs		4.6 4.8		mm	at 1mm from lens at 5mm from lens

* These specifications are subject to change without notice.

KRH-4686BAAN

Outline Drawing



UNIT:mm

Ordering information

KRH	PKG type	Wavelength	Output Power	PKG Method	Beam Divergence	Pin Config.
KODENSHI R-type High power	46:TO46	65:650nm	A: 0.3 mW	F:CAN with Flat Window	A: ±2	A:Cathode Common
	56:TO56	86:860nm	B: 1mW	B:CAN with Ball lens	C: ±5	B:Anode Common
	18:TO18	31:1310nm		T: Tilted Window	D: ±10	C:CASE GND
				A: Aspherical lens	E: ±15	D:CASE Anode
				D: Dome lens		N: Normal