



1. Mechanical Dimensions:



Notes:

1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: -40°C to +85°C
6. Storage Temperature Range: -55°C to +125°C
7. UL60950 approved to Supplementary Insulation requirements for a working voltage up to 250Vrms, file #E165866.

2. Schematic:



3. Electrical Specifications @25°C:

- OCL: Pins 1-5 3.67mH±10% @10KHz 0.1V
- Leakage L: Pins 1-5 18uH Max @100KHz 0.1V (Short Chip)
- CW/W: Pins 1-9 70pF Max @100KHz 0.1V (tie 2+4)
- Turns Ratio: (1-5):(9-7) = 4.29:1±2%
- DC Res.: Pins 1-4 1.45 Ohms±10%
- DC Res.: Pins 2-5 1.45 Ohms±10%
- DC Res.: Pins 9-7 0.310 Ohms±10%
- Insertion Loss: 0.7dB Max 100KHz, 7.3 Ohm load
- Longitudinal Balance: 40dB Min @5KHz-1.1MHz
- THD: -80dB Max @20KHz, 5Vrms, across Pri 7.3 Ohm Load
135 Ohm Input
- HYPOT: 1875VAC Chip to Line, Wdgs to Core for 1 Sec

DOC. REV: A/1

PROPRIETARY

Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.

XFMRS Inc	Title: ADSL TRANSFORMER		
	UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ±0.010 Dimensions in INCH	P/N: XFADSL61	REV. A
SHEET 1 OF 1	DWN.	廖玉坤	Mar-30-04
	CHK.	李清儿	Mar-30-04
	APP.	BW	Mar-30-04