



SANYO Semiconductors

DATA SHEET

15GN01F

NPN Epitaxial Planar Silicon Transistor

VHF to UHF Band High-frequency Switching, High-frequency General-Purpose Amplifier Applications

Features

- Small ON-resistance [$R_{on}=2\Omega$ ($I_B=3mA$)].
- Small output capacitance [$C_{ob}=1.05pF$ ($V_{CB}=10V$)].
- Ultrasmall package permitting applied sets to be small and slim.

Specifications

Absolute Maximum Ratings at $T_a=25^\circ C$

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	V_{CBO}		15	V
Collector-to-Emitter Voltage	V_{CEO}		8	V
Emitter-to-Base Voltage	V_{EBO}		3	V
Collector Current	I_C		50	mA
Collector Dissipation	P_C		100	mW
Junction Temperature	T_J		150	$^\circ C$
Storage Temperature	T_{stg}		-55 to +150	$^\circ C$

Electrical Characteristics at $T_a=25^\circ C$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	I_{CBO}	$V_{CB}=10V, I_E=0$			0.5	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=2V, I_C=0$			0.5	μA
DC Current Gain	h_{FE}	$V_{CE}=5V, I_C=10mA$	200		400	
Gain-Bandwidth Product	f_T	$V_{CE}=5V, I_C=10mA$	1.0	1.5		GHz
Output Capacitance	C_{ob}	$V_{CB}=10V, f=1MHz$		1.05		pF
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=20mA, I_B=2mA$		0.06	0.12	V
Output ON resistance	R_{on}	$I_B=3mA, f=10kHz$		2.0		Ω

Marking : ZA

■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.

■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.






SANYO Electric Co., Ltd. Semiconductor Company

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN







Package Dimensions

unit : mm

2159A



15GN01F



15GN01F

S Parameters (Common emitter)

$V_{CE}=5V, I_C=5mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.636	-29.26	4.627	121.79	0.031	70.82	0.771	-10.77
200	0.541	-41.53	2.957	111.08	0.055	69.54	0.736	-14.72
300	0.491	-52.12	2.246	103.82	0.077	64.75	0.716	-18.43
400	0.455	-62.14	1.850	97.45	0.095	62.63	0.702	-21.95
500	0.432	-70.66	1.589	91.57	0.111	60.39	0.696	-25.37
600	0.417	-78.45	1.409	86.16	0.124	58.19	0.691	-28.97
700	0.406	-85.71	1.265	80.93	0.137	56.87	0.686	-32.34
800	0.399	-92.36	1.160	76.30	0.147	54.99	0.684	-35.73
900	0.393	-98.33	1.077	71.81	0.157	53.99	0.689	-39.06
1000	0.391	-103.55	1.005	67.91	0.166	52.98	0.692	-42.43

$V_{CE}=5V, I_C=10mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.557	-36.05	6.684	118.39	0.028	67.60	0.693	-12.72
200	0.466	-52.06	4.150	108.35	0.049	68.62	0.652	-16.48
300	0.419	-65.70	3.097	100.84	0.069	65.50	0.628	-20.06
400	0.389	-77.52	2.503	94.29	0.085	62.41	0.614	-23.06
500	0.374	-86.85	2.119	88.50	0.098	62.21	0.607	-26.37
600	0.365	-95.89	1.839	83.29	0.111	60.82	0.606	-29.67
700	0.361	-103.38	1.629	78.45	0.121	59.33	0.601	-32.85
800	0.360	-109.45	1.476	74.05	0.133	59.09	0.602	-36.16
900	0.361	-115.58	1.347	69.84	0.141	58.43	0.608	-39.48
1000	0.361	-120.47	1.247	66.01	0.149	57.85	0.613	-42.67

$V_{CE}=5V, I_C=20mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.477	-46.69	8.907	115.02	0.025	69.63	0.611	-14.74
200	0.395	-68.44	5.408	104.10	0.044	67.32	0.563	-17.93
300	0.358	-85.04	3.912	96.17	0.061	65.26	0.541	-20.73
400	0.347	-98.10	3.092	89.56	0.074	65.71	0.530	-23.48
500	0.340	-107.94	2.558	84.09	0.086	64.56	0.527	-26.42
600	0.343	-116.56	2.193	79.07	0.097	63.39	0.527	-29.48
700	0.344	-123.49	1.921	74.63	0.108	64.28	0.527	-32.79
800	0.349	-129.14	1.713	70.54	0.118	63.46	0.530	-36.03
900	0.354	-134.26	1.554	66.46	0.127	64.01	0.540	-39.19
1000	0.358	-138.57	1.426	62.92	0.137	63.76	0.545	-42.53

$V_{CE}=5V, I_C=30mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.437	-55.08	10.078	112.37	0.024	68.57	0.564	-15.83
200	0.363	-80.54	5.949	100.89	0.041	66.74	0.517	-18.38
300	0.339	-97.82	4.225	92.93	0.056	67.23	0.496	-20.76
400	0.335	-111.28	3.296	86.55	0.068	66.11	0.490	-23.07
500	0.338	-120.52	2.697	81.14	0.081	66.23	0.489	-26.02
600	0.342	-128.45	2.290	76.51	0.092	66.35	0.492	-29.18
700	0.348	-135.06	1.992	71.82	0.103	66.73	0.494	-32.32
800	0.356	-139.70	1.771	67.97	0.113	66.42	0.499	-35.67
900	0.362	-144.18	1.596	64.13	0.122	66.65	0.509	-39.09
1000	0.368	-147.83	1.463	60.83	0.133	67.62	0.517	-42.44

- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of July, 2004. Specifications and information herein are subject to change without notice.