



LED Backlight Diagram:



| Pin No. | 1   | 2   | 3  | 4  | 5   | 6   | 7   | 8   | 9   | 10  | 11  | 12  | 13  | 14  | 15  | 16   | 17 | 18 | 19 | 20 |
|---------|-----|-----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|----|----|----|----|
| Symbol  | VSS | VDD | BL | RS | /WR | /RD | DB0 | DB1 | DB2 | DB3 | DB4 | DB5 | DB6 | DB7 | /CS | /RST | NC | NC | NC | NC |

Notes:

- 5.7" Transmissive, Normally-White TFT-LCD Module
- Viewing Direction: 12:00
- LCD Controller: SSD1926
- LED Driver: CL6201x2
- Operation Temp.: -10°C~70°C
- Storage Temp.: -30°C~80°C

| DWN.  | YDY       | TITLE    | LCM OUTLINE DIMENSION |            |        |
|-------|-----------|----------|-----------------------|------------|--------|
| CHK.  | LYJ       | PART NO. | LT057B-01A            |            |        |
| APPD. |           | DWG. NO. | LT057BW-01A-A         |            |        |
| REV.  | A         | UNIT     | mm                    | PROJECTION |        |
| DATE  | '08.10.06 | SCALE    | NTS                   | SHEET      | 1 OF 1 |