

Silicon NPN Power Transistors

2SC2563

DESCRIPTION

- With TO-3P(I) package
- High power dissipation

APPLICATIONS

- For audio power amplifier and general purpose applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter




Fig.1 simplified outline (TO-3P(I)) and symbol

ABSOLUTE MAXIMUM RATINGS(T_C=25℃)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	Open emitter	120	V
V _{CEO}	Collector-emitter voltage	Open base	120	V
V _{EBO}	Emitter-base voltage	Open collector	5	V
I _C	Collector current		8	A
P _T	Total power dissipation	T _C =25℃	80	W
T _j	Junction temperature		150	℃
T _{stg}	Storage temperature		-55~150	℃

Silicon NPN Power Transistors

2SC2563

CHARACTERISTICS

T_j=25 °C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =25mA, I _B =0	120			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =1mA, I _C =0	5			V
V _{CE(sat)}	Collector-emitter saturation voltage	I _C =4A; I _B =0.4A			2.0	V
I _{CBO}	Collector cut-off current	V _{CB} =120V; I _E =0			50	μA
I _{EBO}	Emitter cut-off current	V _{EB} =5V; I _C =0			50	μA
h _{FE-1}	DC current gain	I _C =1A; V _{CE} =5V	55		160	
h _{FE-2}	DC current gain	I _C =4A; V _{CE} =5V	35			
f _T	Transition frequency	I _C =1A; V _{CE} =5V		90		MHz

Silicon NPN Power Transistors

2SC2563

PACKAGE OUTLINE

