



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDM-200-002 REV: 1.2

2.0" 5\*7 Dot Matrix Displays

PART NO. : ELM-2002SRWA/P17 ECN :          Page: 1/5

■ Features :

- Large emitting dot 0.2" diameter.
- Low power/high brightness.

■ Applications:

- Instrument panels
- Digital read out display

■ Descriptions :

- The ELM-2002 series is a large emitting area(5.0mm diameter)LED sources configured in a 35 dots 5\*7 matrix array.
- These devices are made with white dots and gray surface.

PART NO.	Chip	
	Material	Emitted Color
ELM-2002SRWA/P17	GaAlAs	Super Red

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.



TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306



<http://www.everlight.com>



2.0" 5\*7 Dot Matrix Displays

PART NO. : ELM-2002SRWA/P17 ECN : \_\_\_\_\_ Page: 2/5**Package Dimensions:**

- CATHODE ROW  
ANODE COLUMN*
- 1 CATHODE ROW 5
  - 2 CATHODE ROW 7
  - 3 ANODE COLUMN 2
  - 4 ANODE COLUMN 3
  - 5 CATHODE ROW 4
  - 6 ANODE COLUMN 5
  - 7 CATHODE ROW 6
  - 8 CATHODE ROW 3
  - 9 CATHODE ROW 1
  - 10 ANODE COLUMN 4
  - 11 ANODE COLUMN 3
  - 12 CATHODE ROW 4
  - 13 ANODE COLUMN 1
  - 14 CATHODE ROW 2

**Notes:**

1. All dimensions are in millimeters tolerance is 0.25mm unless otherwise noted.
  2. Above specification may be changed without notice.
- Supplier will reserve authority on material change for above specification.



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDM-200-002 REV: 1.2

2.0" 5\*7 Dot Matrix Displays

PART NO. : ELM-2002SRWA/P17 ECN : \_\_\_\_\_ Page: 3/5

■ Absolute maximum ratings at Ta = 25°C :


Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	5	V
Forward Current	IF	40	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	110	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	IF(Peak)	180	mA

■ Electronic optical characteristics :

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	7.8	12.0	----	mcd	IF=10mA
Peak Wavelength	$\lambda_p$	----	660	----	nm	IF=20mA
Dominant Wavelength	$\lambda_d$	----	643	----	nm	IF=20mA
Spectrum Radiation Bandwidth	$\Delta \lambda$	----	20	----	nm	IF=20mA
Forward Voltage	VF	1.5	1.7	2.4	V	IF=20mA
Reverse Current	IR	----	----	10	$\mu A$	VR=5V



2.0" 5\*7 Dot Matrix Displays





# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDM-200-002 REV: 1.2

2.0" 5\*7 Dot Matrix Displays

PART NO. : ELM-2002SRWA/P17 ECN : \_\_\_\_\_ Page: 5/5

■ Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C /85% RH	1000 HRS	76 PCS	0/1

