



SS3020HE SERIES

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

VOLTAGE 20~200 Volts **CURRENT** 3.0 Amperes

SOD-123HE Unit:inch(mm)

FEATURES



- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- For surface mounted applications
- Low profile package
- Built-in strain relief
- Metal to silicon rectifier. majority carrier conduction
- Low power loss,high efficiency
- High surge capacity
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

Case: SOD-123HE molded plastic

Terminals:Solder plated, solderable per MIL-STD-750,Method 2026

Polarity: Color band cathode



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Resistive or inductive load.

PARAMETER	SYMBOL	SS3020-HE	SS3030-HE	SS3040-HE	SS3060-HE	SS30100-HE	SS30150-HE	SS30200-HE	UNITS
Marking Code		EA	EB	EC	ED	EF	EH	EJ	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	20	30	40	60	100	150	200	V
Maximum RMS Voltage	V_{RMS}	14	21	28	42	70	105	140	V
Maximum DC Blocking Voltage	V_{DC}	20	30	40	60	100	150	200	V
Maximum Average Forward Current at $T_L=75^\circ\text{C}$	$I_{F(AV)}$	3.0							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load(JEDEC method)	I_{FSM}	80							A
Maximum Forward Voltage at 3.0A (Note 1)	V_F		0.52		0.65	0.8	0.86	0.86	V
Maximum DC Reverse Current $T_J=25^\circ\text{C}$	I_R		160		100	20	20	20	μA
Typical Thermal Resistance (Note 2)	$R_{\theta JL}$ $R_{\theta JA}$				20	105			$^\circ\text{C} / \text{W}$
Operating Junction Temperature Range	T_J				-55 to +125				$^\circ\text{C}$
Storage Temperature Range	T_{STG}				-55 to +125				$^\circ\text{C}$

NOTES:

1. Pulse Test with PW =300 μsec , 1% Duty Cycle.
2. Mounted on P.C. Board with 8.0mm² (.013mm thick) copper pad areas.



SS3020HE SERIES

RATING AND CHARACTERISTIC CURVES




Fig.1- FORWARD CURRENT DERATING CURVE




Fig.2- TYPICAL REVERSE CHARACTERISTICS




Fig.3- TYPICAL REVERSE CHARACTERISTICS




Fig.4- TYPICAL REVERSE CHARACTERISTICS




Fig.5- TYPICAL REVERSE CHARACTERISTICS




Fig.6- TYPICAL REVERSE CHARACTERISTICS



SS3020HE SERIES




Fig.7- TYPICAL JUNCTION CAPACITANCE




Fig.8- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




Fig.9- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




Fig.10- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




Fig.11- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





Fig.12- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



SS3020HE SERIES

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 10K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2010

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.