

**(CRT HORIZONTAL DEFLECTION)  
 MODULATION DIODE**
[www.datasheet4u.com](http://www.datasheet4u.com)
**MAIN PRODUCT CHARACTERISTICS**

<b>I<sub>F</sub> peak</b>	3A
<b>V<sub>RRM</sub></b>	400V
<b>trr</b>	22ns
<b>V<sub>F</sub></b>	1.35V


**FEATURES**

- PRODUCT SPECIFIC TO HORIZONTAL DEFLECTION
- HIGH REVERSE VOLTAGE
- LOW SWITCHING LOSSES DUE TO SMALL RECOVERY CHARGES

**DESCRIPTION**

High voltage diode especially designed for horizontal deflection stage in standard and high resolution displays for TV's and monitors.

This device is packaged in DO27A and is intended for use as a MODULATION diode in deflection circuitry with east-west correction.


**ABSOLUTE MAXIMUM RATINGS**

Symbol	Parameter		Value	Unit
V <sub>RRM</sub>	Repetitive peak reverse voltage		400	V
V <sub>RWM</sub>	Reverse working voltage		400	V
I <sub>F</sub> peak	Peak forward current (1)	T <sub>amb</sub> =130°C (2)	3	A
I <sub>FRM</sub>	Repetitive peak forward current	t <sub>p</sub> ≤ 10μs	60	A
I <sub>FSM</sub>	Surge non repetitive forward current	t <sub>p</sub> =10ms sinusoidal	60	A
T <sub>stg</sub> T <sub>j</sub>	Storage and junction temperature range		- 40 to + 150 - 40 to + 150	°C °C

(1) δ = 0.5 and triangular waveform

(2) on infinite heatsink with 10mm lead length

**THERMAL RESISTANCE**

Symbol	Parameter	Value	Unit
Rth (j-a)	Junction to ambient (*)	20	°C/W

(\*) on infinite heatsink with 10mm lead length

**STATIC ELECTRICAL CHARACTERISTICS**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I <sub>R</sub> *	Reverse leakage current	V <sub>R</sub> = V <sub>RWM</sub>	T <sub>j</sub> = 25°C		20	μA
			T <sub>j</sub> = 100°C		0.5	mA
V <sub>F</sub> **	Forward voltage drop	I <sub>F</sub> = 3 A	T <sub>j</sub> = 25°C		1.45	V
			T <sub>j</sub> = 100°C		1.35	

 Pulse test : \* t<sub>p</sub> = 5 ms, duty cycle < 2 %

 \*\* t<sub>p</sub> = 380 μs, duty cycle < 2 %

**DYNAMIC ELECTRICAL CHARACTERISTICS**
**TURN-OFF SWITCHING**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
t <sub>rr</sub>	Reverse recovery time	I <sub>F</sub> = 0.5 A I <sub>rr</sub> = 0.25 A I <sub>R</sub> = 1 A T <sub>j</sub> = 25°C			22	ns

**TURN ON SWITCHING**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
t <sub>FR</sub>	Forward recovery time	I <sub>F</sub> = 3 A dI <sub>F</sub> /dt = 100 A/μs Measured at 1.1 x V <sub>F</sub> T <sub>j</sub> = 25°C			0.1	μs
V <sub>FP</sub>	Peak forward voltage				17	V

To evaluate the conduction losses, in case of triangular current, use the following equation :

$$P = \frac{1.17 \times I_P \times \delta}{2} + \frac{0.06 \times I_P^2 \times \delta}{3}$$


δ : duty cycle

 I<sub>P</sub> : Peak current

 for I<sub>P</sub> = 3A and δ = 0.5, P = 0.97 W

**BASIC E-W DIODE MODULATOR CIRCUIT**

www.datasheet4u.com



**D1=DTV32-1000A    D2=MTV32-400A**