

## Linear Systems replaces discontinued Siliconix U403 with LSU403

The U403/ LSU403 is a Low Noise, Low Drift, Monolithic Dual N-Channel JFET

The LSU403 is a high-performance monolithic dual JFET featuring extremely low noise, tight offset voltage and low drift over temperature specifications, and is targeted for use in a wide range of precision instrumentation applications. The LSU403 features a 5-mV offset and 10- $\mu\text{V}/^\circ\text{C}$  drift. The LSU403 is a direct replacement for discontinued Siliconix U403.

The hermetically sealed TO-71 & TO-78 packages are well suited for military applications.

(See Packaging Information).

### U403 / LSU403 Applications:

- Wideband Differential Amps
- High-Speed, Temp-Compensated Single-Ended Input Amps
- High-Speed Comparators
- Impedance Converters and vibrations detectors.

### FEATURES

LOW DRIFT	$ V_{GS1-2}/T  = 10\mu\text{V}/^\circ\text{C}$ TYP.
LOW NOISE	$e_n = 6\text{nV}/\text{Hz}$ @ 10Hz TYP.
LOW PINCHOFF	$V_p = 2.5\text{V}$ TYP.

### ABSOLUTE MAXIMUM RATINGS

@ 25°C (unless otherwise noted)

### Maximum Temperatures

Storage Temperature	-65°C to +150°C
Operating Junction Temperature	+150°C

### Maximum Voltage and Current for Each Transistor – Note 1

$-V_{GSS}$	Gate Voltage to Drain or Source	50V
$-V_{DSO}$	Drain to Source Voltage	50V
$-I_{G(f)}$	Gate Forward Current	10mA

### Maximum Power Dissipation

Device Dissipation @ Free Air – Total	300mW
---------------------------------------	-------

### MATCHING CHARACTERISTICS @ 25°C UNLESS OTHERWISE NOTED

SYMBOL	CHARACTERISTICS	VALUE	UNITS	CONDITIONS
$ V_{GS1-2}/T $ max.	DRIFT VS. TEMPERATURE	25	$\mu\text{V}/^\circ\text{C}$	$V_{DG}=10\text{V}$ , $I_D=200\mu\text{A}$ $T_A=-55^\circ\text{C}$ to $+125^\circ\text{C}$
$ V_{GS1-2} $ max.	OFFSET VOLTAGE	10	mV	$V_{DG}=10\text{V}$ , $I_D=200\mu\text{A}$

### ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)


SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
$BV_{GSS}$	Breakdown Voltage	50	60	--	V	$V_{DS} = 0$ $I_D = 1\text{nA}$
$BV_{GGO}$	Gate-To-Gate Breakdown	$\pm 50$	--	--	V	$I_G = 1\text{nA}$ $I_D = 0$ $I_S = 0$
<b>TRANSCONDUCTANCE</b>						
$Y_{fSS}$	Full Conduction	2000	--	7000	$\mu\text{mho}$	$V_{DG} = 10\text{V}$ $V_{GS} = 0\text{V}$ $f = 1\text{kHz}$
$Y_{fS}$	Typical Operation	1000	--	2000	$\mu\text{mho}$	$V_{DG} = 15\text{V}$ $I_D = 200\mu\text{A}$ $f = 1\text{kHz}$
$ Y_{fS1-2}/Y_{fS} $	Mismatch	--	0.6	3	%	
<b>DRAIN CURRENT</b>						
$I_{DSS}$	Full Conduction	0.5	--	10	mA	$V_{DG} = 10\text{V}$ $V_{GS} = 0\text{V}$
$ I_{DSS1-2}/I_{DSS} $	Mismatch at Full Conduction	--	1	5	%	
<b>GATE VOLTAGE</b>						
$V_{GS(off)}$ or $V_p$	Pinchoff voltage	-0.5	--	-2.5	V	$V_{DS} = 15\text{V}$ $I_D = 1\text{nA}$
$V_{GS(on)}$	Operating Range	--	--	-2.3	V	$V_{DS} = 15\text{V}$ $I_D = 200\mu\text{A}$
<b>GATE CURRENT</b>						
$-I_{G(max)}$	Operating	--	-4	-15	$\mu\text{A}$	$V_{DG} = 15\text{V}$ $I_D = 200\mu\text{A}$
$-I_{G(max)}$	High Temperature	--	--	-10	nA	$T_A = +125^\circ\text{C}$
$-I_{GSS(max)}$	At Full Conduction	--	--	100	$\mu\text{A}$	$V_{DS} = 0$
$-I_{GSS(max)}$	High Temperature	5	5	5	$\mu\text{A}$	$V_{DG} = 15\text{V}$ $T_A = +125^\circ\text{C}$
<b>OUTPUT CONDUCTANCE</b>						
$Y_{OSS}$	Full Conduction	--	--	20	$\mu\text{mho}$	$V_{DG} = 10\text{V}$ $V_{GS} = 0\text{V}$
$Y_{OS}$	Operating	--	0.2	2	$\mu\text{mho}$	$V_{DG} = 15\text{V}$ $I_D = 500\mu\text{A}$
<b>COMMON MODE REJECTION</b>						
CMR	$-20 \log  V_{GS1-2}/V_{DS} $	95	--	--	dB	$V_{DS} = 10$ to $20\text{V}$ $I_D = 30\mu\text{A}$
<b>NOISE</b>						
NF	Figure	--	--	0.5	dB	$V_{DS} = 15\text{V}$ $V_{GS} = 0\text{V}$ $R_G = 10\text{M}$ $f = 100\text{Hz}$ $\text{NBW} = 6\text{Hz}$
$e_n$	Voltage	--	20	--	nV/ $\sqrt{\text{Hz}}$	$V_{DS} = 15\text{V}$ $I_D = 200\mu\text{A}$ $f = 10\text{Hz}$ $\text{NBW} = 1\text{Hz}$
<b>CAPACITANCE</b>						
$C_{ISS}$	Input	--	--	8	pF	$V_{DS} = 15\text{V}$ $I_D = 200\mu\text{A}$ $f = 1\text{MHz}$
$C_{RSS}$	Reverse Transfer	--	--	1.5	pF	

Note 1 – These ratings are limiting values above which the serviceability of any semiconductor may be impaired

### Available Packages:

U403 / LSU403 in TO-71 & TO-78  
U403 / LSU403 available as bare die  
Please contact [Micross](http://www.micross.com) for full package and die dimensions

### TO-71 / TO-78 (Top View)



Micross Components Europe



Tel: +44 1603 788967

Email: [chipcomponents@micross.com](mailto:chipcomponents@micross.com)

Web: <http://www.micross.com/distribution>