

P-tec Corp. Tel:(800)688-0613
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa Co. 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL16 Series 5MM T1^{3/4} Hi-Eff Green LED

Features

- *Popular 5mm Lens Style with Flange
- *Low Current Requirements
- *High Light Output
- *Reliable & Rugged
- *IC compatible
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<100µA)	5.0V
Max Forward Current	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100mA
Operating Temperature Range	- 25°C to +85°C
Storage Temperature Range	- 40°C to +100°C
Soldering Temperature (1.6mm below body)260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ 1/2	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL16-CDG15	Green	GaP	567	572	35°	2.1	2.6	25.0	70.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

