

P-tec Corp. Tel:(800)688-0613
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa Co. 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL15 Series 5MM (T1¾) LED

Features

- *Popular 5mm Low Profile Lens Style without Flange
- *GaP Red LED Chip used
- *Low Current Requirements
- *High Light Output
- *Reliable & Rugged
- *IC compatible
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

| | |
|---|----------------------|
| Power Dissipation..... | 90mW |
| Reverse Voltage (<100µA) | 5.0V |
| Max Forward Current | 30mA |
| Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width) | 100mA |
| Operating Temperature Range | - 25°C to +85°C |
| Storage Temperature Range | - 40°C to +100°C |
| Soldering Temperature (1.6mm below body) | .260°C for 5 seconds |

Electrical & Optical Characteristics at T_A = 25°C

| Part Number | Emitting Color | Chip Material | Peak Wave Length | Dominant Wave Length | Viewing Angle 2θ ½ | Forward Voltage @20mA (V) | | Luminous Intensity @20mA (mcd) | |
|-------------|----------------|---------------|------------------|----------------------|--------------------|---------------------------|-----|--------------------------------|-----|
| | | | | | | Typ | Max | Min | Typ |
| PL15-CDR24 | Red | GaP | 700 | 650 | 38° | 2.1 | 2.6 | 2.0 | 5.0 |

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

