


High-Reliability Air Core Inductors ML350RAT ML394RAT



- High Q over a wide range of frequencies
- High temperature materials allow operation in ambient temperatures up to 155°C.

Terminations Tin-silver over copper

Ambient temperature -55°C to +125°C with I_{max} current, +125°C to +155°C with derated current

Storage temperature Component: -55°C to +155°C.
Tape and reel packaging: -55°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Temperature Coefficient of Inductance (TCL) +5 to +70 ppm/°C

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Enhanced crush-resistant packaging

ML350RAT: 500 per 7" reel Plastic tape: 8 mm wide, 0.3 mm thick, 4 mm pocket spacing, 1.5 mm pocket depth

ML394RAT: 500 per 7" reel Plastic tape: 12 mm wide, 0.3 mm thick, 4 mm pocket spacing, 1.6 mm pocket depth

Part number ¹	Turns	L ² (nH)	Percent tol	Q ³ min	SRF min ⁴ (GHz)	DCR max ⁵ (mOhm)	I _{max} (A)
ML350RAT1N7KLZ	2	1.65	10	100	10.0	4.0	1.6
ML350RAT2N6JLZ	3	2.55	5	100	8.2	5.0	1.6
ML350RAT3N9_LZ	4	3.85	5,2	100	7.5	6.0	1.6
ML350RAT5N4_LZ	5	5.40	5,2	100	7.0	8.0	1.6
ML394RAT5N6_LZ	6	5.60	5,2	100	6.5	9.0	1.6
ML394RAT7N2_LZ	7	7.15	5,2	100	6.0	10	1.6
ML394RAT8N8_LZ	8	8.80	5,2	100	6.0	12	1.6
ML394RAT9N9_LZ	9	9.85	5,2	100	5.2	13	1.6
ML394RAT13N_LZ	10	12.55	5,2	100	4.6	14	1.6

1. When ordering, specify **tolerance** and **testing** codes:

ML394RAT10GLZ

Tolerance: G = 2% J = 5%

Testing: Z = COTS

H = Screening per Coilcraft CP-SA-10001

N = Screening per Coilcraft CP-SA-10003

2. Inductance measured at 800 MHz on an Agilent/HP 4286A or equivalent with a Coilcraft SMD-A test fixture and correlation.


3. Q measured at 800 MHz on an Agilent/HP 4291A or equivalent with a 16193A test fixture or equivalent.

4. SRF measured on an Agilent/HP 8753ES or equivalent with a Coilcraft CCF1268 test fixture. Parts with SRF >5 GHz are verified to >5 GHz in screening.


5. DCR measured on a Keithley 580 Micro-Ohmmeter or equivalent.

6. Electrical specifications at 25°C.


Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



Size	A max	B max	C max	D	E	F max
350	0.095	0.135	0.060	0.055 ±0.010	0.072 ±0.010	0.020
	2,41	3,43	1,52	1,40 ±0,25	1,83 ±0,25	0,51
394	0.165	0.135	0.062	0.055 ±0.010	0.144 ±0.012	0.020
	4,19	3,43	1,58	1,40 ±0,25	3,66 ±0,30	0,51



Suggested Land Patterns



Specifications subject to change without notice.
Please check our website for latest information.

Document ML163-1 Revised 09/08/11

1102 Silver Lake Road
Cary IL 60013

Phone 800-981-0363
Fax 847-639-1508

E-mail cps@coilcraft.com
Web www.coilcraft-cps.com

S-Parameter files


ON OUR WEB SITE

SPICE models


ON OUR WEB SITE

ML350RAT/ML394RAT Air Core Inductors


L vs Frequency – ML350RAT Series




L vs Frequency – ML394RAT Series



Q vs Frequency – ML350RAT Series



Q vs Frequency – ML394RAT Series



Typical Current Derating

