



1202-26-9

REVISIONS	
ISSUE	CHANGES
0	ER 35885 KH 11/03/94
1	CN 37995 E TML 04/06/00
C	REVISED PER DMF304 & ER34488 KPL 08/17/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE	4:1		
APPROX SURFACE AREA			
WAS:	E-18245		
CAGE CODE:	91836		
REF:			
JACK, BULKHEAD, N			
DRAWN	MJB	DATE	08/11/94
DESIGN	CT	DATE	11/03/94
APPR.	JT	DATE	11/04/94

WINCHESTER ELECTRONICS Winchester Electronics Corporation
62 Barnes Industrial Road North
Wallingford, Connecticut 06492

- NOTES:
- FOR USE WITH BOEING BMS13-65 OJ & ADAMS RUSSELL FC38Z CABLES.
 - FOR CABLING INSTRUCTIONS SEE 3-546-2.
 - FOR CRIMPING USE DIE KTH-2213.
 - INTERFACE PER MIL-STD-348, FIG. 304-2.
 - CENTER CONTACT (1-534-86MA9) SUPPLIED UNASSEMBLED.
 - MARK PACKAGE: KINGS 1202-26-9 (DATE CODE)
 - MATERIALS:
INSULATOR-TEFLON, ASTM D1710
LOCKWASHER-PHOS. BRONZE, ASTM B103
CENTER CONTACT-BERYLLIUM COPPER, ASTM B196
K-GRIP SLEEVE-COM. BRONZE, ASTM B135
GASKET-SILICONE RUBBER, A-A-59588
ALL OTHER METAL PARTS-BRASS, ASTM B16
 - FINISHES:
CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM-B-488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
 - ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE-50 OHMS
FREQUENCY RANGE-DC TO 11 GHZ
WORKING VOLTAGE-1000 VRMS
 - WEIGHT: 43.5 GRAMS

1202-26-9