

Part Number: C2754A

Revision Level: 4

Date: 7/13/2007

2C 19 SOLID BC SR-PVC PVC

COMMUNICATION CABLE

A. CONSTRUCTION

Conductor: #19 AWG Solid Tinned Copper
 Insulation: 0.010" Wall Semi-Rigid Polyvinyl Chloride
 Cable: 2 conductors @ 2.00" LHL.
 Jacket: 0.032" Wall Polyvinyl Chloride
 Print Legend: *CAROL (R) 19 AWG -- C2754A -- 75C E111240-8 CM (UL) C (UL) OR AWM STYLE 2464 --- CSA LL69381 CMG -- MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000' TO 0')*

DIAMETERS

0.036" nom.
 0.056" nom.
 0.112" nom.
 0.176" +/- 0.009"

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	300 Vrms
CONDUCTOR D.C. RESISTANCE:	8.05 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	29.5 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red