


- Designed for solderless press-fit into plated-thru holes.
- Pin lengths are suitable for .062" and .093"-.125" thick panels.
- Required plated thru-hole is .036"-.041", ie: use a 1.1mm drill prior to plating.
- Uses M-M# 0477 or 0478 with #30 contact, rated for 3 amps. See page 131 for pin details.



Total number of pins				Quantity per tube	Ordering Information			
	A	B	C		L = .175 (for .062 thick panel)	L = .250 (for .125 thick panel)		
10	0.5	0.2	0.3	40	104-13-210-41-770	104-13-210-41-780	<div style="border: 1px solid black; border-radius: 15px; padding: 10px; text-align: center;"> <p>For High Temperature Insulators Add '100' To End Of Part Numbers</p> </div>	
4	0.2	0.3	0.4	102	104-13-304-41-770	104-13-304-41-780		
6	0.3	0.3	0.4	67	104-13-306-41-770	104-13-306-41-780		
8	0.4	0.3	0.4	50	104-13-308-41-770	104-13-308-41-780		
10	0.5	0.3	0.4	40	104-13-310-41-770	104-13-310-41-780		
14	0.7	0.3	0.4	28	104-13-314-41-770	104-13-314-41-780		
16	0.8	0.3	0.4	25	104-13-316-41-770	104-13-316-41-780		
18	0.9	0.3	0.4	22	104-13-318-41-770	104-13-318-41-780		
20	1.0	0.3	0.4	20	104-13-320-41-770	104-13-320-41-780		
22	1.1	0.3	0.4	18	104-13-322-41-770	104-13-322-41-780		
24	1.2	0.3	0.4	16	104-13-324-41-770	104-13-324-41-780		
28	1.4	0.3	0.4	14	104-13-328-41-770	104-13-328-41-780		
20	1.0	0.4	0.5	20	104-13-420-41-770	104-13-420-41-780		
22	1.1	0.4	0.5	18	104-13-422-41-770	104-13-422-41-780		
24	1.2	0.4	0.5	16	104-13-424-41-770	104-13-424-41-780		
28	1.4	0.4	0.5	14	104-13-428-41-770	104-13-428-41-780		
32	1.6	0.4	0.5	12	104-13-432-41-770	104-13-432-41-780		
24	1.2	0.6	0.7	16	104-13-624-41-770	104-13-624-41-780		
28	1.4	0.6	0.7	14	104-13-628-41-770	104-13-628-41-780		
32	1.6	0.6	0.7	12	104-13-632-41-770	104-13-632-41-780		
36	1.8	0.6	0.7	11	104-13-636-41-770	104-13-636-41-780		
40	2.0	0.6	0.7	10	104-13-640-41-770	104-13-640-41-780		
42	2.1	0.6	0.7	9	104-13-642-41-770	104-13-642-41-780		
48	2.4	0.6	0.7	8	104-13-648-41-770	104-13-648-41-780		
50	2.5	0.6	0.7	8	104-13-650-41-770	104-13-650-41-780		
52	2.6	0.6	0.7	7	104-13-652-41-770	104-13-652-41-780		
50	2.5	0.9	1.0	8	104-13-950-41-770	104-13-950-41-780		
52	2.6	0.9	1.0	7	104-13-952-41-770	104-13-952-41-780		
64	3.2	0.9	1.0	6	104-13-964-41-770	104-13-964-41-780		
PLATING CODE =					13			
Sleeve (Pin)					10μ" Au			
Contact (Clip)					30μ" Au			