

Filter Inductors High Current



ELECTRICAL SPECIFICATIONS

Inductance: Measured at 1.0 V with no DC current

Incremental Current: The typical current at which the inductance will be decreased by 5 % from its initial zero DC value

Dielectric Rating: 2500 VRMS between winding and outer circumference to within 0.250" [6.35 mm] of the insulating sleeve edge

Operating Temperature: - 55 °C to + 125 °C (no load)
- 55 °C to + 85 °C (at full rated current)

Current Rating: Maximum continuous Operating current (DC or RMS) based on a 40 °C temperature rise

FEATURES

- Printed circuit mounting (axial leads)
- Protected by polyolefin tubing
- High saturation bobbin used allowing high inductance with low DC resistance
- Pre-tinned leads
- High resistivity core offers very high parallel resistance, resulting in maximum coil performance
- 20 sleeveless models available at reduced cost



RoHS
COMPLIANT

MECHANICAL SPECIFICATIONS


Wire: Solid soft copper

Terminals: 20 AWG tinned copper leads

Coating: Polyolefin tubing - flame retardant UL type VW-1 per MIL-I-23053/5, Class 3 requirements

Core Material: Ferrite

DIMENSIONS in inches [millimeters]



MODEL	A (Max.)	B (Max.)
IHD-1	0.270 [6.85]	0.700 [17.78]
IHD-3	0.460 [11.68]	0.900 [22.86]

STANDARD ELECTRICAL SPECIFICATIONS

IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)	IND. at 1 kHz (μ H)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)
MODEL IHD-1									
1.0	± 15 %	0.009	5.3	7.00	56.0	± 15 %	0.130	1.4	0.97
1.2	± 15 %	0.010	5.0	6.40	68.0	± 15 %	0.145	1.3	0.88
1.5	± 15 %	0.011	4.8	5.70	82.0	± 15 %	0.152	1.3	0.80
1.8	± 15 %	0.012	4.6	5.20	100.0	± 15 %	0.208	1.1	0.73
2.2	± 15 %	0.013	4.4	4.70	120.0	± 15 %	0.283	0.94	0.66
2.7	± 15 %	0.014	4.2	4.30	150.0	± 15 %	0.330	0.87	0.60
3.3	± 15 %	0.016	4.0	3.90	180.0	± 15 %	0.362	0.83	0.54
3.9	± 15 %	0.017	3.8	3.60	220.0	± 15 %	0.505	0.70	0.49
4.7	± 15 %	0.022	3.4	3.30	270.0	± 15 %	0.557	0.67	0.45
5.6	± 15 %	0.024	3.2	3.00	330.0	± 15 %	0.650	0.62	0.40
6.8	± 15 %	0.026	3.1	2.70	390.0	± 15 %	0.770	0.57	0.37
8.2	± 15 %	0.028	3.0	2.50	470.0	± 15 %	1.030	0.49	0.34
10.0	± 15 %	0.033	2.8	2.30	560.0	± 15 %	1.140	0.47	0.31
12.0	± 15 %	0.037	2.6	2.10	680.0	± 15 %	1.500	0.41	0.28
15.0	± 15 %	0.040	2.5	1.90	820.0	± 15 %	1.980	0.36	0.26
18.0	± 15 %	0.044	2.4	1.70	1000.0	± 15 %	2.300	0.33	0.23
22.0	± 15 %	0.050	2.2	1.50	1200.0	± 15 %	2.550	0.31	0.21
27.0	± 15 %	0.070	1.9	1.40	1500.0	± 15 %	3.000	0.29	0.19
33.0	± 15 %	0.075	1.8	1.30	1800.0	± 15 %	4.000	0.25	0.18
39.0	± 15 %	0.084	1.7	1.20	2200.0	± 15 %	4.400	0.24	0.16
47.0	± 15 %	0.104	1.6	1.10	2700.0	± 15 %	5.800	0.21	0.14



STANDARD ELECTRICAL SPECIFICATIONS									
IND. at 1 kHz (μH)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)	IND. at 1 kHz (μH)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps Approx.)
MODEL IHD-1									
3300.0	± 15 %	6.560	0.20	0.13	8200.0	± 15 %	20.800	0.11	0.08
3900.0	± 15 %	8.630	0.17	0.12	10000.0	± 15 %	23.400	0.10	0.08
4700.0	± 15 %	10.100	0.16	0.11	12000.0	± 15 %	26.000	0.10	0.07
5600.0	± 15 %	11.200	0.15	0.10	15000.0	± 15 %	36.000	0.08	0.06
6800.0	± 15 %	15.000	0.13	0.09	18000.0	v	40.000	0.08	0.06
MODEL IHD-3									
3.9	± 15 %	0.007	4.0	8.20	680.0	± 15 %	0.570	1.0	0.67
4.7	± 15 %	0.008	4.0	7.50	820.0	± 15 %	0.643	0.8	0.61
5.6	± 15 %	0.011	4.0	6.90	1000.0	± 15 %	0.844	0.8	0.56
6.8	± 15 %	0.011	4.0	6.30	1200.0	± 15 %	0.977	0.6	0.51
8.2	± 15 %	0.013	4.0	5.70	1500.0	± 15 %	1.180	0.6	0.46
10.0	± 15 %	0.016	4.0	5.20	1800.0	± 15 %	1.500	0.6	0.42
12.0	± 15 %	0.018	4.0	4.70	2200.0	± 15 %	1.760	0.5	0.38
15.0	± 15 %	0.020	4.0	4.30	2700.0	± 15 %	2.130	0.4	0.34
18.0	± 15 %	0.022	4.0	3.90	3300.0	± 15 %	2.530	0.4	0.31
22.0	± 15 %	0.024	4.0	3.50	3900.0	± 15 %	2.840	0.4	0.29
27.0	± 15 %	0.025	4.0	3.20	4700.0	± 15 %	3.790	0.4	0.26
33.0	± 15 %	0.028	4.0	2.90	5600.0	± 15 %	4.240	0.32	0.24
39.0	± 15 %	0.031	4.0	2.70	6800.0	± 15 %	5.750	0.25	0.22
47.0	± 15 %	0.034	4.0	2.50	8200.0	± 15 %	6.440	0.25	0.20
56.0	± 15 %	0.043	3.2	2.30	10000.0	± 15 %	7.300	0.25	0.18
68.0	± 15 %	0.059	2.5	2.10	12000.0	± 15 %	9.340	0.20	0.17
82.0	± 15 %	0.066	2.0	1.90	15000.0	± 15 %	10.700	0.20	0.15
100.0	± 15 %	0.084	1.6	1.70	18000.0	± 15 %	14.800	0.16	0.14
120.0	± 15 %	0.113	1.6	1.60	22000.0	± 15 %	18.000	0.13	0.12
150.0	± 15 %	0.129	1.6	1.40	27000.0	± 15 %	22.700	0.13	0.11
180.0	± 15 %	0.150	1.6	1.30	33000.0	± 15 %	25.700	0.13	0.10
220.0	± 15 %	0.162	1.6	1.20	39000.0	± 15 %	29.700	0.10	0.09
270.0	± 15 %	0.226	1.6	1.10	47000.0	± 15 %	33.700	0.10	0.09
330.0	± 15 %	0.257	1.6	0.95	56000.0	± 15 %	38.000	0.10	0.08
390.0	± 15 %	0.288	1.6	0.88	68000.0	± 15 %	52.800	0.08	0.07
470.0	± 15 %	0.393	1.2	0.80	82000.0	± 15 %	67.300	0.07	0.07
560.0	± 15 %	0.504	1.0	0.74	100000.0	± 15 %	76.000	0.07	0.06

MARKING
- Vishay Dale
- Model
- Value
- Date code

ORDERING INFORMATION				
IHD-1	3.9 μH	± 15 %	ER	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER INFORMATION			
I H D 1	E R	3 R 9	L
MODEL	PACKING CODE	INDUCTANCE VALUE	TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

Leaded Magnetics Packaging Methods

TAPE AND REEL in inches [millimeters]													
Reel Pack													
MODEL	PREVIOUS CODE*	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE	REEL SIZE	CARRIER TAPE WIDTH (W)	COMPONENT PITCH (P)	UNITS/ REEL	PREVIOUS CODE*	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE	UNITS/ REEL		
IM-1	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	4000	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000						
IM-2	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	4000	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000						
IM-4	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	2500	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000						
IM-6	R36	RU	ER	12	2.06 [52.39]	0.4 [10.16]	2000	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.4 [10.16]	400						
IM-8	RB5	RA	EZ	12	2.06 [52.39]	0.4 [10.16]	1000	B08	BH	EB	100		
	RJ2	SJ	ET	7.5	2.06 [52.39]	0.4 [10.16]	400						
IM-9	RB5	RA	EZ	12	2.06 [52.39]	0.4 [10.16]	800	B08	BH	EB	80		
	RJ2	SJ	ET	7.5	2.06 [52.39]	0.4 [10.16]	400						
	RJ5	SS	EW	12	2.06 [52.39]	0.4 [10.16]	1000						
IM-10	RB5	RA	EZ	12	2.06 [52.39]	0.4 [10.16]	800	B08	BH	EB	70		
	RJ2	SJ	ET	7.5	2.06 [52.39]	0.4 [10.16]	400						
IM-6-38	RB5	RA	EZ	12	2.06 [52.39]	0.4 [10.16]	1000	B08	BH	EB	200		
	RJ2	SJ	ET	7.5	2.06 [52.39]	0.4 [10.16]	400						
IM-6RFCS-40	R36	RU	ER	12	2.06 [52.39]	0.4 [10.16]	1000	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.4 [10.16]	400						
IM-10-22	RB5	RR	EZ	12	2.06 [52.39]	0.4 [10.16]	500	B08	BH	EB	100		
IM-10-28	R07	NA	EY	12	2.88 [73.15]	0.4 [10.16]	250	B08	BH	EB	70		
IM-10-31	-	-	-	-	-	-	-	B08	BH	EB	50		
IM-10-37	RB5	RA	EZ	12	2.06 [52.39]	0.4 [10.16]	500	B08	BH	EB	40		
IM-10-46	-	-	-	-	-	-	-	B08	BH	EB	25		
IM-10RFCL-12	RB5	RA	EZ	12	2.19 [55.63]	0.4 [10.16]	250	B08	BH	EB	50		
IMS-2WWD-40	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	4000	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000						
IMS-2SWWD-3	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	4000	B08	BH	EB	100		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000						
IMS-2	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	4000	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000						
IMS-5	R36	RU	ER	12	2.50 [63.50]	0.2 [5.08]	2500	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.50 [63.50]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.50 [63.50]	0.2 [5.08]	1000						
IMS-5WD-40	R36	RU	ER	12	2.50 [63.50]	0.2 [5.08]	2500	B08	BH	EB	200		
	RJ1	SH	ES	7.5	2.50 [63.50]	0.2 [5.08]	400						
	RJ4	ST	EV	7.5	2.50 [63.50]	0.2 [5.08]	1000						




TAPE AND REEL in inches [millimeters]											
MODEL	PREVIOUS CODE*	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE	REEL SIZE	CARRIER TAPE WIDTH (W)	COMPONENT PITCH (P)	UNITS/ REEL	PREVIOUS CODE*	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE	UNITS/ REEL
IMS-5SWD-65	R36	RU	ER	12	2.50 [63.50]	0.2 [5.08]	2500	B08	BH	EB	200
	RJ1	SH	ES	7.5	2.50 [63.50]	0.2 [5.08]	400				
	RJ4	ST	EV	7.5	2.50 [63.50]	0.2 [5.08]	1000				
IR-2	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	4000	B08	BH	EB	200
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400				
	RJ4	ST	EV	12	2.06 [52.39]	0.2 [5.08]	1000				
IR-4	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	2500	B08	BH	EB	200
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400				
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000				
IRF-1	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	4000	B08	BH	EB	200
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400				
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000				
IRF-3	R36	RU	ER	12	2.06 [52.39]	0.2 [5.08]	2500	B08	BH	EB	200
	RJ1	SH	ES	7.5	2.06 [52.39]	0.2 [5.08]	400				
	RJ4	ST	EV	7.5	2.06 [52.39]	0.2 [5.08]	1000				
IRF-24	-	-	ER	12	2.06 [52.39]	0.2 [5.08]	5000	-	-	-	-
IRF-36	-	-	ER	12	2.06 [52.39]	0.2 [5.08]	5000	-	-	-	-
IRF-46	-	-	ER	12	2.06 [52.39]	0.2 [5.08]	3000	-	-	-	-
IHD-1	R16	RR	ER	12	2.06 [52.39]	0.4 [10.16]	800	B08	BH	EB	50
IHD-3	RA3	AC	ER	12	2.87 [72.90]	0.6 [15.24]	200	B08	BH	EB	190
IHD-2	-	-	-	-	-	-	-	-	-	EB	150
IHD-4	-	-	-	-	-	-	-	-	-	EB	60
IHA-101	-	-	-	-	-	-	-	B01	BA	EB	210
IHA-102	-	-	-	-	-	-	-	B01	BA	EB	210
IHA-103	-	-	-	-	-	-	-	B01	BA	EB	200
IHA-104	-	-	-	-	-	-	-	B01	BA	EB	160
IHA-105	-	-	-	-	-	-	-	B01	BA	EB	160
IHA-201	-	-	-	-	-	-	-	B01	BA	EB	200
IHA-202	-	-	-	-	-	-	-	B01	BA	EB	180
IHA-203	-	-	-	-	-	-	-	B01	BA	EB	160
IHA-204	-	-	-	-	-	-	-	B01	BA	EB	120
IHA-205	-	-	-	-	-	-	-	B01	BA	EB	75
IHA-301	-	-	-	-	-	-	-	B01	BA	EB	210
IHA-302	-	-	-	-	-	-	-	B01	BA	EB	240
IHA-303	-	-	-	-	-	-	-	B01	BA	EB	160
IHA-304	-	-	-	-	-	-	-	B01	BA	EB	160
IHA-305	-	-	-	-	-	-	-	B01	BA	EB	160
IHA-501	-	-	-	-	-	-	-	B01	BA	EB	210
IHA-502	-	-	-	-	-	-	-	B01	BA	EB	200
IHA-503	-	-	-	-	-	-	-	B01	BA	EB	75
IHA-504	-	-	-	-	-	-	-	B01	BA	EB	75
IHA-505	-	-	-	-	-	-	-	B01	BA	EB	75
IH-3 5, 27, 50 & 100 µH	-	-	-	-	-	-	-	B15	BQ	EB	150
IH-3 10 µH	-	-	-	-	-	-	-	B15	BQ	EB	200
IH-3 50 µH	-	-	-	-	-	-	-	B15	BQ	EB	50
IH-3 250 µH	-	-	-	-	-	-	-	B15	BQ	EB	75
IH-4 0 µH	-	-	-	-	-	-	-	B15	BQ	EB	160
IH-5 5 & 10 µH	-	-	-	-	-	-	-	B15	BQ	EB	200
IH-5 27 µH	-	-	-	-	-	-	-	B15	BQ	EB	150
IH-5 50, 68, 100 & 150 µH	-	-	-	-	-	-	-	B15	BQ	EB	50
IH-10 5 & 10 µH	-	-	-	-	-	-	-	B15	BQ	EB	150

TAPE AND REEL in inches [millimeters]											
MODEL	PREVIOUS CODE*	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE	REEL SIZE	CARRIER TAPE WIDTH (W)	COMPONENT PITCH (P)	UNITS/ REEL	PREVIOUS CODE*	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE	UNITS/ REEL
IH-10 27 μ H	-	-		-	-	-	-	B15	BQ	EB	50
IH-10 50, 68 & 100 μ H	-	-		-	-	-	-	B15	BQ	EB	75
IH-15 5 μ H	-	-		-	-	-	-	B15	BQ	EB	50
IH-15 10 & 27 μ H	-	-		-	-	-	-	B15	BQ	EB	75
IH-15 50 μ H	-	-		-	-	-	-	B15	BQ	EB	60
IHM-2	-	-		-	-	-	-	P12	PM	EB	20
IHB-1	-	-		-	-	-	-	B40	BV	EB	48
IHB-2	-	-		-	-	-	-	B40	BV	EB	30
IHB-3	-	-		-	-	-	-	B40	BV	EB	20
IHB-4	-	-		-	-	-	-	B40	BV	EB	16
IHB-5	-	-		-	-	-	-	B40	BV	EB	16
IHB-6	-	-		-	-	-	-	B40	BV	EB	16
IHV-15-500	-	-		-	-	-	-	B48	BZ	EB	10
IHV-20-200	-	-		-	-	-	-	B48	BZ	EB	10
IHV-28-60	-	-		-	-	-	-	B48	BZ	EB	14
IHV-30-150	-	-		-	-	-	-	B48	BZ	EB	5
IHV-40-39	-	-		-	-	-	-	B48	BZ	EB	10
IHV-45-92	-	-		-	-	-	-	B48	BZ	EB	5
IHV-50-50	-	-		-	-	-	-	B48	BZ	EB	5
IHV-60-24	-	-		-	-	-	-	B48	BZ	EB	5
PC	-	-		-	-	-	-	F09	FJ	EB	40
VIV	-	-		-	-	-	-	F09	FJ	EB	40
VIH	-	-		-	-	-	-	F09	FJ	EB	40
WVL	-	-		-	-	-	-	F09	FJ	EB	40
TJ3-1U	-	-		-	-	-	-	T07	TG	EB	100
TJ3-2U	-	-		-	-	-	-	T07	TG	EB	100
TJ4-1U	-	-		-	-	-	-	T07	TG	EB	100
TJ4-2U	-	-		-	-	-	-	T07	TG	EB	30
TJ5-1U	-	-		-	-	-	-	T07	TG	EB	100
TJ5-2U	-	-		-	-	-	-	T07	TG	EB	30
TJ6-1U	-	-		-	-	-	-	T07	TG	EB	20
TJ6-2U	-	-		-	-	-	-	T07	TG	EB	36
TJ7-1U	-	-		-	-	-	-	T07	TG	EB	20
TJ7-2U	-	-		-	-	-	-	T07	TG	EB	12
TJ8-1U	-	-		-	-	-	-	T07	TG	EB	15
TJ8-2U	-	-		-	-	-	-	T07	TG	EB	8
TJ9-1U	-	-		-	-	-	-	T07	TG	EB	9
TJ9-2U	-	-		-	-	-	-	T07	TG	EB	3
TE-3	-	-		-	-	-	-	P09	PJ	EB	5
TE-4	-	-		-	-	-	-	P09	PJ	EB	2
TE-5	-	-		-	-	-	-	P09	PJ	EB	2
TD-3	-	-		-	-	-	-	P09	PJ	EB	5
TD-4	-	-		-	-	-	-	P09	PJ	EB	2
TD-5	-	-		-	-	-	-	P09	PJ	EB	2
TC	-	-		-	-	-	-	B09	BJ	EB	36
TA	-	-		-	-	-	-	B42	BX	EB	45
PT-10	-	-		-	-	-	-	C03	CC	EB	32
PT-20	-	-		-	-	-	-	B09	BJ	EB	32
PT-50	-	-		-	-	-	-	B09	BJ	EB	45
PT-100	-	-		-	-	-	-	B09	BJ	EB	50
PT-200	-	-		-	-	-	-	B09	BJ	EB	50
PL-11-xx	-	-		-	-	-	-	C03	CC	EB	10
PL-22-xx	-	-		-	-	-	-	C03	CC	EB	10

MILITARY PART ORDERING EXAMPLES	
TRANSFORMERS AND INDUCTORS	
MIL-T-27E (Basic [TF]) (Established Reliability - None) $\frac{M27}{1} \frac{215}{2} \frac{05}{3} =$ Dale TE- 1.0 2 % Type 3Q0TR mH	1. Military Specification 2. Specification Sheet Number 3. Specification Sheet Dash Number Indicating Value and Electrical Ratings
MIL-C-15305E (Basic [LT]) (Established Reliability MIL-C-39010) $\frac{LT}{1} \frac{4}{2} \frac{K}{3} =$ Dale IM-2 (0.10 μ H to 1.00 μ H) 10 % Type	NOTE: Parts will be color banded. Value per Military Standard dash number. 1. Style 2. Grade and Class 3. Family K = Coil, Radio Frequency, Fixed

MILITARY COLOR CODES - RF COILS			
COLOR	BAND B & C SIGNIFICANT FIGURES or DECIMAL POINT	BAND D MULTIPLIER* or SIGNIFICANT FIGURE	BAND E INDUCTANCE TOLERANCE
Black	0	1	-
Brown	1	10	± 1 %
Red	2	100	± 2 %
Orange	3	1000	± 3 %
Yellow	4	10 000	± 4 %
Green	5	-	-
Blue	6	-	-
Violet	7	-	-
Gray	8	-	-
White	9	-	-
None**	-	-	± 20 %
Silver	-	-	± 10 %
Gold	Decimal Point	-	± 5 %



Band "A" is twice the width of the other bands and is silver in color to identify part as an inductor. ***
For Inductance Values Less Than 10 either Band "B" or Band "C" will be gold and will represent the decimal point. The other two bands ("B" and "D" or "C" and "D") will represent significant figures.
For Inductance Values of 10 or More Band "B" and Band "C" represent significant figures and Band "D" is the Multiplier.
For small units, dots may be used in place of bands.

* The multiplier is the factor by which two significant figures are multiplied to yield the nominal inductance value.
 ** Indicates body color.
 *** Coated inductors are marked with four color bands, the first being a double wide significant figure or decimal point in lieu of the double wide silver inductor identifier.