

RF AMPLIFIER

MODEL *TM6615PM*

Available as: TM6615PM, 4 Pin TO-8 (T4)
 TN6615PM, 4 Pin .450" Sq. Surface Mount (SM3)
 FP6615PM, 4 Pin Flatpack (FP4)
 BX6615PM, SMA Connectorized Housing (H1)

Features

- Superior Phase Noise Performance
- Output Power: +15.5 dBm Typical
- Operating Temp. -55 °C to +85 °C

Specifications

CHARACTERISTIC	TYPICAL	MIN/MAX
	Ta= 25 °C	Ta = -55 °C to +85 °C
Frequency	5 - 500 MHz	5 - 500 MHz
Gain (dB)	10	8.5 Min.
Power @ 1 dB Comp. (dBm)	+15.5	+14.0 Min
Reverse Isolation (dB)	-15.5	-14
VSWR In	1.5:1	2.0:1 Max.
VSWR Out	1.5:1	2.0:1 Max.
Noise Figure (dB)	5.5	7.0 Max.
Power Vdc	+15	+15
mA	50	55 Max.

Note: Care should always be taken to effectively ground the case of each unit.
 Revision 12/3/2013

Typical Intermodulation Performance at 25 °C

Second Order Harmonic Intercept Point +48 dBm (Typ.)
 Second Order Two Tone Intercept Point +42 dBm (Typ.)
 Third Order Two Tone Intercept Point +30 dBm (Typ.)

Absolute Maximum (No Damage) Ratings


Ambient Operating Temperature -55°C to +100 °C
 Storage Temperature -62°C to +125 °C
 Case Temperature +125 °C
 DC Voltage +18 Volts
 Continuous RF Input Power +13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 μsec Max.)
 Thermal Resistance θ_{jc} 19.68 °C/watt

Guaranteed @ 25 °C (200 MHz) Phase Noise Performance (dBc/Hz)*

Frequency	Typical	Guarantee (Min.)
100 Hz	-163	-159
1 kHz	-172	-168
10 kHz	-173	-169
100 kHz	-175	-171
1 MHz	-175	-171

*Note: Phase Noise Performance typically tested at midband.
 Bandedge performance may vary.

Typical Performance Data



Phase Noise Test Conditions:

Carrier Frequency: 200 MHz
 Power Output: +15.5 dBm
 Temperature: 25 °C
 Agilent ES5500 System

Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
5	.02	-72	3.20	-178	.14	4	.13	-164
50	.02	-87	3.30	172	.14	1	.13	-176
100	.04	-89	3.19	164	.14	0	.13	-174
200	.09	-107	3.19	148	.15	-0	.15	-170
300	.14	-120	3.18	132	.15	-1	.17	-169
400	.19	-132	3.21	116	.16	-2	.20	-174
500	.26	-145	3.24	100	.17	-2	.23	-180



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

www.SpectrumMicrowave.com · Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001