


Inductors, Commercial, Molded, Axial Leaded



FEATURES

- High Q and SRF
- Non standard tolerances are also available in all types
- Maximum protection with minimum size as a result of full encapsulation in a thermo-setting mineral filled plastic jacket
- Assured uniformity of product, a result of stringent quality control and inspection procedures at every production stage
- Compliant to RoHS directive 2002/95/EC



RoHS
COMPLIANT

INDUCTANCE RANGE				
MODEL	INDUCTANCE RANGE (μH)		CORE MATERIAL	MAXIMUM OPERATING TEMPERATURE ($^{\circ}\text{C}$)
	MIN.	MAX.		
IM-10-22	0.47	4.7	Phenolic	+ 125
	5.6	39	Iron	+ 105
	1100	3600	Iron	+ 105
IM-10-28	1.2	18	Phenolic	+ 125
	22	120	Iron	+ 105
IM-10-31	180	390	Iron	+ 105
IM-10-37	470	1000	Iron	+ 105
IM-10-46	1500	10 000	Iron	+ 105

DIMENSIONS in inches [millimeters]			
MODEL	A (DIA.)	B	C (TYP.)
IM-10-22	0.560 \pm 0.010 [14.22 \pm 0.254]	#22 AWG 0.025 \pm 0.002 [0.635 \pm 0.051] (0.47 μH thru 39 μH) #21 AWG 0.028 \pm 0.002 [0.711 \pm 0.051] (1100 μH thru 3600 μH)	0.220 \pm 0.010 [5.59 \pm 0.254]
IM-10-28	0.940 \pm 0.010 [23.88 \pm 0.254]	#21 AWG 0.028 \pm 0.002 [0.711 \pm 0.051]	0.280 \pm 0.010 [7.11 \pm 0.254]
IM-10-31	0.560 \pm 0.010 [14.22 \pm 0.254]	#21 AWG 0.028 \pm 0.002 [0.711 \pm 0.051]	0.310 \pm 0.010 [7.87 \pm 0.254]
IM-10-37	0.625 \pm 0.010 [15.88 \pm 0.254]	#21 AWG 0.028 \pm 0.002 [0.711 \pm 0.051]	0.375 \pm 0.010 [9.52 \pm 0.254]
IM-10-46	0.687 \pm 0.010 [17.45 \pm 0.254]	#21 AWG 0.028 \pm 0.002 [0.711 \pm 0.051]	0.468 \pm 0.010 [11.89 \pm 0.254]

STANDARD ELECTRICAL SPECIFICATIONS								
MODEL	IND. (μH)	TOL. (%)	PREVIOUS PART NO.	Q MIN.	TEST FREQUENCY Q (MHz)	SRF MIN. (MHz)	DCR MAX. (Ω)	RATED DC CURRENT (mA)
IM-10-22	0.47	\pm 10	4412-1K	65	25	300	0.06	1970
IM-10-22	0.56	\pm 10	4412-2K	65	25	270	0.07	1850
IM-10-22	0.68	\pm 10	4412-3K	65	25	240	0.08	1700
IM-10-22	0.82	\pm 10	4412-4K	65	25	220	0.11	1450
IM-10-22	1.0	\pm 10	4412-5K	65	25	200	0.14	1290
IM-10-22	1.2	\pm 10	4412-6K	40	7.9	180	0.19	1120
IM-10-22	1.5	\pm 10	4412-7K	40	7.9	160	0.28	925
IM-10-22	1.8	\pm 10	4412-8K	40	7.9	150	0.37	790
IM-10-22	2.2	\pm 10	4412-9K	40	7.9	135	0.50	680
IM-10-22	2.7	\pm 10	4412-10K	40	7.9	120	0.65	600
IM-10-22	3.3	\pm 10	4412-11K	40	7.9	105	1.00	480
IM-10-22	3.9	\pm 10	4412-12K	40	7.9	100	1.20	440
IM-10-22	4.7	\pm 10	4412-13K	40	7.9	90	1.80	360

PHENOLIC CORE

IM-10-22, IM-10-28, IM-10-31, IM-10-37, IM-10-46



Vishay Dale

Inductors, Commercial, Molded, Axial Leaded

STANDARD ELECTRICAL SPECIFICATIONS									
MODEL	IND. (μH)	TOL. (%)	PREVIOUS PART NO.	Q MIN.	TEST FREQUENCY Q (MHz)	SRF MIN. (MHz)	DCR MAX. (Ω)	RATED DC CURRENT (mA)	
IM-10-22	5.6	± 10	4422-1K	35	7.9	55	0.13	885	
IM-10-22	6.8	± 10	4422-2K	35	7.9	50	0.20	710	
IM-10-22	8.2	± 10	4422-3K	35	7.9	44	0.22	680	
IM-10-22	10	± 10	4422-4K	35	7.9	42	0.26	625	
IM-10-22	12	± 10	4422-5K	45	2.5	34	0.45	465	
IM-10-22	15	± 10	4422-6K	45	2.5	32	0.52	442	
IM-10-22	18	± 10	4422-7K	50	2.5	28	0.70	380	
IM-10-22	22	± 10	4422-8K	60	2.5	24	1.00	326	
IM-10-22	27	± 10	4422-9K	60	2.5	22	1.30	275	
IM-10-22	33	± 10	4422-10K	60	2.5	20	1.50	258	
IM-10-22	39	± 10	4422-11K	70	2.5	18	2.00	224	
IM-10-22	1100	± 5	1312-20J	60	0.25	2.8	21.0	78	
IM-10-22	1200	± 5	1312-21J	60	0.25	2.7	22.0	76	
IM-10-22	1300	± 5	1312-22J	60	0.25	2.6	23.0	75	
IM-10-22	1500	± 5	1312-23J	65	0.25	2.4	25.0	72	
IM-10-22	1600	± 5	1312-24J	65	0.25	2.3	26.0	70	
IM-10-22	1800	± 5	1312-25J	65	0.25	2.2	28.0	68	
IM-10-22	2000	± 5	1312-26J	65	0.25	2.1	29.0	67	
IM-10-22	2200	± 5	1312-27J	70	0.25	2.0	30.0	66	
IM-10-22	2400	± 5	1312-28J	70	0.25	1.9	31.0	64	
IM-10-22	2700	± 5	1312-29J	70	0.25	1.8	33.0	62	
IM-10-22	3000	± 5	1312-30J	70	0.25	1.7	35.0	61	
IM-10-22	3300	± 5	1312-31J	70	0.25	1.6	38.0	58	
IM-10-22	3600	± 5	1312-32J	70	0.25	1.5	40.0	57	
IM-10-28	1.2	± 10	4414-1K	60	7.9	170	0.075	2400	
IM-10-28	1.5	± 10	4414-2K	60	7.9	160	0.090	2150	
IM-10-28	1.8	± 10	4414-3K	60	7.9	140	0.135	1750	
IM-10-28	2.2	± 10	4414-4K	60	7.9	125	0.160	1600	
IM-10-28	2.7	± 10	4414-5K	60	7.9	115	0.220	1350	
IM-10-28	3.3	± 10	4414-6K	60	7.9	100	0.305	1150	
IM-10-28	3.9	± 10	4414-7K	60	7.9	95	0.450	955	
IM-10-28	4.7	± 10	4414-8K	60	7.9	90	0.560	860	
IM-10-28	5.6	± 10	4414-9K	60	7.9	80	0.745	745	
IM-10-28	6.8	± 10	4414-10K	60	7.9	75	1.05	635	
IM-10-28	8.2	± 10	4414-11K	60	7.9	68	1.40	550	
IM-10-28	10	± 10	4414-12K	60	7.9	60	1.90	460	
IM-10-28	12	± 10	4414-13K	40	2.5	53	2.65	395	
IM-10-28	15	± 10	4414-14K	40	2.5	50	3.25	355	
IM-10-28	18	± 10	4414-15K	40	2.5	45	4.15	315	
IM-10-28	22	± 10	4424-1K	50	2.5	24	0.295	725	
IM-10-28	27	± 10	4424-2K	45	2.5	22	0.350	660	
IM-10-28	33	± 10	4424-3K	60	2.5	19	0.550	525	
IM-10-28	39	± 10	4424-4K	55	2.5	18	0.650	485	
IM-10-28	47	± 10	4424-5K	65	2.5	16	1.00	390	
IM-10-28	56	± 10	4424-6K	65	2.5	14	1.15	360	
IM-10-28	68	± 10	4424-7K	75	2.5	13	1.85	285	
IM-10-28	82	± 10	4424-8K	75	2.5	12	2.10	265	
IM-10-28	100	± 10	4424-9K	75	2.5	12	2.50	245	
IM-10-28	120	± 10	4424-10K	95	0.79	10	4.10	195	
IM-10-31	180	± 10	31A181K	80	0.79	6	5.5	148	
IM-10-31	220	± 10	31A221K	80	0.79	5.5	5.9	145	
IM-10-31	270	± 10	31A271K	80	0.79	5.1	6.6	138	
IM-10-31	330	± 10	31A331K	75	0.79	4.2	7.8	122	
IM-10-31	390	± 10	31A391K	75	0.79	3.9	8.7	118	
IM-10-37	470	± 10	37A471K	80	0.79	3.7	9.0	125	
IM-10-37	560	± 10	37A561K	80	0.79	3.5	10.0	118	
IM-10-37	680	± 10	37A681K	75	0.79	3.2	11.2	112	
IM-10-37	820	± 10	37A821K	75	0.79	3.0	13.0	105	
IM-10-37	1000	± 10	37A102K	70	0.79	2.7	14.5	95	
IM-10-46	1500	± 10	46A152K	85	0.25	2.2	22.0	84	
IM-10-46	2200	± 10	46A222K	85	0.25	1.8	27.0	76	
IM-10-46	2700	± 10	46A272K	85	0.25	1.6	32.0	69	
IM-10-46	5100	± 10	46A512K	70	0.25	1.0	66.0	48	
IM-10-46	10 000	± 10	46A103K	70	0.25	0.8	70.0	47	



IM-10-22, IM-10-28, IM-10-31, IM-10-37, IM-10-46

Inductors, Commercial, Molded, Axial Leaded

Vishay Dale

MARKING

- Color coded, see packaging

ORDERING INFORMATION

IM-10-22
MODEL

22 μ H
INDUCTANCE
VALUE

$\pm 10\%$
INDUCTANCE
TOLERANCE

EZ
PACKAGE
CODE

e2
JEDEC LEAD (Pb)-FREE
STANDARD

GLOBAL PART NUMBER

I **M** **1** **0**
MODEL

E **Z**
PACKAGE
CODE

2 **2** **0**
INDUCTANCE
VALUE

K
INDUCTANCE
TOLERANCE

2 **2**
SERIES



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.