

FEATURES

16-bit resolution with no missing codes

Throughput: 1 MSPS

Low power dissipation: 7.0 mW @ 1 MSPS, 70 μ W @ 10 kSPS

INL: ± 1.5 LSB typical, ± 1.25 LSB maximum

SINAD: 91.5 dB @ 10 kHz

THD: -114 dB @ 10 kHz

Pseudo differential analog input range

0 V to V_{REF} with V_{REF} between 2.5 V to 5.5 V

Any input range and easy to drive with the ADA4841

No pipeline delay

Single-supply 2.5 V operation with 1.8 V/2.5 V/3 V/5 V logic interface

Serial interface SPI-/QSPI™-/MICROWIRE™-/DSP-compatible

Daisy-chain multiple ADCs and busy indicator

Supports defense and aerospace applications (AQEC)

Controlled manufacturing baseline

One assembly/test site

One fabrication site

Enhanced product change notification

Qualification data available on request

10-lead MSOP

Military temperature range: -55°C to +125°C

APPLICATIONS

Battery-powered equipment


Communications

ATE

Data acquisitions

Medical instruments

APPLICATION DIAGRAM EXAMPLE



09304-001

Figure 1.

GENERAL DESCRIPTION

The AD7980-EP is a 16-bit, successive approximation, analog-to-digital converter (ADC) that operates from a single power supply, VDD. It contains a low power, high speed, 16-bit sampling ADC and a versatile serial interface port. On the CNV rising edge, it samples an analog input IN+ between 0 V to REF with respect to a ground sense IN-. The reference voltage, REF, is applied externally and can be set independent of the supply voltage, VDD. Its power scales linearly with throughput.

The SPI-compatible serial interface also features the ability, using the SDI input, to daisy-chain several ADCs on a single, 3-wire bus and provides an optional busy indicator. It is compatible with 1.8 V, 2.5 V, 3 V, or 5 V logic, using the separate supply VIO.

The AD7980-EP is housed in a 10-lead MSOP with operation specified from -55°C to +125°C.

Table 1. MSOP, QFN (LFCSP) 14-/16-/18-Bit PuISAR® ADC

Type	100 kSPS	250 kSPS	400 kSPS to 500 kSPS	1000 kSPS	ADC Driver
18-Bit		AD7691 ¹	AD7690 ¹	AD7982 ¹	ADA4941 ADA4841
16-Bit	AD7680 AD7683 AD7684	AD7685 ¹ AD7687 ¹ AD7694	AD7686 ¹ AD7688 ¹ AD7693 ¹	AD7980 ¹	ADA4941 ADA4841
14-Bit	AD7940	AD7942 ¹	AD7946 ¹		

¹ Pin-for-pin compatible.

Rev. 0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

TABLE OF CONTENTS

Features	1	Absolute Maximum Ratings	6
Applications.....	1	ESD Caution.....	6
Application Diagram Example.....	1	Pin Configurations and Function Descriptions	7
General Description	1	Typical Performance Characteristics	8
Revision History	2	Outline Dimensions.....	12
Specifications.....	3	Ordering Guide	12
Timing Specifications.....	5		

REVISION HISTORY

9/10 —Revision 0: Initial Version

SPECIFICATIONS

VDD = 2.5 V, VIO = 2.3 V to 5.5 V, V_{REF} = 5 V, T_A = -55°C to +125°C, unless otherwise noted.

Table 2.

Parameter	Conditions	Min	Typ	Max	Unit
RESOLUTION		16			Bits
ANALOG INPUT					
Voltage Range	IN+ – IN–	0		V _{REF}	V
Absolute Input Voltage	IN+	-0.1		V _{REF} + 0.1	V
	IN–	-0.1		+0.1	V
Analog Input CMRR	f _{IN} = 100 kHz		60		dB
Leakage Current @ 25°C	Acquisition phase		1		nA
ACCURACY					
No Missing Codes		16			Bits
Differential Linearity Error	REF = 5 V	-0.9	±0.4	+0.9	LSB ¹
	REF = 2.5 V		±0.55		LSB ¹
Integral Linearity Error	REF = 5 V	-1.5	±0.6	+1.5	LSB ¹
	REF = 2.5 V		±0.65		LSB ¹
Transition Noise	REF = 5 V		0.6		LSB ¹
	REF = 2.5 V		1.0		LSB ¹
Gain Error, T _{MIN} to T _{MAX} ²			±2		LSB ¹
Gain Error Temperature Drift			±0.35		ppm/°C
Zero Error, T _{MIN} to T _{MAX} ²		-0.62	±0.08	+0.62	mV
Zero Temperature Drift			0.54		ppm/°C
Power Supply Sensitivity	VDD = 2.5 V ± 5%		±0.1		LSB ¹
THROUGHPUT					
Conversion Rate	VIO ≥ 2.3 V up to 85°C, VIO ≥ 3.3 V above 85°C up to 125°C	0		1	MSPS
Transient Response	Full-scale step			290	ns
AC ACCURACY					
Dynamic Range	V _{REF} = 5 V		92		dB ³
	V _{REF} = 2.5 V		87		dB ³
Oversampled Dynamic Range	f _O = 10 kSPS		111		dB ³
Signal-to-Noise Ratio, SNR	f _{IN} = 10 kHz, V _{REF} = 5 V		91		dB ³
	f _{IN} = 10 kHz, V _{REF} = 2.5 V		86.5		dB ³
Spurious-Free Dynamic Range, SFDR	f _{IN} = 10 kHz		-110		dB ³
Total Harmonic Distortion, THD	f _{IN} = 10 kHz		-114		dB ³
Signal-to-(Noise + Distortion), SINAD	f _{IN} = 10 kHz, V _{REF} = 5 V		91.5		dB ³
	f _{IN} = 10 kHz, V _{REF} = 2.5 V		87.0		dB ³

¹ LSB means least significant bit. With the 5 V input range, 1 LSB is 76.3 µV.

² These specifications include full temperature range variation, but not the error contribution from the external reference.

³ All specifications in dB are referred to a full-scale input FSR. Tested with an input signal at 0.5 dB below full scale, unless otherwise specified.

AD7980-EP

VDD = 2.5 V, VIO = 2.3 V to 5.5 V, V_{REF} = 5 V, T_A = -55°C to +125°C, unless otherwise noted.

Table 3.

Parameter	Conditions	Min	Typ	Max	Unit
REFERENCE					
Voltage Range		2.4		5.1	V
Load Current	1 MSPS, REF = 5 V		330		μA
SAMPLING DYNAMICS					
-3 dB Input Bandwidth			10		MHz
Aperture Delay	VDD = 2.5 V		2.0		ns
DIGITAL INPUTS					
Logic Levels					
V _{IL}	VIO > 3V	-0.3		0.3 × VIO	V
V _{IH}	VIO > 3V	0.7 × VIO		VIO + 0.3	V
V _{IL}	VIO ≤ 3V	-0.3		0.1 × VIO	
V _{IH}	VIO ≤ 3V	0.9 × VIO		VIO + 0.3	μA
I _{IL}		-1		+1	μA
I _{IH}		-1		+1	μA
DIGITAL OUTPUTS					
Data Format		Serial 16 bits straight binary			
Pipeline Delay		Conversion results available immediately after completed conversion			
V _{OL}	I _{SINK} = 500 μA		0.4		V
V _{OH}	I _{SOURCE} = -500 μA	VIO - 0.3			V
POWER SUPPLIES					
VDD		2.375	2.5	2.625	V
VIO	Specified performance	2.3		5.5	V
VIO Range		1.8		5.5	V
Standby Current ^{1,2}	VDD and VIO = 2.5 V, 25°C		0.35		nA
Power Dissipation	10 kSPS throughput		70		μW
	1 MSPS throughput		7.0	10	mW
Energy per Conversion			7.0		nJ/sample
TEMPERATURE RANGE					
Specified Performance	T _{MIN} to T _{MAX}	-55		+125	°C

¹ With all digital inputs forced to VIO or GND as required.

² During the acquisition phase.

TIMING SPECIFICATIONS

–55°C to +125°C, VDD = 2.37 V to 2.63 V, VIO = 3.3 V to 5.5 V, unless otherwise stated. See Figure 2 and Figure 3 for load conditions.

Table 4.

Parameter	Symbol	Min	Typ	Max	Unit
Conversion Time: CNV Rising Edge to Data Available	t_{CONV}	500		710	ns
Acquisition Time	t_{ACQ}	290			ns
Time Between Conversions	t_{CYC}	1000			ns
CNV Pulse Width (\overline{CS} Mode)	t_{CNVH}	10			ns
SCK Period (\overline{CS} Mode)	t_{SCK}				ns
VIO Above 4.5 V		10.5			ns
VIO Above 3 V		12			ns
VIO Above 2.7 V		13			ns
VIO Above 2.3 V		15			ns
SCK Period (Chain Mode)	t_{SCK}				ns
VIO Above 4.5 V		11.5			ns
VIO Above 3 V		13			ns
VIO Above 2.7 V		14			ns
VIO Above 2.3 V		16			ns
SCK Low Time	t_{SCKL}	4.5			ns
SCK High Time	t_{SCKH}	4.5			ns
SCK Falling Edge to Data Remains Valid	t_{HSDO}	3			ns
SCK Falling Edge to Data Valid Delay	t_{DSDO}				
VIO Above 4.5 V			9.5		ns
VIO Above 3 V			11		ns
VIO Above 2.7 V			12		ns
VIO Above 2.3 V			14		ns
CNV or SDI Low to SDO D15 MSB Valid (\overline{CS} Mode)	t_{EN}				
VIO Above 3 V			10		ns
VIO Above 2.3 V			15		ns
CNV or SDI High or Last SCK Falling Edge to SDO High Impedance (\overline{CS} Mode)	t_{DIS}			20	ns
SDI Valid Setup Time from CNV Rising Edge	$t_{SSDICNV}$	5			ns
SDI Valid Hold Time from CNV Rising Edge (\overline{CS} Mode)	$t_{HSDICNV}$	2			ns
SDI Valid Hold Time from CNV Rising Edge (Chain Mode)	$t_{HSDICNV}$	0			ns
SCK Valid Setup Time from CNV Rising Edge (Chain Mode)	$t_{SSCKCNV}$	5			ns
SCK Valid Hold Time from CNV Rising Edge (Chain Mode)	$t_{HSCKCNV}$	5			ns
SDI Valid Setup Time from SCK Falling Edge (Chain Mode)	$t_{SSDISCK}$	2			ns
SDI Valid Hold Time from SCK Falling Edge (Chain Mode)	$t_{HSDISCK}$	3			ns
SDI High to SDO High (Chain Mode with Busy Indicator)	$t_{DSDOSDI}$			15	ns





Figure 2. Load Circuit for Digital Interface Timing



¹FOR $V_{IO} \leq 3.0V$, $X = 90$ AND $Y = 10$; FOR $V_{IO} > 3.0V$ $X = 70$, AND $Y = 30$.
²MINIMUM V_{IH} AND MAXIMUM V_{IL} USED. SEE DIGITAL INPUTS SPECIFICATIONS IN TABLE 3.

09304-003

Figure 3. Voltage Levels for Timing

ABSOLUTE MAXIMUM RATINGS

Table 5.

Parameter	Rating
Analog Inputs IN+, IN– to GND	-0.3 V to V _{REF} + 0.3 V or ±130 mA
Supply Voltage REF, VIO to GND	-0.3 V to +6 V
VDD to GND	-0.3 V to +3 V
VDD to VIO	+3 V to -6 V
Digital Inputs to GND	-0.3 V to VIO + 0.3 V
Digital Outputs to GND	-0.3 V to VIO + 0.3 V
Storage Temperature Range	-65°C to +150°C
Junction Temperature	150°C
θ _{JA} Thermal Impedance (10-Lead MSOP)	200°C/W
θ _{JC} Thermal Impedance (10-Lead MSOP)	44°C/W
Lead Temperature	
Vapor Phase (60 sec)	215°C
Infrared (15 sec)	220°C

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ESD CAUTION



ESD (electrostatic discharge) sensitive device.
Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATIONS AND FUNCTION DESCRIPTIONS




Figure 4. 10-Lead MSOP Pin Configuration

Table 6. Pin Function Descriptions

Pin No.	Mnemonic
1	REF
2	VDD
3	IN+
4	IN-
5	GND
6	CNV
7	SDO
8	SCK
9	SDI
10	VIO

TYPICAL PERFORMANCE CHARACTERISTICS

VDD = 2.5 V, V_{REF} = 5.0 V, VIO = 3.3 V, unless otherwise noted.




Figure 5. Integral Nonlinearity vs. Code, REF = 5 V




Figure 8. Differential Nonlinearity vs. Code, REF = 5 V




Figure 6. Integral Nonlinearity vs. Code, REF = 2.5 V




Figure 9. Differential Nonlinearity vs. Code, REF = 2.5 V




Figure 7. FFT Plot, REF = 5 V




Figure 10. FFT Plot, REF = 2.5 V




Figure 11. Histogram of a DC Input at the Code Center, REF = 5 V




Figure 14. Histogram of a DC Input at the Code Center, REF = 2.5 V




Figure 12. Histogram of a DC Input at the Code Transition, REF = 5 V




Figure 15. SNR vs. Input Level




Figure 13. SNR, SINAD, and ENOB vs. Reference Voltage




Figure 16. THD, SFDR vs. Reference Voltage

AD7980-EP




Figure 17. SINAD vs. Frequency




Figure 20. THD vs. Frequency




Figure 18. SNR vs. Temperature




Figure 21. THD vs. Temperature




Figure 19. Operating Currents vs. Supply




Figure 22. Operating Currents vs. Temperature





Figure 23. Power-Down Currents vs. Temperature

OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MO-187-BA

Figure 24.10-Lead Mini Small Outline Package [MSOP]

(RM-10)

Dimensions shown in millimeters

091708-A

ORDERING GUIDE

Model	Integral Nonlinearity	Temperature Range	Ordering Quantity	Package Description	Package Option	Branding
AD7980SRMZ-EP-RL7 ¹	±1.5 LSB max	−55°C to +125°C	Reel, 1,000	10-Lead MSOP	RM-10	C78

¹Z = RoHS Compliant Part.