




Three-Phase Bridge Rectifier, 75A

MTP7508S Thru MTP7518S

(MTP75/08 Thru MTP75/18)



FEATURES


- UL recognition file number E320098 
- Typical IR less than 2.0 μ A
- High surge current capability
- Low thermal resistance
- Compliant to RoHS 
- Isolation voltage up to 2500V

TYPICAL APPLICATIONS

General purpose use in AC/DC bridge full wave rectification for big power supply, field supply for DC motor, industrial automation applications.

ADVANTAGE

- International standard package
Epoxy meets UL 94 V-O flammability rating
- Small volume, light weight
- Small thermal resistance
- **Weight:** 183g (6.5 ozs)



PRIMARY CHARACTERISTICS	
$I_{F(AV)}$	75A
V_{RRM}	800V to 1800V
I_{FSM}	1000A
I_R	20 μ A
V_F	1.3V
$T_{Jmax.}$	150°C

Nell High Power Products

MAJOR RATINGS AND CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)							
PARAMETER	SYMBOL	MTP75..S					UNIT
		08	10	12	16	18	
Maximum repetitive peak reverse voltage	V_{RRM}	800	1000	1200	1600	1800	V
Peak reverse non-repetitive voltage	V_{RSM}	900	1100	1300	1700	1900	V
Maximum DC blocking voltage	V_{DC}	800	1000	1200	1600	1800	V
Maximum average forward rectified output current	$I_{F(AV)}$	75					A
Peak forward surge current single sine-wave superimposed on rated load	I_{FSM}	1000					A
Rating (non-repetitive, for t greater than 1 ms and less than 8.3 ms) for fusing	I^2t	5100					A ² s
RMS isolation voltage from case to leads	V_{ISO}	2500					V
Operating junction storage temperature range	T_J	-40 to 150					°C
Storage temperature range	T_{STG}	-40 to 125					°C

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)								
PARAMETER	TEST CONDITIONS	SYMBOL	MTP75..S					UNIT
			08	10	12	16	18	
Maximum instantaneous forward drop per diode	$I_F = 75\text{A}$	V_F	1.3					V
Maximum reverse DC current at rated DC blocking voltage per diode	$T_A = 25^\circ\text{C}$	I_R	20					μA
	$T_A = 150^\circ\text{C}$		4000					

THERMAL AND MECHANICAL ($T_A = 25^\circ\text{C}$ unless otherwise noted)								
PARAMETER	TEST CONDITIONS	SYMBOL	MTP75..S					UNIT
			08	10	12	16	18	
Typical thermal resistance junction to case	Single-side heat dissipation, sine half wave	$R_{\theta JC}^{(1)}$	0.24					°C/W
Mounting torque $\pm 10\%$ to heatsink M6 to terminal M5	A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound.		4					Nm
			4					
Approximate weight			183					g

Notes

- (1) With heatsink, single side heat dissipation, half sine wave.
- (2) M6 screw.




Fig.1 Forward characteristic




Fig.2 Thermal Impedance (junction to case)




Fig.3 Power dissipation vs. output current




Fig.4 Case temperature vs. output current




Fig.5 Forward surge current vs. cycle




Fig.6 I²t characteristic

