


HIGH-REL HEXFETs

INTERNATIONAL RECTIFIER 

INTERNATIONAL RECTIFIER 26E D
M-pak — TO-254AA Isolated Package
N-CHANNEL

4855452 0010566 8 ■ T-39-03

Types	V _{DS} V	R _{DS(ON)} (max) Ω	I _D cont T _C = 25°C A	I _{DM} pulsed A	P _D max W	Bulletin	Case Style
IRFM050 IRFM040	50	0.03 0.04	25.0 25.0	100 100	125 96	PD-9.485 PD-9.484	TO-254AA
IRFM150 IRFM140	100	0.065 0.10	25.0 23.0	100 92	125 96	PD-9.487 PD-9.486	
IRFM250 IRFM240	200	0.10 0.20	24.0 15.0	96 60	125 96	PD-9.489 PD-9.488	
IRFM360 IRFM350 IRFM340	400	0.20 0.31 0.56	25.0 14.0 8.5	100 56 34	250 125 96	— PD-9.491 PD-9.490	
IRFM460 IRFM450 IRFM440	500	0.20 0.42 0.86	25.0 11.0 6.9	100 42 28	250 125 96	— PD-9.493 PD-9.492	



P-CHANNEL

Types	V _{DS} V	R _{DS(ON)} (max) Ω	I _D cont T _C = 25°C A	I _{DM} pulsed A	P _D max W	Bulletin
IRFM9140 IRFM9130	-100	0.21 0.31	-15.0 -11.5	-60 -48	96 75	PD-9.495 PD-9.494
IRFM9240 IRFM9230	-200	0.51 0.81	-9.3 -6.5	-37 -26	96 75	PD-9.497 PD-9.496