



# MINI DIN CONNECTORS




2MJ-0006A110 SERIES


Rating: 1A 100V AC  
2A 12V DC  
Insulation Resistance: 50MΩ MIN.  
Dielectric strength: 250V AC/1 minute  
Contact Resistance: 30mΩ MAX.




NORMAL TYPE



CLAMP TYPE




ARRANGEMENT OF CONTACTS							
NO OF CONTACTS		3	4	5	6	7	8
MODEL NO	NORMAL TYPE	2MJ-0001A110	2MJ-0002A110	2MJ-0003A110	2MJ-0004A110	2MJ-0005A110	2MJ-0006A110
	CLAMP TYPE	2MJ-0001A111	2MJ-0002A111	2MJ-0003A111	2MJ-0004A111	2MJ-0005A111	2MJ-0006A111
PCB LAYOUT (BOTTOM VIEW)							




2MJ-0106A120 SERIES


Rating: 1A 100V AC  
2A 12V DC  
Insulation Resistance: 50MΩ MIN.  
Dielectric strength: 250V AC/1 minute  
Contact Resistance: 30mΩ MAX.



NORMAL TYPE



CLAMP TYPE



ARRANGEMENT OF CONTACTS							
NO OF CONTACTS		3	4	5	6	7	8
MODEL NO	NORMAL TYPE	2MJ-0001A120	2MJ-0002A120	2MJ-0003A120	2MJ-0004A120	2MJ-0005A120	2MJ-0006A120
	CLAMP TYPE	2MJ-0001A121	2MJ-0002A121	2MJ-0003A121	2MJ-0004A121	2MJ-0005A121	2MJ-0006A121
PCB LAYOUT (BOTTOM VIEW)							