

APT5085BN	500V	9.5A	0.85 Ω
APT4585BN	450V	9.5A	0.85 Ω
APT501R1BN	500V	9.0A	1.10 Ω
APT451R1BN	450V	9.0A	1.10 Ω

POWER MOS IV™

N - CHANNEL ENHANCEMENT MODE HIGH VOLTAGE POWER MOSFETS

MAXIMUM RATINGS

All Ratings: $T_C = 25^\circ\text{C}$ unless otherwise specified.

Symbol	Parameter	APT				UNIT
		4585BN	5085BN	451R1BN	501R1BN	
V_{DSS}	Drain-Source Voltage	450	500	450	500	Volts
I_D	Continuous Drain Current	9.5		9.0		Amps
I_{DM}	Pulsed Drain Current ¹	38		36		Amps
V_{GS}	Gate-Source Voltage	±30				Volts
P_D	Total Power Dissipation @ $T_C = 25^\circ\text{C}$, Derate Above 25°C	180				Watts
T_J, T_{STG}	Operating and Storage Junction Temperature Range	- 55 to 150				°C

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Characteristic / Test Conditions / Part Number	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-Source Breakdown Voltage ($V_{GS} = 0V, I_D = 250 \mu\text{A}$)	APT5085BN / APT501R1BN		500	Volts
		APT4585BN / APT451R1BN		450	Volts
I_{DSS}	Zero Gate Voltage Drain Current ($V_{DS} = V_{DSS}, V_{GS} = 0V$) ($V_{DS} = 0.8 V_{DSS}, V_{GS} = 0V, T_C = 125^\circ\text{C}$)			250	μA
				1000	
I_{GSS}	Gate-Source Leakage Current ($V_{GS} = \pm 30V, V_{DS} = 0V$)			±100	nA
$I_{D(ON)}$	On State Drain Current ² ($V_{DS} > I_{D(ON)} \times R_{DS(ON)}$ Max, $V_{GS} = 10V$)	APT5085BN / APT4585BN		9.5	Amps
		APT501R1BN / APT451R1BN		9.0	Amps
$V_{GS(TH)}$	Gate Threshold Voltage ($V_{DS} = V_{GS}, I_D = 1\text{mA}$)	2		4	Volts
$R_{DS(ON)}$	Static Drain-Source On-State Resistance ² ($V_{GS} = 10V, I_D = 0.5 I_D$ [Cont.])	APT5085BN / APT4585BN		0.85	Ohms
		APT501R1BN / APT451R1BN		1.10	Ohms

THERMAL CHARACTERISTICS

Symbol	Characteristic	MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction to Case			0.68	°C/W
$R_{\theta JA}$	Junction to Ambient			40	°C/W
T_L	Max. Lead Temp. for Soldering Conditions: 0.063" from Case for 10 Sec.			300	°C

405 S.W. COLUMBIA STREET
BEND, OREGON 97702-1035
U.S.A.

PHONE ... (503) 382-8028

FAX (503) 388-0364

DYNAMIC CHARACTERISTICS

APT5085/4585/501R1/451R1BN

Symbol	Characteristic	Test Conditions	MIN	TYP	MAX	UNIT
C_{iss}	Input Capacitance	$V_{GS} = 0V$ $V_{DS} = 25V$ $f = 1\text{ MHz}$		740	950	pF
C_{oss}	Output Capacitance			167	234	pF
C_{rss}	Reverse Transfer Capacitance			63	94	pF
Q_g	Total Gate Charge ³	$V_{GS} = 10V, I_D = I_D[\text{Cont.}]$ $V_{DD} = 0.5 V_{DSS}$		33	55	nC
Q_{gs}	Gate-Source Charge			5.6	8	nC
Q_{gd}	Gate-Drain ("Miller") Charge			16	24	nC
$t_{d(on)}$	Turn-on Delay Time	$V_{DD} = 0.5 V_{DSS}$ $I_D = I_D[\text{Cont.}], V_{GS} = 15V$ $R_G = 1.8\Omega$		10	20	ns
t_r	Rise Time			14	28	ns
$t_{d(off)}$	Turn-off Delay Time			35	48	ns
t_f	Fall Time			11	22	ns

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Symbol	Characteristic / Test Conditions / Part Number	MIN	TYP	MAX	UNIT
I_S	Continuous Source Current (Body Diode)	APT5085BN / APT4585BN		9.5	Amps
		APT501R1BN / APT451R1BN		9.0	Amps
I_{SM}	Pulsed Source Current ¹ (Body Diode)	APT5085BN / APT4585BN		38	Amps
		APT501R1BN / APT451R1BN		36	Amps
V_{SD}	Diode Forward Voltage ² ($V_{GS} = 0V, I_S = -I_D[\text{Cont.}]$)			1.3	Volts
t_{rr}	Reverse Recovery Time ($I_S = -I_D[\text{Cont.}], di_S/dt = 100A/\mu s$)	108	216	432	ns
Q_{rr}	Reverse Recovery Charge	1.2	2.5	5.0	μC

SAFE OPERATING AREA CHARACTERISTICS

Symbol	Characteristic	Test Conditions / Part Number	MIN	TYP	MAX	UNIT
SOA1	Safe Operating Area	$V_{DS} = 0.4 V_{DSS}, I_{DS} = P_D / 0.4 V_{DSS}, t = 1\text{ Sec.}$	180			Watts
SOA2	Safe Operating Area	$I_{DS} = I_D[\text{Cont.}], V_{DS} = P_D / I_D[\text{Cont.}], t = 1\text{ Sec.}$	180			Watts
I_{LM}	Inductive Current Clamped	APT5085BN / APT4585BN	38			Amps
		APT501R1BN / APT451R1BN	36			Amps

1.) Repetitive Rating: Pulse width limited by maximum junction temperature. See Transient Thermal Impedance Curve. (Fig.1)

2.) Pulse Test: Pulse width < 380 μs
Duty Cycle < 2%
3.) See MIL-STD-750 Method 3471












FIGURE 1, MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs PULSE DURATION






FIGURE 10, MAXIMUM SAFE OPERATING AREA




FIGURE 11, TYPICAL CAPACITANCE vs DRAIN-TO-SOURCE VOLTAGE




FIGURE 12, GATE CHARGES vs GATE-TO-SOURCE VOLTAGE





FIGURE 13, TYPICAL SOURCE-DRAIN DIODE FORWARD VOLTAGE

TO-247AD Package Outline



Dimensions in Millimeters and (Inches)