

# DET4TC2 & DET4TCR2

## Digital Ground Testers



- IP54 rated
- 2, 3 and 4 point testing
- Attached Rod Technique (ART)
- Stakeless measurements
- User selectable test frequency
- Dry cell or rechargeable versions
- User selectable output voltage
- Simple one button operation
- Robust carry case
- Backlit display
- Delivered with calibration certificate

### DESCRIPTION

Megger's DET4 family of ground testing instruments offers a comprehensive solution to your ground stake and soil resistivity testing needs. The basic kit option comprises, the instrument, test leads, stakes, batteries and calibration certificate are delivered in a tough carry case which has space to accommodate all the instrument accessories - everything you need to start testing in one kit.

The DET4TC2 and DET4TCR2 are designed for extended temperature range use with an IP54 rated enclosure making them genuinely outdoor instruments. The instrument provides all the functions required for ground system testing: variable frequency 2 pole, 3 pole, 4 pole, Attached Rod Technique (ART), stakeless, leakage current and ground noise voltage measurement.

The instrument is easy to use with a large rotary selector switch and one-press test button, both of which permit operation with gloved hands. Unlike some instruments, the design negates the need for a shorting link when making two pole measurements. There are no hidden functions with the instrument: clearly labelled auxiliary controls are used to select the test frequency (94 Hz, 105 Hz, 111 Hz and 128 Hz), output voltage (50 V or 25 V where local standards apply) and to switch the backlight on or off.

The optional ICLAMP augments the traditional fall-of-potential measurement method with ART (Attached Rod Technique) which allows electrode testing without disconnection and also leakage current measurements down to 1 mA. A second optional clamp, the VCLAMP, enables

true stakeless measurements to be made in situations where driving stakes is not practical.

The clear, easy-to-read display provides excellent contrast and viewing angle making the instrument ideally suited to outdoor use. The display is backlit, extending the operational environment of the instrument to cable cellars and other dark locations.

The instrument offers a wide measurement range of 0.01  $\Omega$  to 200 k $\Omega$ , ground noise voltage measurement from 1 V to 100 V and ground current from 1 mA to 20 A. Accurate results can be obtained in electrically noisy environments since the instrument is capable of rejecting noise voltages of 40 V peak to peak and the user can select different test frequencies to minimise the effect of interference.

The DET4TC2 Digital Ground tester is powered from 8 AA batteries which are widely available and deliver excellent testing time. The DET4TCR2 is powered from rechargeable AA cells. The battery charger is built in and the instrument is supplied with an AC/DC adaptor. For both instruments, the battery status is display using a bar-graph.

The Megger ground testers comply with stringent safety standards and are rated to 100 V CAT IV. They also have selectable 25 V or 50 V output for compliance with IEC 61557-5.

## SPECIFICATIONS

### Ingress protection

IP54

### C stake, P stake and Noise check

Automatic

### Noise rejection

40 V pk to pk

### 2-wire, 3-wire, 4-wire test

Yes, no shorting links required

### No disconnect testing (ART)

Yes, with ICLAMP

### Stakeless measurement

Yes, with ICLAMP and VCLAMP

### Instrument output

Voltage:  $\pm 25$  V or  $\pm 50$  V at 94 Hz, 105 Hz, 111 Hz and 128 Hz

Current: 4.5 mA or 0.45 mA or 0.045 mA

### Ground current range with clamp

0.5 mA to 19.9 A

### Ground current accuracy

5%  $\pm 3$  digits

### Ground voltage range

0 to 100 V ac

### Ground voltage accuracy

2%  $\pm 2$  V

### Resistance range

0.01  $\Omega$  to 200 k $\Omega$

### Resistance accuracy

2P measurements: 2%  $\pm 3$  digits

3P measurements: 2%  $\pm 3$  digits

4P measurements: 2%  $\pm 3$  digits

ART measurements: 5%  $\pm 3$  digits

Stakeless measurements: 7%  $\pm 3$  digits

### Maximum probe resistance

R<sub>p</sub> limit: 200 k $\Omega$  (50 V output voltage)

R<sub>c</sub> limit: 200 k $\Omega$  (50 V output voltage)

Limits reduced to 100 k $\Omega$  for 25 V output voltage

Limits reduced to 5 k $\Omega$  for 0.01  $\Omega$  resolution

### Display

3½ digit high contrast liquid crystal, backlit

### Battery type

**DET4TC2:** 8 off AA (LR6) cells

**DET4TCR2:** 8 off AA (LR6) NiMH rechargeable cells

### Operating temperature range

-15°C to +55°C / 5°F to 131°F

### Storage temperature range

-40°C to +70°C / -40°F to 158°F

### Safety

Complies with the requirements of IEC61010-1 100V CAT IV between terminal pairs.

### EMC

In accordance with IEC61326-1

### Standards Compliance

Complies with the requirements of KEMA K85B

Complies with the following parts of EN61557, "Electrical safety in low voltage distribution systems up to 1000 V a.c. and 1500 V d.c. - Equipment for testing, measuring or monitoring of protective measures".

Part 1 - General requirements

Part 5 - Resistance to earth

### Dimensions

203 mm x 148 mm x 78 mm (8in x 5.8in x 3in)

### Weight

1kg (2.2lb)

**ORDERING INFORMATION**

Item	Order Code.	Item	Order Code.
DET4TC2 Basic kit	1000-345	<b>Accessories</b>	
DET4TCR2 Basic kit (rechargeable)	1000-346	Replacement hard carry case	5410-429
<b>"Basic kit" included Accessories</b>			
Hard carry case		Replacement calibration check PCB (two-clamp measurements)	6220-831
Stake and wire kit (15m, 10m, 10m, 3m)		Replacement ground test stakes (x2) for included kit (200mm, 8mm dia)	6220-804
External AC/DC charger (DET4TCR2 only)		Replacement ground test leads (x4) for included kit (15m, 10m, 10m, 3m)	6220-806
DET4TC2 + adaptors	1000-402	Replacement auger stake for professional kit	6220-839
DET4TCR2 + adaptors (rechargeable)	1000-403	Replacement cable reel (50m, red cable) for professional kit	1000-349
<b>"+ adaptors" included Accessories</b>			
Hard carry case		Replacement cable reel (50m, black cable) for professional kit	1000-350
Right angle terminal adaptors (to connect bare wires to terminals)		Replacement cable reel (30m, green cable) for professional kit	1000-362
External AC/DC charger (DET4TCR2 only)		Replacement cable reel (30m, yellow cable) for professional kit	1000-361
<b>Kitted options for ART and Stakeless testing</b>			
DET4TC2 + clamps	1000-365	Replacement external AC/DC adaptor (DET4TCR2 only)	6280-370
DET4TCR2 + clamps (rechargeable)	1000-366	Current clamp and connecting lead	ICLAMP
<b>"+ clamps" included Accessories</b>			
Hard carry case		Calibration check box (25 Ohm)	6220-824
Stake and wire kit (15m, 10m, 10m, 3m)		Right angle terminal adaptor set	6220-803
ICLAMP (for ART testing)		Black crocodile clip (1)	6220-850
VCLAMP (adds stakeless testing)		Professional ground testing kit (2 x 50m, 2 x 30, 4 auger stakes, tape measure, in hard carry case)	6320-245
Field calibration check for instrument and CLAMPS		Vehicle 12 V socket charger (DET4TCR2 only)	6220-375
Right angle terminal adaptors (to connect bare wires to terminals)		"Getting down to earth"	
External AC/DC charger (DET4TCR2 only)		Megger guide to earth ground testing	21500-072
<b>Professional kitted options for ART and Stakeless testing</b>			
DET4TC2 + kit	1000-404		
DET4TCR2 + kit (rechargeable)	1000-405		
<b>"+ kit" included Accessories</b>			
Hard carry case			
Stake and wire kit (15m, 10m, 10m, 3m)			
ICLAMP (for ART testing)			
VCLAMP (adds stakeless testing)			
Field calibration check for instrument and CLAMPS			
Right angle terminal adaptors (to connect bare wires to terminals)			
External AC/DC charger (DET4TCR2 only)			
Separate professional ground testing kit (2 x 50m, 2 x 30m, 4 auger stakes, tape measure, in hard carry case)			