

FEATURES

- True double-conversion online UPS
- Output power factor 0.9
- User-friendly and easy-shift LCD display
- Rack/Tower design
- Programmable power management outlets
- 50/60Hz frequency converter mode
- ECO and advanced ECO mode for energy saving
- Emergency power off function (EPO)
- Hot-swappable battery design for 1-3K models only
- DSP technology applied for 6K and up models
- Active input power factor correction 0.99 for 6K and up models
- N+X paralalled redundancy available for 6K and up models



PHASE (ONLY FOR ONLINE UPS)

Phase: 1-phase in / 1-phase out

INPUT

Capacity: 3000 VA / 2700 W
Voltage: 100*/110*/115*/120 VAC or 208/220/230/240 VAC
Voltage Range: 55-150 VAC ± 5% or 110-300 VAC ± 5%
Frequency Range: 40Hz ~ 70 Hz

OUTPUT

AC Voltage Regulation (Batt. Mode) : ± 1%
Frequency Range (Batt. Mode): 47~ 53 Hz or 57 ~ 63 Hz
Waveform (Batt. Mode): Pure Slin Wave

BATTERY

Battery Type: 12 V/9 Ah
Battery Number: 6
Typical Recharge Time: NONE

SAFETY STANDARD APPAOVAL



PROTECTION

Full Protection: Full Protection

PHYSICAL

Output Receptacles: India, French, Schuko, NEMA, and IEC selections
Dimension: 480mm(L) x 438mm(W) x 88mm(H)
Net Weight (kgs): 28

OPERATING ENVIRONMENT

Humidity: 20-90% RH @ 0-40°C (non-condensing)
Noise Level: Less than 50dB @ 1 Meter

MANAGEMENT

Optional USB/RS-232 Port: Support Windows 98/2000/2003/XP/Vista/2008, Windows 7, Linux, and MAC

This content is subject to change, please refer to specification for more detail. FSP reserve the right to change the content without prior notice