

FEATURES

- High frequency design
- Suitable for active PFC equipped personal computers
- Auto restart while AC is recovering
- Simulated sine wave
- Cold start function
- Optional USB communication port and RJ-11/RJ-45 protection

PHASE (ONLY FOR ONLINE UPS)

Phase: 1-phase in / 1-phase out

INPUT

Capacity: 800 VA / 480 W
Voltage: 110/120 VAC or 220/230/240 VAC

Voltage Range: 90-145 VAC / 180-270 VAC
Frequency Range: 60/50 Hz (auto sensing)

OUTPUT

AC Voltage Regulation (Batt. Mode): ±10%

Frequency Range (Batt. Mode): 60 Hz or 50 Hz ±1 Hz

Transfer Time: Typical 2 ~ 6 ms,

Waveform (Batt. Mode): Simulated Sine Wave

BATTERY

Battery Type: 12 V/9 Ah
Battery Number: 1
Typical Recharge Time: 8 hours up to 90% capacity



SAFETY STANDARD APPROVAL



PROTECTION

Full Protection: Overload, Discharge, and Overcharge Protection

PHYSICAL

Output Receptacles: India, French, Schuko, NEMA, and IEC ions
Dimension: 228mm(L) x 82.5mm(W) x 207mm(H)

Net Weight (kgs): 3.1

OPERATING ENVIRONMENT

Humidity: 0-90 % RH @ 0- 40°C (non-condensing)
Noise Level: Less than 40dB

MANAGEMENT

Optional USB/RS-232 Port: Support Windows 98/2000/2003/XP/Vista/2008, Windows 7, Linux, and MAC 8

This content is subject to change, please refer to specification for more detail.
 FSP reserve the right to change the content without prior notice