

High-Temp (250°C) Universal ZIF DIP Burn-in & Test Socket - (300°C Special Order)

FEATURES

- Accepts devices on 0.300 to 0.600 [7.62 to 15.24] centers
- All pin counts go into PCB with either 0.300 or 0.600 [7.62 or 15.24] centers
- · Contacts normally-closed to eliminate dependence on plastic to sustain contact integrity
- · Socket handle configured with closed contacts (on) when in the UP or DOWN position, and mounted on the RIGHT or LEFT side of socket





GENERAL SPECIFICATIONS

- SOCKET BODY: natural UL 94V-0 glass-filled Polyetheretherketone (PEEK)
- HANDLE: Stainless Steel
- CONTACTS: BeNi 360, 1/2 hard
- CONTACT PLATING: 50μ [1.27μ] min. NiB
- CONTACT CURRENT RATING: 1 amp
- OPERATING TEMPERATURES: -67°F to 482°F [-55°C to 250°C]
- RETENTION FORCE (closed): 55g/pin based on a 0.020 [0.51] dia. test lead
- INSULATION RESISTANCE: $1000 \text{ M}\Omega$ min.
- DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC
- LIFE CYCLE: 25,000 to 50,000 cycles
- ACCEPTS LEADS: 0.014-0.045 [0.38-1.14] wide, 0.110-0.280 [2.79-7.11] long

MOUNTING CONSIDERATIONS

See Socket Footprint below





ALL DIMENSIONS: INCHES [MILLIMETERS] ALL TOLERANCES: ±0.005 [0.13] UNLESS OTHERWISE SPECIFIED DO NOT USE THIS SOCKET IN A BURN-IN OVEN WITH CONTACTS IN OPEN POSITION, AS IT WILL DAMAGE THE SOCKET CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS

CUSTOMIZATION: ARIES SPECIALIZES IN CUSTOM DESIGN AND PRODUCTION. SPECIAL MATERIALS, PLATINGS, SIZES, AND CONFIGURATIONS CAN BE FURNISHED, DEPENDING ON QUANTITY.

ARIES RESERVES THE RIGHT TO CHANGE PRODUCT GENERAL SPECIFICATIONS WITHOUT NOTICE

PRINTOUTS OF THIS DOCUMENT MAY BE OUT-OF-DATE AND SHOULD BE CONSIDERED UNCONTROLLED



