




**Features**

- ✧ Low power loss, high efficiency.
- ✧ High current capability, Low VF.
- ✧ High reliability
- ✧ High surge current capability.
- ✧ Epitaxial construction.
- ✧ Guard-ring for transient protection.
- ✧ For use in low voltage, high frequency inverter, free wheeling, and polarity protection application



**Mechanical Data**

- ✧ Cases: DO-41 molded plastic
- ✧ Epoxy: UL 94V-0 rate flame retardant
- ✧ Lead: Pure tin plated, lead free., solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: Color band denotes cathode
- ✧ High temperature soldering guaranteed: 260°C/10 seconds/.375", (9.5mm) lead lengths at 5 lbs., (2.3kg) tension
- ✧ Weight: 0.33 gram

Dimensions in inches and (millimeters)

**Maximum Ratings and Electrical Characteristics**

Rating at 25°C ambient temperature unless otherwise specified.  
 Single phase, half wave, 60 Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%

Type Number	Symbol	SR 102	SR 103	SR 104	SR 105	SR 106	SR 109	SR 110	SR 115	Units	
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	20	30	40	50	60	90	100	150	V	
Maximum RMS Voltage	V <sub>RMS</sub>	14	21	28	35	42	63	70	105	V	
Maximum DC Blocking Voltage	V <sub>DC</sub>	20	30	40	50	60	90	100	150	V	
Maximum Average Forward Rectified Current See Fig. 1	I <sub>(AV)</sub>	1.0								A	
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I <sub>FSM</sub>	30								A	
Maximum Instantaneous Forward Voltage @ 1.0A	V <sub>F</sub>	0.55		0.70		0.80		0.95		V	
Maximum D.C. Reverse Current @ T <sub>A</sub> =25°C at Rated DC Blocking Voltage @ T <sub>A</sub> =125°C	I <sub>R</sub>	0.5					0.1				mA
		10		5		2.0				mA	
Typical Junction Capacitance (Note 2)	C <sub>j</sub>	80		65		28				pF	
Typical Thermal Resistance (Note 1)	R <sub>θJA</sub>	90								°C/W	
Operating Junction Temperature Range	T <sub>J</sub>	- 65 to +125				-65 to +150				°C	
Storage Temperature Range	T <sub>STG</sub>	-65 to +150								°C	

Notes: 1. Mount on Cu-Pad Size 5mm x 5mm on P.C.B.  
 2. Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

## RATINGS AND CHARACTERISTIC CURVES (SR102 THUR SR115)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE




FIG.6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS

