



SAW Components

SAW Tx filter

Cellular/WCDMA Band VIII

Series/Type:	B9893
Ordering code:	B39901B9893P810
Date:	September 11, 2013
Version:	2.0

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.


EPCOS AG is a TDK Group Company.

Data Sheet
Application


- RF filter for mobile telephone
- WCDMA 900 systems, Transmit path (Tx)
- Usable passband 35 MHz
- Impedance 50 ohm input and output
- Unbalanced /unbalanced operation


Features

- Package size 1.1 x 0.9 mm²
- max. Package height 0.45 mm
- RoHS compatible
- Approx. weight 0.001g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**
- **Moisture Sensitive Level 3**


Pin configuration

- 1 Input, unbalanced
- 4 Output, unbalanced
- 2,3,5 To be grounded



Data Sheet
Characteristics

Temperature range for specification: $T = -20\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

					min.	typ. @ 25°C	max.		
Center frequency		f_C			—	897.5	—	MHz	
Maximum insertion attenuation									
	880.0 ... 915.0	MHz	α_{\max}	—	1.9	2.5	dB		
@ f_{Carrier}	882.4 ... 912.6	MHz	$\alpha_{\text{WCDMA}}^{1)}$	—	1.5	2.0	dB		
Amplitude ripple (p-p)		$\Delta\alpha$							
	880.0 ... 915.0	MHz		—	1.3	1.9	dB		
Error Vector Magnitude²⁾									
@ f_{Carrier}	882.4 ... 912.6	MHz	EVM	—	3.0	6.0	%		
Input VSWR									
	880.0 ... 915.0	MHz		—	2.1	2.4			
Output VSWR									
	880.0 ... 915.0	MHz		—	2.0	2.4			
Attenuation									
	10.0 ... 850.0	MHz	α	20	32	—	dB		
	925.0 ... 960.0	MHz		8	21	—	dB		
@ f_{Carrier}	927.4 ... 957.6	MHz	$\alpha_{\text{WCDMA}}^{3)}$	16	24	—	dB		
	960.0 ... 1880.0	MHz		18	27	—	dB		
	1880.0 ... 2400.0	MHz		26	31	—	dB		
	2400.0 ... 2620.0	MHz		22	29	—	dB		
	2620.0 ... 2690.0	MHz		22	29	—	dB		
	2690.0 ... 2745.0	MHz		22	29	—	dB		
	2745.0 ... 6000.0	MHz		15	21	—	dB		

Data Sheet

- 1) Attenuation of WCDMA signal ("Powertransferfunction", α_{WCDMA}) is determined by

$$\int_{-\infty}^{\infty} |S_{\text{ds21}}(f)H_{\text{RRC}}(f - f_{\text{Carrier}})|^2 df$$

f_{Carrier} according to 3GPP TS 25.101 (e.g. for band VIII TX passband, f_{Carrier} ranges from 882.4MHz (lowest Tx channel) to 912.6MHz (highest Tx channel)). $H_{\text{RRC}}(f)$ is the transfer function of the root-raised cosine transmit pulse shaping filter according to 3GPP TS 25.101 with the following normalization:

$$\int_{-\infty}^{\infty} |H_{\text{RRC}}(f)|^2 df = 1$$

- 2) Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141.

Data Sheet
Maximum ratings

Storage temperature range	T_{stg}	-40/+85 ¹⁾	°C	
DC voltage	V_{DC}	5 ²⁾	V	
ESD voltage	V_{ESD}	100 ³⁾	V	machine model, 10 pulse
Input Power at 880.0... 915.0 MHz	P_{IN}	13	dBm	Continuous wave


1) extended upperlimit : 168h @ 125°C acc. to IEC60068-2-67 Cy

2) 168h damp Heat Steady State acc. to IEC60068-2-67 Cy


3) acc. to JESD22-A115B (machine model), 10 negative & 10 positive pulses.

Data Sheet

Transfer function (narrowband)





Transfer function (wideband)





Data Sheet

Smith charts

S_{11} function



S_{22} function



Please read *cautions and warnings* and *important notes* at the end of this document.

SAW Components	B9893
SAW Filter	897.5 MHz

Data Sheet

References

Type	B9893
Ordering code	B39901B9893P810
Marking and package	C61157-A8-A56
Packaging	F61074-V8255-Z000
Date codes	L_1126
S-parameters	B9893_NB.s2p B9893_WB.s2p See file header for port/pin assignment table.
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching Coils	See http://www.tdk.co.jp/tefe02/coil.htm#aname1 http://www.tdk.co.jp/etvcl/index.htm for a large variety of matching coils.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2013. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CeraLink, CeraPlas, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.