

Features

- ▶ 8 or 12 high current outputs
- ▶ $R_{ON} = 1.5\Omega$ (typ.) $I_{MAX} = 350mA$
- ▶ Outputs combinable for higher loads
- ▶ Digital voltage range VDD 3.3V or 5.0V
- ▶ Low standby current $< 1\mu A @ 50^\circ C$
- ▶ Low output leakage $< 5\mu A @ 13V, RT$
- ▶ SPI interface with diagnostics
- ▶ Open load detection
- ▶ Short circuit limitation, - detection
- ▶ Output clamping for inductive loads typ. $> 40V$
- ▶ Thermal overload protection
- ▶ $-40^\circ C$ to $+125^\circ C$ operation temperature (QFN)

Applications

- ▶ Stepper Motor Driver with Stall Detection
- ▶ DC Motor Driver with PWM
- ▶ Relay Driver with VBAT- automatically PWM
- ▶ LED Driver with 3 logarithmic PWM sources
- ▶ Switch Monitoring with pulsed current check and control lamp
- ▶ Switch Monitoring with control lamp


General Description

The IC drives 2 or 3 unipolar stepper motors and provides an optional stall detection for end position detection. For LED dimming a quasi logarithmic duty cycle is following the physiology of the human eye. With 3 PWM sources color LEDs can be driven in 3-color LED mode (245Hz PWM). The Relay PWM mode automatically adjusts the PWM to an effective supply voltage of typ. 11V. All outputs are short circuit and over-temperature protected with error read back capability. Switch monitoring with control lamp combination with only 1 wire and output is possible.

Ordering Information

Product ID	Channels	Stall Detection	Package
E520.01	12	X	QFN32L5, SOIC28
E520.02	12		QFN32L5, SOIC28
E520.03	8	X	QFN32L5, QFN20L5, SOIC20
E520.08	8		QFN32L5, QFN20L5, SOIC20

Typical Applications Circuit



This document contains information on a pre-production product. ELMOS Semiconductor AG reserves the right to change specifications and information herein without notice.

ELMOS Support 06/2012

Headquarters

ELMOS Semiconductor AG
Heinrich-Hertz-Str. 1
44227 Dortmund (Germany)
Phone: +49 (0) 231 / 75 49-100
Fax: +49 (0) 231 / 75 49-149
sales@elmos.com
www.elmos.com

Regional Sales and Application Support Office Munich

ELMOS Semiconductor AG
Am Gefluegelhof 12
85716 Unterschleißheim/Eching (Germany)
Phone: +49 (0) 89 / 31 83 70-0
Fax: +49 (0) 89 / 31 83 70-31
sales-elmuc@elmos.com

Sales and Application Support Office North America

ELMOS NA. Inc.
32255 Northwestern Highway, Suite 45
Farmington Hills, MI 48334 (United States)
Phone: +1 (0) 248 / 8 65 32 00
elna-sales@elmosna.com

Sales and Application Support Office Korea and Japan

ELMOS Korea
Suite 1907
Park View Office Tower
6 Jeongja-dong, Bundang-gu, Seongnam-si, Kyonggi-do,
463-863 Republic of Korea
Phone: +82 (0)31 / 7 14 11 31
jin-koo.lee@elmos.com

Sales and Application Support Office China

ELMOS Semiconductor Technology (Shanghai) Co., Ltd.
Unit London, 1BF GC Tower,
No. 1088 YuanShen Road,
Pudong New District,
Shanghai, PR China, 200122
Phone: +86 (0) 21 / 5178 5178
sales_china@elmos.com

中国地区销售与应用支持

艾尔默斯半导体技术(上海)有限公司
中国上海浦东新区源深路1088号
葛洲坝大厦1B楼伦敦单元, 200122
电话: +86 (0) 21 / 5178 5178
sales_china@elmos.com

Sales and Application Support Office Singapore

ELMOS Semiconductor Singapore Pte Ltd.
60 Alexandra Terrace
#09-31 The Comtech (Singapore 118502)
Phone: +65 (0) 663 / 5 11 41
Fax: +65 (0) 663 / 5 11 40
sales@elmos.com

Note ELMOS Semiconductor AG (below ELMOS) reserves the right to make changes to the product contained in this publication without notice. ELMOS assumes no responsibility for the use of any circuits described herein, conveys no licence under any patent or other right, and makes no representation that the circuits are free of patent infringement. While the information in this publication has been checked, no responsibility, however, is assumed for inaccuracies. ELMOS does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of a life-support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications.

Copyright © 2012 ELMOS. Reproduction, in part or whole, without the prior written consent of ELMOS, is prohibited.