



## Features

- ▶ Temperature stability down to 50ppb
- ▶ Single 12V supply (15V or 18V optional)
- ▶ Low profile compact package
- ▶ Standard European IEC CO-08 pin-out
- ▶ Custom options available

## Standard Models

The table shows the most common models. In most cases selecting one of these models will ensure the best combination of price / performance and availability.

| Freq    | Specification | Ageing per day      | Temperature stability        | Part No |
|---------|---------------|---------------------|------------------------------|---------|
| 5.0MHz  | HCD310/BNDN   | ±5x10 <sup>-9</sup> | ±5x10 <sup>-8</sup> -20+60°C | MS08441 |
| 10.0MHz | HCD310/BNDN   | ±5x10 <sup>-9</sup> | ±5x10 <sup>-8</sup> -20+60°C | MS06244 |
| 13.0MHz | HCD310/BNDN   | ±5x10 <sup>-9</sup> | ±5x10 <sup>-8</sup> -20+60°C | MS08799 |
| 50.0MHz | HCD310/BNDN   | ±5x10 <sup>-9</sup> | ±5x10 <sup>-8</sup> -20+60°C | MA02777 |
| 5.0MHz  | HCD311/BNDN   | ±5x10 <sup>-9</sup> | ±5x10 <sup>-8</sup> -20+60°C | MA05180 |
| 10.0MHz | HCD311/BNDN   | ±5x10 <sup>-9</sup> | ±5x10 <sup>-8</sup> -20+60°C | MA01432 |
| 50.0MHz | HCD311/BNDN   | ±5x10 <sup>-9</sup> | ±5x10 <sup>-8</sup> -20+60°C | MA05478 |

## Specifications

**HCD310: Sine wave output**

**HCD311: HCMOS / TTL compatible output**

| Parameters   | Product               |                       | Option Codes |
|--|-----------------------|-----------------------|--------------|
|  | HCD310                | HCD311                |              |
| <b>Frequency range:</b><br>5.0 ~ 60.0MHz<br>5.0 ~ 50.0MHz  | ■                     | ■                     |              |
| <b>Ageing per day (at despatch):</b><br>< ±1x10 <sup>-8</sup><br>< ±5x10 <sup>-9</sup>   | □<br>■                | □<br>■                | A<br>B       |
| <b>Frequency stability:</b><br>±5x10 <sup>-7</sup> per year<br>±1x10 <sup>-7</sup> per 5% change in V <sub>DD</sub>  | ■<br>■                | ■<br>■                |              |
| <b>Temperature stability:</b><br>< ±1x10 <sup>-7</sup><br>< ±5x10 <sup>-8</sup>  | □<br>■                | □<br>■                | M<br>N       |
| <b>Operating temperature range:</b><br>-20 to +60°C<br>0 to +70°C<br>-20 to +70°C  | ■<br>□<br>□           | ■<br>□<br>□           | D<br>E<br>F  |
| <b>Storage temperature range:</b><br>-40 to +90°C  | ■                     | ■                     |              |
| <b>Output waveform:</b><br>Sine wave, 1.5V p-p ±0.5V into 50Ω<br>HCMOS / TTL compatible  | ■                     | ■                     |              |
| <b>Frequency adjustment:</b><br>±1x10 <sup>-5</sup> typ (10MHz), +0.5 to +6.0V<br>(sufficient for 10 years ageing min)<br>Stabilised +6.0V supply provided | ■                     | ■                     |              |
| <b>Supply voltage (V<sub>DD</sub>):</b><br>+12V (±0.5V)<br>+15V (±0.5V)<br>+18V (±0.5V)  | ■<br>□<br>□           | ■<br>□<br>□           | N<br>P<br>R  |
| <b>Power consumption:</b><br>4.5W max at switch on<br>1.0W typ when stabilised at 25°C   | ■<br>■                | ■<br>■                |              |
| <b>Warm up:</b><br>±5x10 <sup>-8</sup> after 10mins at +25°C   | ■                     | ■                     |              |
| <b>Phase noise (@ 10.0MHz):</b><br>< -110dBc/Hz @ 10Hz<br>< -130dBc/Hz @ 100Hz<br>< -145dBc/Hz @ 1kHz<br>< -150dBc/Hz @ 10kHz<br>< -150dBc/Hz @ 50kHz      | ■<br>■<br>■<br>■<br>■ | ■<br>■<br>■<br>■<br>■ |              |
| <b>Shock:</b><br>IEC 68-2-27 Test Ea<br>50G for 11ms   | ■                     | ■                     |              |
| <b>Vibration:</b><br>IEC 68-2-06 Test Fc<br>10-55Hz, 1.5mm. 55-500Hz, 10G  | ■                     | ■                     |              |

■ Standard. □ Optional - Please specify required code(s) when ordering

## Ordering Information

Part No, or product name + option codes + frequency  
eg: **HCD310/BNDN 10.0MHz**

**HCD311/AMFP 20.0MHz**

Option code X (eg HCD310/X) denotes a custom specification.

♦ See HCD210 for chassis-mounted version of HCD310