



Smart Technology. Delivered.

# 10x10x2 DCE

## Die-Cast Enclosure Antennas

### 10X10 DCE OFFERS 900 TO 5850 MHZ OPERATION OPTIONS

The DCE series die cast aluminum enclosures from Laird are an innovative antenna system which gives the operator ultimate system flexibility. The die-cast enclosure is available as a stand-alone enclosure, with an integrated low-gain antenna, or with a detachable high-gain panel antenna. Antennas are wide band for spectral flexibility.

Radomes are UV resistant ASA plastic. Hardware is stainless steel. The antenna systems come with a pigtail cable with choice of connectors to adapt to any available radio equipment. There is a removable and customizable user mounting plate inside for mounting electronics. The antenna models come standard with Laird Technologies patented RJ45-ECS field replaceable ethernet connector feedthru.

The die-cast enclosure can be pole or wall mounted. A heavy duty tilt bracket is available for those installations requiring up or downtilt. Eleven (11) engineered knockouts are provided; 9 sized for N connectors and 2 sized for a cable feedthru.



### FEATURES

- 11 engineered knockouts
- Wide band antennas
- Rugged and weatherproof
- Hinged cover for easy maintenance
- IP 67 Rated
- Integrated low gain or detachable high gain antenna in variety of frequencies and gains

### MARKETS

- WiFi / WLAN / WiMAX systems
- Industrial wireless
- Mesh networks
- Wi-POP base stations
- Client antennas
- Industrial wet process electrical enclosure

SPECIFICATIONS	900-928	2400-2700	4900-5850	2400-2485/ 5150-5850
Gain (integrated antenna)	8dBi	15dBi	19dBi	12dBi at 2.4GHz, 16dBi at 5.15GHz
Gain (detachable antenna)	12dBi	19dBi	24dBi	N/A
VSWR (integrated antenna)	1.5:1	1.5:1	1.7:1	2:1
VSWR (detachable antenna)	1.5:1	1.5:1	1.5:1	N/A
Impedance	50 OHM			
Input Power	100 W			
Wind Survivability	Die-cast enclosure (150mph); Detachable antenna (125mph)			
Weight (die-cast enclosure)	5.3lb (2.4kg)			
Weight (detachable antenna)	3lb (1.4kg)			
Dimensions (inside)	254 x 254 x 51 mm (10" x 10" x 2")			
Dimensions (outside integrated antenna)	317 x 264 x 99 mm (12.5" x 10.4" x 3.9")			
Dimensions (outside detachable antenna)	410 x 371 x 32 mm (16.13" x 14.63" x 1.3")			
Dimensions (stand alone DCE enclosures)	317.5 x 264.16 x 76.2 mm (12.5" X 10.4" X 3")			
Radome	ASA			
Operational Temperature	-30°C to +75°C			
Mount Style	Wall / Mast / Tilt			

### SYSTEM ORDERING INFORMATION

DCE10D-912-NF	Die Cast Enclosure with detachable 900-928MHz 12dBi panel antenna
DCE10D-2419-NF	Die Cast Enclosure with detachable 2400-2700MHz 19dBi panel antenna
DCE10D-4924-NF	Die Cast Enclosure with detachable 4940-5850MHz 24dBi panel antenna
DCE10I-985-xxxx	Die Cast Enclosure with integrated 900-928MHz 8dBi panel antenna
DCE10I-2416-xxxx	Die Cast Enclosure with integrated 2400-2700Mhz 16dBi antenna
DCE10I-4919-xxxx	Die Cast Enclosure with integrated 4940-5850Mhz 19dBi antenna
DCE10I-2451-xxxx	Die Cast Enclosure with integrated 2400-2485MHz and 4900-5850MHz 16dBi antenna
DCE10-H-001	Hinged die-cast enclosure only

(xxxx = connector type - NF, SFMF, RSMM, MCM, MMCXP, RTNM, RMMXP, SSMB and UFL)

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941  
IAS-EUSales@lairdtech.com


Asia: +86.21.5855.0827.127  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)


## ANTENNA PATTERNS




**Integrated 10x10 902-928 MHz**




**Detachable 14x16 902-928 MHz**




**Integrated 10x10 2.4-2.7 GHz**




**Detachable 14x16 2.4-2.7 GHz**



**Integrated 10x10 4.9-5.875 GHz**




**Detachable 14x16 4.9-5.85 GHz**




## DUAL BAND PATTERNS

### 2400-2485 MHz



### 5150-5850 MHz



### ANT-DS-10x10-DCE 09115

Any information furnished by Laird, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.