


Features

- High switching speed: max. 4 ns
- Continuous reverse voltage: max. 75 V
- Repetitive peak reverse voltage: max. 100 V
- Repetitive peak forward current: max. 225 mA



Mechanical Data

- **Case:** DO-35 Glass Case
- **Weight:** approx. 0.13g

DO-35		
Dim	Min	Max
A	25.40	—
B	—	4.00
C	—	0.60
D	—	2.00
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics @ T_A = 25°C unless otherwise specified

Parameter	Symbol	Value	Unit			
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	100	V			
Maximum Continuous Reverse Voltage	V _{RM}	75	V			
Maximum Continuous Forward Current	I _F	75	mA			
Maximum Power Dissipation	P _D	250	mW			
Maximum Repetitive Peak Forward Current	I _{FRM}	225	mA			
Maximum Non-repetitive Peak Forward Current at t = 1s	I _{FSM}	0.5	A			
Maximum Junction Temperature	T _J	175	°C			
Storage Temperature Range	T _S	-65 to + 200	°C			
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Current	I _R	V _R = 20 V	-	-	25	nA
		V _R = 20 V, T _J = 150 °C	-	-	50	μA
Forward Voltage	V _F	I _F = 10 mA	-	-	1.0	V
		I _F = 20 mA	-	-	1.0	V
		I _F = 5 mA	0.62	-	0.72	V
		I _F = 100 mA	-	-	1.0	V
Diode Capacitance	C _d	f = 1MHz ; V _R = 0	-	-	4.0	pF
Reverse Recovery Time	T _{rr}	I _F = 10 mA to I _R = 60 mA R _L = 100 Ω ; measured at I _R = 1mA	-	-	4	ns



FIG. 1 MAXIMUM PERMISSIBLE CONTINUOUS FORWARD CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE.




FIG. 2 TYPICAL FORWARD VOLTAGE




FIG. 3 TYPICAL DIODE CAPACITANCE AS A FUNCTION OF REVERSE VOLTAGE




FIG. 4 TYPICAL REVERSE CURRENT VERSUS JUNCTION TEMPERATURE

