


## 150mA DUAL LDO REGULATOR

### ■ DESCRIPTION

The UTC **LR8XXYY** Series are a low dropout regulator with high output voltage accuracy, low quiescent current, low dropout, and high ripple rejection. This regulator is based on a CMOS process. Each of these regulator ICs contains dual LDO regulator, both of them includes a voltage reference, an error amplifier, resistors for setting Output Voltage, a current limit circuit, and a chip enable circuit.

The UTC **LR8XXYY** Series exhibit ultra excellent line transient response and load transient response, thus they are very suitable for the power supply for hand-held communication equipment.



SOT-23-6  
(JDEDE TO-236)



DFN-6(1.6x1.6)


### ■ FEATURES

- \* Supply Current: TYP. 40 $\mu$ A (VR1, VR2)
- \* Standby Mode: TYP. 0.1 $\mu$ A (VR1, VR2)
- \* Low Dropout Voltage: TYP. 0.22V ( $I_{OUT}$ =150mA,  $V_{OUT}$ =2.8V)
- \* High Ripple Rejection: TYP. 70dB (f=1kHz), TYP. 65dB (f=10kHz)
- \* High Output Voltage Accuracy:  $\pm 1.0\%$
- \* Low Temperature-Drift Coefficient of Output Voltage:  
TYP.  $\pm 80\text{ppm}/^{\circ}\text{C}$
- \* Excellent Line Regulation: TYP. 0.02%/V
- \* Built-in Fold Back Protection Circuit TYP. 40mA  
(Current at short mode)
- \* Ceramic capacitors are recommended to be used with this IC  
0.22 $\mu$ F or more

### ■ ORDERING INFORMATION

Ordering Number	Package	Packing
LR8XXYYBG-AE6-R	SOT-23-6	Tape Reel
LR8XXYYBG-K06-1616-R	DFN-6(1.6×1.6)	Tape Reel


Note: XXYY: Output Voltage, refer to Marking Information.

 LR8XXYYBG-AE6-R	(1) Packing Type (2) Package Type (3) Green Package (4) Discharge Function (5) Voltage Code at $V_{OUT2}$ (6) Voltage Code at $V_{OUT1}$	(1) R: Tape Reel (2) AE6: SOT-23-6, K06-1616: DFN-6(1.6×1.6) (3) G: Halogen Free and Lead Free (4) B: without auto-discharge function at off state (5) YY: refer to Marking Information (6) XX: refer to Marking Information
--------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### ■ MARKING INFORMATIONS

PACKAGE	VOLTAGE CODE				MARKING
	CODE	X	CODE	Y	
SOT-23-6	1	1.2V	1	1.2V	<p>6 5 4 EXYB 1 2 3</p> <p>Voltage Code at V<sub>OUT1</sub> → Voltage Code at V<sub>OUT2</sub></p>
	2	1.5V	2	1.5V	
	3	1.8V	3	1.8V	
	4	2.0V	4	2.0V	
DFN-6(1.6×1.6)	5	2.5V	5	2.5V	<p>XYB 1 2 3</p> <p>Voltage Code at V<sub>OUT1</sub> → Voltage Code at V<sub>OUT2</sub></p>
	6	2.8V	6	2.8V	
	7	3.0V	7	3.0V	
	8	3.3V	8	3.3V	
	9	3.6V	9	3.6V	


### ■ PIN CONFIGURATION



### ■ PIN DESCRIPTION

PIN NO.		PIN NAME	DESCRIPTION
SOT-23-6	DFN-6(1.6×1.6)		
1	3	CE1	Chip Enable Pin 1 ("H" Active)
2	2	V <sub>DD</sub>	Input Pin
3	1	CE2	Chip Enable Pin 2 ("H" Active)
4	6	V <sub>OUT2</sub>	Output Pin 2
5	4	GND	Ground Pin
6	5	V <sub>OUT1</sub>	Output Pin 1

## ■ BLOCK DIAGRAM



### ■ ABSOLUTE MAXIMUM RATINGS

PARAMETER		SYMBOL	RATINGS	UNIT
Input Voltage		V <sub>IN</sub>	6.0	V
Input Voltage (CE Pin)		V <sub>CE</sub>	-0.3 ~ 6.0	V
Output Voltage		V <sub>OUT</sub>	-0.3 ~ V <sub>IN</sub> +0.3	V
Output Current 1		I <sub>OUT1</sub>	180	mA
Output Current 2		I <sub>OUT2</sub>	180	mA
Power Dissipation	SOT-23-6	P <sub>D</sub>	420	mW
	DFN-6(1.6×1.6)		138	mW
Operating Temperature Range		T <sub>OPR</sub>	-40 ~ +85	°C
Storage Temperature Range		T <sub>STG</sub>	-55 ~ +125	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

### ■ ELECTRICAL CHARACTERISTICS

(V<sub>IN</sub>=Set V<sub>OUT</sub>+1.0V for V<sub>OUT</sub> options greater than 1.5V, V<sub>IN</sub>=2.5V for V<sub>OUT</sub>≤1.5V, I<sub>OUT</sub>=1mA, C<sub>IN</sub>=C<sub>OUT</sub>=0.22μF unless otherwise noted. (T<sub>A</sub>=25°C))

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Output Voltage	V <sub>OUT</sub>	T <sub>A</sub> =25°C	V <sub>OUT</sub> >2.0V	x 0.99		x 1.01	V
			V <sub>OUT</sub> ≤2.0V	-20		+20	mV
Output Current	I <sub>OUT</sub>			150			mA
Load Regulation	$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	1mA≤I <sub>OUT</sub> ≤150mA	0.8V≤V <sub>OUT</sub> <1.1V		10		
			1.1V≤V <sub>OUT</sub> <1.6V		15		
			1.6V≤V <sub>OUT</sub> <2.0V		15		
			2.0V≤V <sub>OUT</sub> ≤3.6V		15		
			V <sub>OUT</sub> =0.8V		0.63		
Dropout Voltage	V <sub>DIF</sub>	I <sub>OUT</sub> =150mA	V <sub>OUT</sub> =0.9V		0.55		
			1.0V≤V <sub>OUT</sub> <1.2V		0.50		
			1.2V≤V <sub>OUT</sub> <1.4V		0.42		
			1.4V≤V <sub>OUT</sub> <1.7V		0.37		
			1.7V≤V <sub>OUT</sub> <2.1V		0.30		
			2.1V≤V <sub>OUT</sub> <2.5V		0.25		
			2.5V≤V <sub>OUT</sub> <3.0V		0.23		
			3.0V≤V <sub>OUT</sub> ≤3.6V		0.21		
Supply Current	I <sub>SS</sub>	I <sub>OUT</sub> =0mA		50	60	μA	
Supply Current (Standby)	I <sub>STANDBY</sub>	V <sub>CE</sub> =0V		0.1			μA
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	Set V <sub>OUT</sub> +0.5V≤V <sub>IN</sub> ≤5.0V		0.02			%/V
Ripple Rejection	RR	f=1kHz, Ripple 0.2Vp-p, V <sub>IN</sub> =Set V <sub>OUT</sub> +1.0V, I <sub>OUT</sub> =30mA (In case V <sub>OUT</sub> ≤2.0V, V <sub>IN</sub> =3.0V)		70			dB
Input Voltage (Note 1)	V <sub>IN</sub>				5.25		V
Output Voltage Temperature Coefficient	$\frac{\Delta V_{OUT}}{\Delta T_{OPT}}$	-40°C≤Ta≤85°C		±80			ppm
Short Current	I <sub>LIM</sub>	V <sub>OUT</sub> =0V		40			mA


■ ELECTRICAL CHARACTERISTICS (Cont.)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
CE Pull-down Current	$I_{PD}$				0.3		$\mu A$
CE Input Voltage "H"	$V_{CEH}$			1.0			V
CE Input Voltage "L"	$V_{CEL}$				0.4		V
Output Noise	en	BW=10Hz ~ 100kHz			60		$\mu V_{rms}$
Nch ON Resistance For Auto Discharge (B/C/E Version Only)	$R_{LOW}$	$V_{IN}=4.0V, V_{CE}=0V$	C Ver. (VR2) Others		10 50		$\Omega$

Notes: 1. The specification in **boldface** is checked and guaranteed by design engineering.

2. All of unit are tested and specified under load conditions such that  $T_J \approx T_A = 25^\circ C$  except for Output Noise, Ripple Rejection and Output Voltage Temperature Coefficient items.
3. The maximum Input Voltage of the ELECTRICAL CHARACTERISTICS is 5.25V. In case of exceeding this specification, the IC must be operated on condition that the Input Voltage is up to 5.5V and the total operating time is within 500hrs.

- TYPICAL APPLICATION CIRCUIT



$C_{IN}=C_{OUT1}=C_{OUT2}=\text{Ceramic } 0.22\mu\text{F}$

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.