

Great value DDR2 for desktops and notebooks: U-DIMM/SO-DIMM

ADATA 800MHz/667MHz DDR2 memory is available in U-DIMM and SO-DIMM form factors, accommodating desktops and notebooks. Modules deliver double data rate SDRAM bolstered by FBGA (Fine-pitch Ball Grid Array) packaging on a 240-pin/204-pin (U-DIMM/SO-DIMM) glass-epoxy printed circuit board. Running at 1.8V and 800MHz, transmission bandwidth reaches 6,400MB/s in the PC2-6400 specification. With 667MHz clocks, transmission bandwidth goes up to 5,300MB/s in the PC2-5300 specification.



Features

- High speed up to 800MHz
- Transfer bandwidths up to 6.4GB/s
- 6-layer PCB provides improved signal transfer and system stability

U-DIMM



SO-DIMM



Specifications

Type	DDR2 800 U-DIMM	DDR2 667 U-DIMM	DDR2 667 SO-DIMM	DDR2 800 SO-DIMM
Form factor	Standard	Standard	Standard	Standard
Suitable for	Desktop	Desktop	Notebook	Notebook
Interface	240-pin	240-pin	200-pin	200-pin
Capacity	1GB/2GB	1GB/2GB	1GB/2GB	1GB/2GB
Rank	Single / Dual	Single / Dual	Single / Dual	Single / Dual
Speed	800MHz	667MHz	800MHz	667MHz
VDD voltage	1.8V			
CAS latency	CL5			
Refresh	Auto-refresh / self-refresh			
Operating temperature	0°C-85°C			
RoHS	Yes			
Standard	JEDEC			
Warranty	Limited lifetime warranty			

Ordering Information

Product	Capacity	Rank	Voltage	Data rate	Speed	CL	Part number
DDR2 800 U-DIMM	1GB	Single	1.8V	800MT/s	PC2-6400	CL = 5	AD2U800B1G5
	2GB	Dual	1.8V	800MT/s	PC2-6400	CL = 5	AD2U800B2G5
DDR2 667 U-DIMM	1GB	Single	1.8V	667MT/s	PC2-5300	CL = 5	AD2U667B1G5
	2GB	Dual	1.8V	667MT/s	PC2-5300	CL = 5	AD2U667B2G5
DDR2 800 SO-DIMM	1GB	Single	1.8V	800MT/s	PC2-6400	CL = 5	AD2S800B1G5
	2GB	Dual	1.8V	800MT/s	PC2-6400	CL = 5	AD2S800B2G5
DDR2 667 SO-DIMM	1GB	Single	1.8V	667MT/s	PC2-5300	CL = 5	AD2S667B1G5
	2GB	Dual	1.8V	667MT/s	PC2-5300	CL = 5	AD2S667B2G5