

# SKM350MB120SCH15



SEMITRANS® 3

## SiC MOSFET Module

### SKM350MB120SCH15

#### Target Data

#### Features


- Full Silicon Carbide (SiC) power module
- Latest generation SiC MOSFETs
- Optimized for fast switching and lowest power losses
- Insulated copper baseplate using DBC technology (Direct Bonded Copper)
- Improved thermal performances with Aluminium Nitride (AlN) substrate
- UL recognized, file no. E63532

#### Typical Applications\*

- High frequency power supplies
- AC inverters

#### Remarks

- Case temperature limited to  $T_c=125^\circ\text{C}$  max.
- Recommended  $T_{jop} = -40\dots+150^\circ\text{C}$



MB

Absolute Maximum Ratings				
Symbol	Conditions	Values	Unit	
<b>MOSFET</b>				
$V_{DSS}$		1200	V	
$I_D$	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	523	A
		$T_c = 80^\circ\text{C}$	416	A
$I_{DM}$		1280	A	
$V_{GS}$		-6 ... 22	V	
$T_j$		-40 ... 175	$^\circ\text{C}$	
<b>Integrated body Diode</b>				
$I_{FM}$			A	

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
<b>Module</b>			
$I_{t(RMS)}$		500	A
$T_{stg}$		-40 ... 125	$^\circ\text{C}$
$V_{isol}$	AC sinus 50 Hz, $t = 1$ min	4000	V

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>MOSFET</b>					
$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 8\text{ mA}$	1200			V
$V_{GS(th)}$	$V_{GS} = V_{GS}, I_D = 71.2\text{ mA}$	1.6		4	V
$I_{DSS}$	$V_{GS} = 0\text{ V}, V_{DS} = 1200\text{ V}, T_j = 25^\circ\text{C}$			0.08	mA
$I_{GSS}$	$V_{GS} = 22\text{ V}, V_{DS} = 0\text{ V}$			600	nA
$R_{DS(on)}$	$V_{GS} = 18\text{ V}$ $I_D = 176\text{ A}$	$T_j = 25^\circ\text{C}$	5.6	7.0	m $\Omega$
		$T_j = 150^\circ\text{C}$	9.5		m $\Omega$
$C_{iss}$	$V_{GS} = 0\text{ V}$		34.48		nF
$C_{oss}$	$V_{DS} = 800\text{ V}$		1.096		nF
$C_{rss}$	$f = 1\text{ MHz}$		0.152		nF
$Q_G$	$V_{GS} = 18\text{ V}$		1512		nC
$R_{Gint}$	$T_j = 25^\circ\text{C}$		0.6		$\Omega$
$t_{d(on)}$	$V_{DD} = 600\text{ V}$ $I_D = 250\text{ A}$ $V_{GS} = -6 \dots 20\text{ V}$	$T_j = 150^\circ\text{C}$			ns
$t_r$		$T_j = 150^\circ\text{C}$			ns
$t_{d(off)}$		$T_j = 150^\circ\text{C}$			ns
$t_f$		$T_j = 150^\circ\text{C}$			ns
$E_{on}$		$T_j = 150^\circ\text{C}$		10.3	
$E_{off}$	$T_j = 150^\circ\text{C}$		4.7		mJ
$R_{th(j-c)}$				0.05	K/W
$R_{th(c-s)}$			0.03		K/W
<b>Integrated body Diode</b>					
$V_F = V_{SD}$	$V_{GS} = 0\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	6.40		V
		$T_j = 150^\circ\text{C}$	5.20		V
$V_{F0}$	chipelevel	$T_j = 25^\circ\text{C}$	3.9		V
		$T_j = 150^\circ\text{C}$	3.4		V
$r_F$	chipelevel	$T_j = 25^\circ\text{C}$	6.25		m $\Omega$
		$T_j = 150^\circ\text{C}$	4.5		m $\Omega$
$t_{rr}$					$\mu\text{s}$
$Q_{rr}$					$\mu\text{C}$
$I_{rr}$	$V_{GS} = -6 \dots 20\text{ V V}$				A
$E_{rr}$					mJ

# SKM350MB120SCH15



**SEMITRANS® 3**

## SiC MOSFET Module

### SKM350MB120SCH15

#### Target Data

#### Features

- Full Silicon Carbide (SiC) power module
- Latest generation SiC MOSFETs
- Optimized for fast switching and lowest power losses
- Insulated copper baseplate using DBC technology (Direct Bonded Copper)
- Improved thermal performances with Aluminium Nitride (AlN) substrate
- UL recognized, file no. E63532


#### Typical Applications\*

- High frequency power supplies
- AC inverters

#### Remarks



- Case temperature limited to  $T_c=125^{\circ}\text{C}$  max.
- Recommended  $T_{jop} = -40\dots+150^{\circ}\text{C}$

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>Module</b>					
$L_{CE}$			15		nH
$R_{CC'+EE'}$	measured per switch,		0.55		mΩ
$R_{th(c-s)1}$	per module		0.015		K/W
$R_{th(c-s)2}$	including thermal coupling, Ts underneath module		0.0237		K/W
$M_s$	to heat sink M6	3		5	Nm
$M_t$					Nm
	to terminals M6	2.5		5	Nm
					Nm
w				325	g



**MB**

# SKM350MB120SCH15



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

## **\*IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.