

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0348033211](#)  
**Status:** **Active**  
**Overview:** [Stac64 Single, Multi-Pocket and Hybrid Header System](#)  
**Description:** [CTX64 Female Terminal, Tin, S-Grip, D-Wind, Left Payoff, SAE 22](#)

**Documents:**

<a href="#">Drawing (PDF)</a>	<a href="#">Packaging Specification PK-31301-053 (PDF)</a>
<a href="#">Product Specification PS-502306-001-001 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>
<a href="#">Application Specification AS-502306-002-001 (PDF)</a>	<a href="#">Product Literature (PDF)</a>

**General**

Product Family	Crimp Terminals
Series	<a href="#">34803</a>
Application	Signal
Crimp Quality Equipment	Yes
Overview	<a href="#">Stac64 Single, Multi-Pocket and Hybrid Header System</a>
Product Literature Order No	987650-4561
Product Name	CTX64
UPC	887191519272

**Physical**

Gender	Female
Grip Code	S
Material - Metal	Copper Alloy
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.114/g
Packaging Type	Reel
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.10 to 1.65mm
Wire Size AWG	22
Wire Size mm <sup>2</sup>	0.22-0.35

**Electrical**

Current - Maximum per Contact	1.5A
Voltage - Maximum	14V DC

**Material Info**

**Reference - Drawing Numbers**

Application Specification	AS-502306-002-001
Packaging Specification	PK-31301-053
Product Specification	PS-502306-001-001
Sales Drawing	SD-31301-053, SD-34803-002-001



*Series image - Reference only*

**EU ELV**

**Compliant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per  
-ED/01/2018 (15  
January 2018)

**Halogen-Free**

**Status**

**Low-Halogen**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS	Green Image
ELV	Compliant
RoHS Phthalates	Not Contained

**Search Parts in this Series**

[34803](#) Series

**Use With**

[34729](#) 2.54mm Pitch Stac64 Right Angle Receptacle