


MATERIALS

BODY	BRASS NICKEL PLATED
CONTACT (M)	GOLD PLATED
CONTACT (F)	SILVER PLATED
INSULATOR	PTFE



SPECIFICATIONS

FREQUENCY RANGE: DC TO 1,000 MHz
 IMPEDANCE: 50 OHMS
 VSWR: 1.50:1 MAXIMUM

FUSE ELEMENT: 1/4 AMP

FUSE LEVEL: +35 dBm



PASTERNACK ENTERPRISES, INC.
 P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

DWG TITLE		DES.			
PE7300-3		N FUSE HOLDER, FREQUENCY RANGE: DC TO 1,000 MHz			
SIZE A	FSCM NO. 53919	CAD FILE 080902	SCALE N/A	127	

- NOTES:**
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 - ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.